Cold Weld HC-40
.600 Reference Blank Diameter

Part Description	Flange Dia.	Glass	Post/Lead Dia.	Grd. Pin	No. of Lead(s)	Lead Lgth. (+/015)	Mount Information			
							Туре	Max. Ht.	Thk. x Wdth.	Temp. & Mat'l.
CW-40-B-VN646C	.810	Natural	.040	Yes	5	.281	3 Pt. V-Clip	.185	.006 x .046	Ni. 200, As Rolled
CW-40-BW-C-VN330A	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. V-Clip	.185	.003 x .030	Ni. 200, 1/2 Hard
CW-40-BW-C-VN530A	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. V-Clip	.185	.005 x .030	Ni. 200, 1/2 Hard
CW-40-BW-C-VN550A	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. V-Clip	.185	.005 x .050	Ni. 200, 1/2 Hard
CW-40-BW-C-CMN550A	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. Claw Mount	.160	.005 x .050	Ni. 200, 1/2 Hard
CW-40-BW-C-CMN550B	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. Claw Mount	.137	.005 x .050	Ni. 200, 1/2 Hard
CW-40-BW-C-CMN550C	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. Claw Mount	.160	.005 x .050	Ni. 200, 1/2 Hard
CW-40-BW-D-VN646C	.810	Natural	.040 / .019	Yes	5	1.015	3 Pt. V-Clip	.185	.006 x .046	Ni. 200, As Rolled
CW-40-BW-D-VN646D	.810	Natural	.040 / .019	Yes	5	1.015	3 Pt. V-Clip	.145	.006 x .046	Ni. 200, As Rolled
CW-40-BW-C-VN646C	.810	Natural	.040 / .019	Yes	5	1.015	3 Pt. V-Clip	.185	.006 x .046	Ni. 200, As Rolled
CW-40-BW-C-VN646A	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. V-Clip	.185	.006 x .046	Ni. 200, As Rolled
CW-40-BW-C-VN646M	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. V-Clip	.145	.006 x .046	Ni. 200, As Rolled
CW-40-BW-C-VN646P	.810	Natural	.040 / .019	Yes	5	1.015	4 Pt. V-Clip	.185	.006 x .046	Ni. 200, As Rolled