

# Solder Seal .950 x .950 Disscreeet Package (Pin Grid. Pattern .750x.750)

Part Description	Header Information								
	Post Ht. & Post Dia.	Posts	Lead Lgth. & Lead Dia.	Leads	Insulated Pin Position	Grd. Pin Position	S.O. Ht. +/- .005 & Grid. Pattern	S.O.	Header Mat'l.
DC-950-E	.485+/- .010 (.018) Flush .095+/- .005 (.018)	2 2 5	.250+/- .010 (.018)	9	13 & 19 Thru 2 & 6 Leads Only 1,4,7,15 & 17 Thru	4 Thru	N/A	N/A	C.R.S.
DC-950-M	.550+/- .010 (.030)	5	.250+/- .010 (.030)	5	1,7,13 & 19 Thru	4 Thru	Inline Grid 2,6,15 & 17 .025+/- .005	4	C.R.S.
DC-950-P	.390+/- .010 (.030)	5	.250+/- .010 (.030)	5	1,7,13 & 19 Thru	4 Thru	Inline Grid 2,6,15 & 17 .025+/- .005	4	C.R.S.
DC-950-S	.250+/- .010 (.030)	5	.250+/- .010 (.030)	5	1,7 & 13 Thru	6 & 19 Thru	Inline Grid 2,4,15 & 17 Glass In Holes	4	C.R.S.