

Resistance Weld HC-52 Hook Mounts or C-Clip

Part Description	Post/Lead Dia. & Lead Lgth.	Grd. Pin	Mount Information					
			Center Lead Type & Ht.	Contact Area Dim.	Mount To Mount	Mount Ht.	Thk. x Wdth.	Temp. & Mat'l.
RR-45-HM09-12	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Slot & .020 R.	.170+/- .015	.115+/- .015	.003 x .030	C770, Full Hard
RR-45-015A-HM09-6 B.197	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-015A-HM09-1 B.216	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Slot & .020 R.	.216+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-A-HM05-1 B.216	.019 (2 Plcs.) .520+/- .020	No	N/A	.011 Slot & .020 R.	.216+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-A-HM09-1 B.216	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Slot & .020 R.	.216+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-A-HM09-6 B.197	.019 (2 Plcs.) .520+/- .020	No	N/A	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-CGFTF-HM09-6 B.197	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush Tack Fork .035 SH	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-CGFTF-HM09-1 B.216	.019 (3 Plcs.) .520+/- .020	Yes	Center Grd. Flush Tack Fork .035 SH	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-CIF-HM09-6 B.197	.019 (3 Plcs.) .520+/- .020	No	Center Insulated Fork .037 SH	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-CIF-HM09-1 B.216	.019 (3 Plcs.) .520+/- .020	No	Center Insulated Fork .037 SH	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard
RR-45-HM017-6 B.196	.019 (2 Plcs.) .520+/- .020	No	N/A	.011 Slot & .020 R.	.196+/- .015	.135+/- .015	.003 x .030	S.S. 301, Spring Hard
RR-45-HM017-1 B.216	.019 (2 Plcs.) .520+/- .020	No	N/A	.011 Slot & .020 R.	.216+/- .015	.135+/- .015	.003 x .030	S.S. 301, Spring Hard
RR-45-TF-HM09-6 B.197	.019 (2 Plcs.) .520+/- .020	Fork Only	Tack Fork Grd. .035 SH	.005 Slot & .020 R.	.197+/- .015	.135+/- .015	.003 x .030	C770, Full Hard C770, Full Hard
RR-45-TF-HM09-1 B.216	.019 (2 Plcs.) .520+/- .020	Fork Only	Tack Fork Grd. .035 SH	.005 Slot & .020 R.	.216+/- .015	.135+/- .015	.003 x .030	C770, Full Hard C770, Full Hard