

Resistance Weld .498 x .798 (14 Lead)
(D.I.L.) Dual In Line Or (D.I.P.) Dual Inline Package

Part Description	Header Information (Pin Grid. Pattern .300x.600)								
	Post Ht.	Posts	Lead Lgth.	Leads	Insulated Pin Position	Grd. Pin Position	S.O. Ht. +/- .005 & Grid. Pattern	S.O.	Header Mat'l.
RR-498798-DF	Flush .050+/- .005	10 4	.250+/- .020	14	2-6 & 9-13 Leads Only 1,8 & 14 Thru	7 Thru	N/A	N/A	C.R.S.
RR-498798-MV	.065+/- .005	14	.250+/- .020	14	1 - 14 Thru	7 Thru	.025 .150x.500 Grid.	4	C.R.S.
RR-498798-PR	Flush .205+/- .005	10 4	.250+/- .020	14	2-6 & 9-13 Leads Only 1,8 & 14 Thru	7 Thru	N/A	N/A	C.R.S.
RR-498798-PV	.050+/- .005	14	.250+/- .020	14	1-6 & 8-14 Thru	7 Thru	N/A	N/A	C.R.S.
RR-498798-V	.050+/- .005	14	.250+/- .020	14	1-6 & 8-14 Thru	7 Thru	N/A	N/A	C.R.S.