

## Cold Weld HC-45 Welded Slot Mounts or Slot Mounts

Part Description	Post/Lead Dia. & Lead Lgth.	Grd. Pin	Mount Information					
			Center Lead Type & Ht.	Contact Area Dim.	Mount To Mount	Mount Ht.	Thk. x Wdth.	Temp. & Mat'l.
CW-45-015A-WSM018A B.185	.015 (2 Plcs.) .520+/- .020	No	N/A	.011 Wd. x .075 Lg.	.185+/- .015	.143+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-WSM018A B.210	.015 (2 Plcs.) .520+/- .020	No	N/A	.011 Wd. x .075 Lg.	.210+/- .015	.141+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-WSM018F B.210	.015 (2 Plcs.) .520+/- .020	No	N/A	.011 Wd. x .075 Lg.	.210+/- .015	.124+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-WSM019A B.185	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.185+/- .015	.143+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-WSM019A B.210	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.210+/- .015	.141+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-WSM019A B.230	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	.230+/- .015	.135+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-1231 B.185	.015 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .093 Lg.	.185+/- .015	.128+/- .015	.004 x .027	Nickel Silver 1/2 Hard
CW-45-015A-1231 B.203	.015 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .093 Lg.	.203+/- .015	.126+/- .015	.004 x .027	Nickel Silver 1/2 Hard
CW-45-015A-DB001A B.212	.015 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .104 Lg.	.175 Ref. Top .212+/- .015	.141+/- .010	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB001A B.228	.015 (2 Plcs.) .520+/- .020	No	N/A	.009 Wd. x .104 Lg.	.228+/- .015	.137+/- .015	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB002A B.185	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.185+/- .015	.136+/- .010	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB002A B.196	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.196+/- .015	.135+/- .010	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB002A B.203	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.203+/- .015	.126+/- .010	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB002A B.220	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.220+/- .015	.133+/- .010	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB002B B.194	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.194+/- .015	.136+/- .010	.004 x .032	Nickel Silver 1/2 Hard
CW-45-015A-DB007A B.203	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .095 Lg.	.203+/- .015	.126+/- .010	.003 x .032	Nickel Silver 1/2 Hard
CW-45-015A-FSM019A B.185	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	Funnel Top .185+/- .015	.143+/- .015	.003 x .030	C770 Full Hard
CW-45-015A-FSM019F B.185	.015 (2 Plcs.) .520+/- .020	No	N/A	.005 Wd. x .075 Lg.	Funnel Top .185+/- .015	.126+/- .010	.003 x .030	C770 Full Hard
CW-45-015A-TF005 I/S BENT 20 DEGREES	.015 (2 Plcs.) .520+/- .020	No	N/A	.010 Wd. x .015 Dp.	Inside Post 20 Degrees Inward	Tack Fork .060+/- .005	.003 x .030	Nickel Silver 1/2 Hard
CW-45-015A-SCM018AA B.075	.015 (2 Plcs.) .520+/- .020	No	N/A	Slotted Claw Mount .011 Wd. x .073 Lg.	.125 Top Outside .100 Top Slot .075 Inside Slot	.087+/- .010	.003 x .030	C770 Full Hard