

**Resistance Weld .795 x .970
(D.I.L.) Dual In Line Or (D.I.P.) Dual Inline Package**

Part Description	Header Information (Pin Grid. Pattern .600x.700)								
	Post Ht.	Posts	Lead Lgth.	Leads	Insulated Pin Position	Grd. Pin Position	S.O. Ht. +/- .005 & Grid. Pattern	S.O.	Header Mat'l.
RR-795970-BC	.355+/- .010	6	.250+/- .020	6	1,7,9,10 & 16 Thru	8 Thru	.025 .400x.500 Grid.	4	C.R.S.
RR-795970-BG	.355+/- .010	10 6	.250+/- .020	16	2-6 & 11-15 Leads Only 1,7,9,10 & 16 Thru	8 Thru	.025 .400x.500 Grid.	4	C.R.S.
RR-795970-DA	.355+/- .010	8 8	.250+/- .020	16	2-5 & 11-14 Leads Only 1,6,7,8,10,15 & 16 Thru	9 Thru	N/A	N/A	C.R.S.
RR-795970-DC	.355+/- .010	8 8	.250+/- .020	16	2-5 & 11-14 Leads Only 1,6,7,9,10,15 & 16 Thru	8 Thru	.025 .400x.500 Grid.	4	C.R.S.
RR-795970-DE	.355+/- .010	4 12	.250+/- .020	16	1,2,5-8,10-12,15 & 16 Thru	2,3,13 & 14 Leads Only 9 Thru	N/A	N/A	C.R.S.
RR-795970-DG	.355+/- .010	16	.250+/- .020	16	1-7 & 9-16 Thru	8 Thru	N/A	N/A	C.R.S.