

Solder Seal 1.003 x 1.350 Disscreeet Package (Pin Grid. Pattern .700x1.000)

Part Description	Header Information								
	Post Ht. & Post Dia.	Posts	Lead Lgth. & Lead Dia.	Leads	Insulated Pin Position	Grd. Pin Position	S.O. Ht. +/- .005 & Grid. Pattern	S.O.	Header Mat'l.
DC-1003-1350-B	.266+/- .010 (.030)	5	.244+/- .010 (.030)	5	2,3,4 & 5 Thru	1 Thru	.600 x .700 .034+/- .005	4	C.R.S.
DC-1003-1350-E	.200+/- .010 (.030)	5	.187+/- .010 (.030)	5	2,3,4 & 5 Thru	1 Thru	.600 x .700 .026+/- .006	4	C.R.S.
DC-1003-1350-H	.633 Ref. (.030)	5	.236+/- .010 (.030)	5	2,3,4 & 5 Thru	1 Thru	.600 x .700 .025+/- .006	4	C.R.S.
DC-1003-1350-M	1.000+/- .020 (.030)	5	.201+/- .010 (.030)	5	2,3,4 & 5 Thru	1 Thru	.600 x .700 .025+/- .006	4	C.R.S.
DC-1003-1350-W	.532+/- .010 (.030)	6	.244+/- .010 (.030)	5	1,3,4 & 5 Thru	4 Thru	.600 x .700 .025+/- .006	4	C.R.S.
DC-1003-1350-Y	1.000+/- .020 (.030)	5	.312+/- .010 (.030)	5	2,3,4 & 5 Thru	2 Thru	.600 x .700 .025+/- .006	4	C.R.S.
DC-1003-1350-AB	1.000+/- .020 (.030)	5	.187+/- .010 (.030)	5	1,2,3,4 & 5 Thru	N/A	.600 x .700 .025+/- .006	4	C.R.S.
DC-1003-1350-AC	.200+/- .010 (.030)	5	.187+/- .010 (.030)	5	1,2,3,4 & 5 Thru	N/A	.600 x .700 .025+/- .006	4	C.R.S.