

Cold Weld HC-35
.268 Reference Blank Diameter

Part Description	Flange Dia.	Glass	Grd. Location & Type	No. of Lead(s)	Lead Lgth. (+/- .015)	Mount Information			
						Type	Max. Ht.	Thk. x Wdth.	Temp. & Mat'l.
CW-TO5-BX-VC009AH	.350	Opaque		3	1.520	3 Pt. V-Clip w/ Paste Hole	.120	.003 x .040	C770, Full Hard
CW-TO5-S-VC009AH	.350	Opaque		3	.615	3 Pt. V-Clip w/ Paste Hole	.120	.003 x .040	C770, Full Hard
CW-TO5-S-VC009CH	.350	Opaque		3	.615	3 Pt. V-Clip w/ Paste Hole	.090	.003 x .040	C770, Full Hard
CW-TO5-G-VC009AH	.350	Opaque		4	.615	4 Pt. V-Clip w/ Paste Hole	.120	.003 x .040	C770, Full Hard
CW-TO5-BR-VC009AH	.380	Opaque		3	.615	3 Pt. V-Clip w/ Paste Hole	.120	.003 x .040	C770, Full Hard
CW-TO5-BR-VC009CH	.380	Opaque		3	.615	3 Pt. V-Clip w/ Paste Hole	.090	.003 x .040	C770, Full Hard
CW-TO5-DN-VC009AH	.380	Opaque		4	.520	3 Pt. V-Clip w/ Paste Hole	.120	.003 x .040	C770, Full Hard
CW-TO5-H-VC009AH	.380	Opaque		3	1.015	3 Pt. V-Clip w/ Paste Hole	.120	.003 x .040	C770, Full Hard
CW-TO5-M-VC009CH	.380	Clear		3	.615	3 Pt. V-Clip w/ Paste Hole	.090	.003 x .040	C770, Full Hard