

Multi Pin Feed Thru

Part Description	Flange Dia. or O.D.	Body Dia. or I.D.	Eyelet Length	Flange Thickness	Post Ht.	# Of Posts	Lead Length	Leads	Lead Dia.	Pin Style	Spacing or Pin Circle	Header Mat'l.
FT-200-018A	0.2	0.13	0.11	0.01	3.390 Ref.	2	.070+/- .010	2	0.018	Straight Cut	.054 P.C.	C.R.S.
FT-2982-A (SQUIB)	0.298	0.256	0.335	N/A	.015+/- .005	2	.960+/- .030	2	0.03	Straight Cut	.060 P.C.	C.R.S.
FT-3102-A (SQUIB)	0.31	0.258	0.215	N/A	.020+/- .005	2	1.785 Ref.	2	0.04	Straight Cut and Full Spherical Lead	.060 P.C.	C.R.S.
FT-3112-A (SQUIB)	0.312	0.208	0.215	N/A	Flush Inside	2	1.807 Ref.	2	0.04	Straight Cut and Full Spherical Lead	.060 P.C.	C.R.S.
FT-3322-B	0.332	.292 Ref.	0.1	0.05	.150+/- .005	2	.382 Ref.	2	0.03	Straight Cut	.095 P.C.	C.R.S.
FT-3322-D	0.332	.292 Ref.	0.1	0.05	Flush	2	.120+/- .010	2	.031 O.D. .021 I.D.	Tube	.095 P.C.	C.R.S.
FT-3402-B	0.34	0.205	0.135	0.01	1.000+/- .020	2	1.000+/- .020	2	0.03	Straight Cut	.075 P.C.	Kovar
FT-3502-028A	0.35	0.205	0.135	0.01	.094 Ref. .560 Ref.	1 1	2.000+/- .062 2.000+/- .062	1 1	0.03 0.03	Straight Cut L Form Post	.075 P.C.	Kovar
FT-3502-030B	0.35	0.205	0.135	0.01	.0625+/- .0100	2	2.000+/- .062	2	0.03	Straight Cut	.075 P.C.	Kovar
FT-3502-030C	0.35	0.205	0.135	0.01	.094 Ref. .560 Ref.	2 1	2.000+/- .062 .0625+/- .0155	2 1	0.03 0.03	Straight Cut L Form Post	.074 P.C.	Kovar
FT-3752-A	0.375	0.218	0.125	0.015	.115+/- .005 .595+/- .010	1 1	2.000+/- .062 2.000+/- .062	1 1	0.03 0.03	Flat Straight Cut Flat L Form Post	.075 P.C.	Kovar
EA00099	0.272	0.25	0.145	N/A	.025+/- .005	2	.140+/- .010	2	0.019	Straight Cut	.125 P.C.	S.S.
EA00112D	0.512	0.428	0.135	.024 REF.	Flush	2	.130+/- .005	2	.040 O.D. .030 I.D.	Tube	.268 P.C.	S.S.