

**Resistance Weld .795 x 1.370**  
**(D.I.L.) Dual In Line Or (D.I.P.) Dual Inline Package**

Part Description	Header Information (Pin Grid. Pattern .600x1.100)								
	Post Ht.	Posts	Lead Lgth.	Leads	Insulated Pin Position	Grd. Pin Position	S.O. Ht. +/- .005 & Grid. Pattern	S.O.	Header Mat'l.
RR-7951370-AC	Flush .205+/- .008	20 4	.250+/- .020	24	2-11 & 14-23 Lead Only 1,3 & 24 Thru	12 Thru	N/A	N/A	Kovar
RR-7951370-AH	.078+/- .005	24	.250+/- .020	24	1-11 & 13-24 Thru	12 Thru	N/A	N/A	Kovar
RR-7951370-AL	.250+/- .100	5	.250+/- .020	5	1,12,13,22 & 24 Thru	Centerline 1.000 Lg. 4-40 Studs (2)	.250 Dia.x.110 Ht. Note: Grd. 4-40 Studs	2	Kovar
RR-7951370-AM	Flush .300+/- .005	4 20	.250+/- .020	24	1-11 & 13-19 Thru	20,21,22 & 23 Lead Only 12 Thru	N/A	N/A	Kovar
RR-7951370-G	.025+/- .005	24	.250+/- .020	24	1-24 Thru	N/A	N/A	N/A	Kovar
RR-7951370-P	.025+/- .005	24	.250+/- .020	24	1-12 & 14-24 Thru	13 Thru	N/A	N/A	Kovar