



Rockfast® Model 620

TOOL CHARACTERISTICS

Height	Width	Length	Weight
12.56 inch	5.11 inch	11.02 inch	5.99 lbs
320 mm	130 mm	280 mm	2.68 kg

Pressure 70 - 120 psi | 5 - 8 bar
Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness
22 ga - 12 ga



Model 620

FASTENER DATA

Pin Type	ASK- 100-0100H	ADW- 100	AKN- 100-0100HA	AKN- 100-0150HA	AKN- 100-0200HA	AKN- 100-0250HA
Wire	0.100" 2.50 mm					
Shank	Knurled					
Head	0.248" 6.3 mm					
Length	1" 25 mm	1 1/2" 38mm 2" 50 mm	1" 25 mm	1 1/2" 40 mm	2" 50 mm	2 1/2" 65 mm
Coating	Electro-galvanized		Aericoate® 1000			
Magazine Capacity	200 pins/coil					

ACTUATION & LOADING

Actuation System: Sequential Fire
Loading: Coil

AIR CONSUMPTION

@ 100 PSI

153.60 SLMP

Performance at 100 psi / 7 bar (0.7MPa)

KINETIC ENERGY

@ 100 PSI

62.82 joules | 46.33 ft-lfb

APPLICATIONS

- Face nailing HardiePanel® fiber cement siding to steel framing (ICC ES ESR-1844)
- Wood sheathing and wood structural panel diaphragms to steel framing (IAPMO ES ER-335)
- Interior drywall to steel studs 20ga and heavier
- Steel to steel fastening