



PANELFAST[®] MODEL 510A

- Engineered for the power and durability required for use with light gauge steel
- Accepts large head (nominal 5/16" diameter) pins for maximum pull over resistance
- Fingertip adjustable depth control to precisely place pin at desired depth
- Power to fasten to 20 ga to 14 ga steel at the speed of fastening to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Sequential fire actuation for accurate pin placement
- Capable of driving pins 1-1/2" to 2-1/2" long
- ET&F[®]'s most versatile tool



CONTACT & SERVICE

Our sales Agent
is available at:

P +1 321-290-8283

F +1 888-934-8837

E Richard@customzfitter.com

W www.customzfitter.com

PIN TYPE

AGS-100 PANELFAST[®] PINS

Panelfast® Model 510A

TOOL CHARACTERISTICS

| Height | Width | Length | Weight |
|------------|-----------|------------|----------|
| 11.69 inch | 5.27 inch | 10.38 inch | 6.01 lbs |
| 297 mm | 134 mm | 264 mm | 2.7 kg |

Pressure 70 - 120 psi | 5 - 8 bar
Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness
20 ga - 14 ga



Model 510A

FASTENER DATA

| Pin Type | AGS-100-0150NA | AGS-100-0200NA | AGS-100-0250NA |
|-------------------|----------------------|----------------|----------------|
| Wire | 0.100" 2.54 mm | | |
| Shank | Knurled | | |
| Head | Nominal 5/16" 8 mm | | |
| Length | 1 1/2" 39 mm | 2" 50 mm | 2 1/2" 63 mm |
| Coating | Aerico® 1000 | | |
| Magazine Capacity | 250 pins/coil | | |

ACTUATION & LOADING

Actuation System: Sequential Fire
Loading: Coil

AIR CONSUMPTION PER SHOT

0.077 SCF | 2.2 L
Performance at 87 psi / 6 bar (0.7MPa)

APPLICATIONS

- HardiePlank® fiber cement siding to steel framing (ICC ES ESR-2290)
- Wood sheathing and wood structural panel diaphragms to steel framing (IAPMO ES ER-335)
- Wood structural panel shear walls to steel framing (ICC ES ESR-1777)
- DensGlass® Gold to steel framing (ICC ES ESR-2398)
- Stucco lath to steel framing
- Rigid foam insulation to steel framing
- Vinyl siding to steel framing