




AERICO® 90



**CODE
RECOGNIZED**



- Engineered for the power and durability required for use with steel and concrete substrates
- Power to drive into poured concrete or 3/16" steel
- Last nail lockout to prevent dry firing
- Capable of driving pins 1-1/4" to 2-1/4" long
- Smooth and knurled collated pins available
- Systems approach with tools and fasteners provides single source responsibility

PIN TYPE

ASM-144 PINS, AKN-144 PINS



TOOL TYPE



Aerico® 90

TOOL CHARACTERISTICS

Height	Width	Length	Weight
18 1/2"	5 1/2"	17"	11 lbs
470 mm	140 mm	432 mm	5 kg

Pressure	120 - 180 psi 8 - 12 bar
Air consumption per shot	0.33 SCF 9.35 l Performances at 100 psi / 7 bar (0.7 MPa)
Lubricant	Non-detergent pneumatic tool lubricant
Recommended substrates	steel 14 ga to 3/16" concrete and concrete block

FASTENER DATA*:

Pin Type	ASM-144-0125P	ASM-144-0150P	AKN-144-0175P
Wire	0.140" 3.6 mm		
Shank	Smooth	Smooth	Knurled
Head	0.300" 7.6 mm		
Length	1 1/4" 32 mm	1 1/2" 39 mm	1 3/4" 45 mm
Coating	Mechanical Galvanized		
Magazine Capacity	25 pins		

**Popular sizes shown; call for additional availability*

ACTUATION & LOADING

Actuation System*	Sequential fire
Loading*	Magazine with last pin lock out

*see instruction manual

APPLICATIONS

- Wood sheathing and wood structural panel diaphragms to steel framing (IAPMO ES ER-335)
- HardiePlank® lap siding to CMU (ICC-ER 2290)
- Wood panel sub-flooring to poured concrete
- Wood nailers to steel, concrete and CMU



ET&F Fastening Systems, INC.
29019 SOLON RD.
SOLON, OHIO 44139
Tel. +1 800 248 2376
Fax +1 440 248 0423
info@ etf-fastening.com
www.etf-fastening.com

For more product details or to place an order, contact ET&F - exclusive North American Master Distributor for the BECK Fastener Group.