

# Fiberlock ShockWave 8310

# ICP Construction Inc. / Fiberlock

Version No: **8.10**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **09/06/2023** Print Date: **09/06/2023** S.GHS.USA.EN

#### **SECTION 1 Identification**

#### **Product Identifier**

Product name	Fiberlock ShockWave 8310	
Synonyms	Not Available	
Other means of identification	Not Available	

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Di	isinfectant, Virucide,	Fungicide
-----------------------------	------------------------	-----------

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc. / Fiberlock	
Address	150 Dascomb Road Andover MA 01810 United States	
Telephone	<b>Telephone</b> 978 623 9980 866 667 5119	
Fax	Not Available	
Website	www.icpgroup.com	
Email	sds@icpgroup.com	

# **Emergency phone number**

Association / Organisation	ChemTel
Emergency telephone numbers	800-255-3924
Other emergency telephone numbers	813-248-0585

# SECTION 2 Hazard(s) identification

# Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1C, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Hazardous to the Aquatic Environment Acute Hazard Category 2

#### Label elements

Hazard pictogram(s)





Signal word

Danger

# Hazard statement(s)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

Version No: **8.10** Page **2** of **10** Issue Date: **09/06/2023** 

#### Fiberlock ShockWave 8310

Toxic to aquatic life.

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) Prevention

H401

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P272	Contaminated work clothing must not be allowed out of the workplace.

#### Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P363	Wash contaminated clothing before reuse.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P330	Rinse mouth.	

#### Precautionary statement(s) Storage

P405	Store locked up.

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
68391-01-5	2.37	benzyl-C12-18-alkyldimethylammonium chloride
68956-79-6	2.37	(C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride
64-02-8	1-5	EDTA tetrasodium salt
497-19-8	1-5	sodium carbonate
84133-50-6	1-5	alcohols C12-14 secondary ethoxylated
7732-18-5	85-95	water

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# **SECTION 4 First-aid measures**

# Description of first aid measures

If this product comes in contact with the eyes:

# Eye Contact

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### If skin or hair contact occu

# Skin Contact

- Immediately flush body and clothes with large amounts of water, using safety shower if available.
- ▶ Quickly remove all contaminated clothing, including footwear.
- ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

Version No: **8.10** Page **3** of **10** Issue Date: **09/06/2023** 

#### Fiberlock ShockWave 8310

Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5 Fire-fighting measures**

#### **Extinguishing media**

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

# Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.		
Special protective equipment and precautions for fire-fighters			
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> </ul>		
Fire/Explosion Hazard	The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk.  Decomposes on heating and produces toxic fumes of:		
	carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.		

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills		Environmental hazard - contain spillage.  Clean up all spills immediately.  Avoid breathing vapours and contact with skin and eyes.  Control personal contact with the substance, by using protective equipment.
	Major Spills	Environmental hazard - contain spillage.  Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 Handling and storage**

# Precautions for safe handling Safe handling Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area.

Version No: 8.10 Page 4 of 10 Issue Date: 09/06/2023

#### Fiberlock ShockWave 8310

▶ DO NOT allow clothing wet with material to stay in contact with skin Other information

#### Conditions for safe storage, including any incompatibilities

Suitable container

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks

Storage incompatibility

None known

# SECTION 8 Exposure controls / personal protection

#### **Control parameters**

Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Not Available

#### Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
benzyl-C12-18- alkyldimethylammonium chloride	0.61 mg/m3	6.8 mg/m3	60 mg/m3
EDTA tetrasodium salt	82 mg/m3	900 mg/m3	5,500 mg/m3
EDTA tetrasodium salt	75 mg/m3	830 mg/m3	5,000 mg/m3
sodium carbonate	7.6 mg/m3	83 mg/m3	500 mg/m3

Ingredient	Original IDLH	Revised IDLH
benzyl-C12-18-alkyldimethylammonium chloride	Not Available	Not Available
(C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride	Not Available	Not Available
EDTA tetrasodium salt	Not Available	Not Available
sodium carbonate	Not Available	Not Available
alcohols C12-14 secondary ethoxylated	Not Available	Not Available
water	Not Available	Not Available

# Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating Occupational Exposure Band Limit			
EDTA tetrasodium salt	E ≤ 0.01 mg/m³			
sodium carbonate	E	≤ 0.01 mg/m³		
alcohols C12-14 secondary ethoxylated	Е	≤ 0.1 ppm		
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			

#### **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

#### Individual protection measures, such as personal protective equipment













#### Eye and face protection

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Full face shield may be required for supplementary but never for primary protection of eyes. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

#### Skin protection See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

#### Hands/feet protection

- NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
  - Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Version No: **8.10** Page **5** of **10** Issue Date: **09/06/2023** 

#### Fiberlock ShockWave 8310

	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> </ul>

#### Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 Physical and chemical properties**

Information on basic physical	and chemical properties		
Appearance	Blue		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	11.0-12.0	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	90
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	0.61

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7.Fiberlock Products and CPVC Compatibility: Manufacturers of chlorinated polyvinyl chloride (CPVC) pipe believe that it can be sensitive to or incompatible with chemicals found in many commonly used household and industrial cleaning products, coatings, adhesives and other compounds, and that those chemicals can cause stress cracks or pipe failure. Fiberlock recommends that users contact the pipe manufacturer directly before applying any Fiberlock products to the CPVC pipe.
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

Version No: 8.10 Issue Date: 09/06/2023 Page 6 of 10

#### Fiberlock ShockWave 8310

#### Information on toxicological effects The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Not normally a hazard due to non-volatile nature of product The material has NOT been classified by EC Directives or other classification systems as 'harmful by inhalation'. This is because of the lack of corroborating animal or human evidence. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Ingestion The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. The material can produce chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Skin Contact Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. Eye If applied to the eyes, this material causes severe eye damage. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Chronic Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. TOXICITY IRRITATION Fiberlock ShockWave 8310 Not Available Not Available IRRITATION TOXICITY benzyl-C12-18-alkyldimethylammonium chloride Oral (Rat) LD50: 447 mg/kg<sup>[2]</sup> Not Available TOXICITY IRRITATION (C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride Not Available Not Available TOXICITY IRRITATION Oral (Rat) LD50: 630 mg/kg<sup>[2]</sup> Eyes (rabbit): 1.9 mg EDTA tetrasodium salt Eyes (rabbit):100 mg/24h-moderate Skin (rabbit):500 mg/24h-moderate \*[BASF] TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg[2] Eye (rabbit): 100 mg/24h moderate Eye (rabbit): 100 mg/30s mild Oral (Rat) LD50: 2800 mg/kg<sup>[2]</sup> sodium carbonate Eye (rabbit): 50 mg SEVERE Eye: adverse effect observed (irritating) $^{[1]}$ Skin (rabbit): 500 mg/24h mild Skin: no adverse effect observed (not irritating)<sup>[1]</sup> TOXICITY IRRITATION alcohols C12-14 secondary ethoxylated Not Available Not Available TOXICITY IRRITATION water Oral (Rat) LD50: >90000 mg/kg[2] Not Available 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise Legend:

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

# **EDTA TETRASODIUM SALT**

\* Sigma Aldrich - for the dihydrate

For ethylendiaminetetraacetic acid (EDTA) and its salts:

EDTA is a strong organic acid, with a high affinity for alkaline-earth ions (for example, calcium and magnesium) and heavy-metal ions (such as lad and mercury), resulting in highly stable chelate complexes. The ability of EDTA to complex is used commercially to either promote or inhibit chemical reactions, depending on application. EDTA and its salts are expected to be absorbed by the lungs and the gastrointestinal tract; absorption through skin is unlikely. They cause mild skin irritation, and severe eye irritation.

Version No: 8.10 Page 7 of 10 Issue Date: 09/06/2023

#### Fiberlock ShockWave 8310

#### For sodium carbonate: Sodium carbonate has little potential for skin irritation, but is irritating to the eyes. Due to its alkaline properties, irritation of the airways is also possible. SODIUM CARBONATE There is no data available for animal studies regarding the repeated dose toxicity of sodium carbonate by any route. There is no evidence that sodium carbonate causes whole-body effects under normal handling and use The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products. Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers. The oxidization products also cause irritation. Humans have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents and other cleaning products. Exposure to these chemicals can occur through swallowing, inhalation, ALCOHOLS C12-14 SECONDARY ETHOXYLATED or contact with the skin or eyes. Studies of acute toxicity show that relatively high volumes would have to occur to produce any toxic response Both laboratory and animal testing has shown that there is no evidence for alcohol ethoxylates (AEs) causing genetic damage, mutations or cancer. No adverse reproductive or developmental effects were observed. Tri-ethylene glycol ethers undergo enzymatic oxidation to toxic alkoxy acids. They may irritate the skin and the eyes. At high oral doses, they may cause depressed reflexes, flaccid muscle tone, breathing difficulty and coma Fiberlock ShockWave 8310 & BENZYL-C12-18-Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to **ALKYLDIMETHYLAMMONIUM CHLORIDE &** a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to (C12-18)ALKYLDIMETHYL(ETHYLBENZYL)AMMONIUM high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways CHLORIDE & EDTA TETRASODIUM SALT & SODIUM disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a CARBONATE documented exposure to the irritant. The following information refers to contact allergens as a group and may not be specific to this product. Fiberlock ShockWave 8310 & EDTA TETRASODIUM Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce BENZYL-C12-18-ALKYLDIMETHYLAMMONIUM severe ulceration. CHLORIDE & Alkyldimethylbenzylammonium chlorides are in the list of dangerous substances of council directive, classified as (C12-18)ALKYLDIMETHYL(ETHYLBENZYL)AMMONIUM 'harmful in contact with skin and on ingestion', and 'corrosive and very toxic to aquatic organisms'. It can cause dose CHLORIDE dependent skin and eye irritation with possible deterioration of vision, possible sensitisation in those with pre-existing eczema. It does not cause cancer, genetic defect, foetal or developmental abnormality. (C12-18)ALKYLDIMETHYL(ETHYLBENZYL)AMMONIUM CHLORIDE & ALCOHOLS C12-14 SECONDARY No significant acute toxicological data identified in literature search. **ETHOXYLATED & WATER Acute Toxicity** Carcinogenicity Reproductivity Skin Irritation/Corrosion Serious Eye Damage/Irritation STOT - Single Exposure Respiratory or Skin × STOT - Repeated Exposure sensitisation Aspiration Hazard Mutagenicity

Legend:

★ - Data either not available or does not fill the criteria for classification

Data available to make classification

#### **SECTION 12 Ecological information**

oxicity									
Fiberlock ShockWave 8310	Endpoint Test Duration (hr)		s	Species		Value		Source	
	Not Available	Not Available	N	lot Available	Not Av	railable	Not Avail	able	
benzyl-C12-18-alkyldimethylammonium	Endpoint Test Duration (hr)			Species		llue	Sou	rce	
chloride	LC50	96h		Fish	0.1	163mg/L	4		
(C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride	Endpoint	pint Test Duration (hr) Speci		Species	s Value		Source		
	Not Available Not Available Not Available Not Available		ilable Not Available						
	Endpoint	Test Duration (hr)	Species	Species		Value	Source		
	EC50	72h	Algae or other aquatic plants		ts	1.01mg/l	1		
EDTA tetrasodium salt	EC50	48h	h Crustacea			>100mg/l	2		
	LC50	96h Fish			>500mg/l	Not Available			
	NOEC(ECx)	72h	72h Algae or other aquatic plants		0.39mg/l	1			
	Endpoint	Test Duration (hr)	Species			Value		Source	
sodium carbonate	EC50	72h	-	other aquatic plant	S	>800mg/l		2	
	EC50	48h	Crustacea	a		156.6-298.9	mg/l	4	
	EC50	96h	Algae or o	Algae or other aquatic plants 242mg/l			4		

Version No: 8.10 Page 8 of 10 Issue Date: 09/06/2023

#### Fiberlock ShockWave 8310

	NOEC(ECx)	48h	Fish		img/l 4
	LC50 96h		Fish	300mg	/I 4
alcohols C12-14 secondary ethoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available Not Available		Not Available	Not Available	Not Available
water	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
sodium carbonate	LOW	LOW	
water	LOW	LOW	

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
sodium carbonate	LOW (LogKOW = -0.4605)

#### Mobility in soil

Ingredient	Mobility
sodium carbonate	HIGH (KOC = 1)

# **SECTION 13 Disposal considerations**

### Waste treatment methods

Product / Packaging disposal

- Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible

#### Otherwise:

If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

- DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
- Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
- Nonrefillable containers. Do not reuse or refill

#### **SECTION 14 Transport information**

#### Labels Required

Marine Pollutant

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

labels and markings in accordance with applicable transport regulations.

Not Applicable

Version No: **8.10** Page **9** of **10** Issue Date: **09/06/2023** 

#### Fiberlock ShockWave 8310

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group	
benzyl-C12-18-alkyldimethylammonium chloride	Not Available	
(C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride	Not Available	
EDTA tetrasodium salt	Not Available	
sodium carbonate	Not Available	
alcohols C12-14 secondary ethoxylated	Not Available	
water	Not Available	

#### Transport in bulk in accordance with the IGC Code

Transport in bank in accordance than the lees code		
Product name	Ship Type	
benzyl-C12-18-alkyldimethylammonium chloride	Not Available	
(C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride	Not Available	
EDTA tetrasodium salt	Not Available	
sodium carbonate	Not Available	
alcohols C12-14 secondary ethoxylated	Not Available	
water	Not Available	

#### **SECTION 15 Regulatory information**

Safety, health and environmental regulations / legislation specific for the substance or mixture

benzyl-C12-18-alkyldimethylammonium chloride is found on the following regulatory lists					
US DOE Temporary Emergency Exposure Limits (TEELs)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory				
(C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride is found on the follow US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	ing regulatory lists				
EDTA tetrasodium salt is found on the following regulatory lists					
US DOE Temporary Emergency Exposure Limits (TEELs)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory				
sodium carbonate is found on the following regulatory lists					
US DOE Temporary Emergency Exposure Limits (TEELs)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory				
alcohols C12-14 secondary ethoxylated is found on the following regulatory I	ists				
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory					
water is found on the following regulatory lists					

Federal Regulations This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label: Danger. Causes irreversible eye damage and skin burns. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing/eye protection/face protection.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	
Combustible Dust	
Carcinogenicity	No
Acute toxicity (any route of exposure)	
Reproductive toxicity	
Skin Corrosion or Irritation	

Version No: **8.10** Page **10** of **10** Issue Date: **09/06/2023** 

#### Fiberlock ShockWave 8310

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Yes

Specific target organ toxicity (single or repeated exposure)

Aspiration Hazard

No

Germ cell mutagenicity

Simple Asphyxiant

Hazards Not Otherwise Classified

#### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

#### State Regulations

# US. California Proposition 65

None Reported

#### **National Inventory Status**

Mational inventory otatus		
National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (benzyl-C12-18-alkyldimethylammonium chloride; (C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride; EDTA tetrasodium salt; sodium carbonate; alcohols C12-14 secondary ethoxylated; water)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	No (alcohols C12-14 secondary ethoxylated)	
Japan - ENCS	No (benzyl-C12-18-alkyldimethylammonium chloride; (C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride)	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No ((C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride)	
Vietnam - NCI	Yes	
Russia - FBEPH	No ((C12-18)alkyldimethyl(ethylbenzyl)ammonium chloride; alcohols C12-14 secondary ethoxylated)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

# **SECTION 16 Other information**

Revision Date	09/06/2023
Initial Date	05/20/2017

# CONTACT POINT

Fiberlock Products and CPVC Compatibility: Manufacturers of chlorinated polyvinyl chloride (CPVC) pipe believe that it can be sensitive to or incompatible withchemicals found in many commonly used household and industrial cleaning products, coatings, adhesives and other compounds, and that those chemicals can cause stress cracks or pipe failure. Fiberlock recommends that users contact the pipe manufacturer directly before applying any Fiberlock products to the CPVC pipe.

# **SDS Version Summary**

Version	Date of Update	Sections Updated
7.10	09/06/2023	Physical and chemical properties - Appearance, Hazards identification - Classification, Composition / information on ingredients - Ingredients

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Powered by AuthorITe, from Chemwatch.