

Modified Carl Little Box

Roof: Called 1 X 8 (Actually 3/4" X 7 1/4") RED CEDAR


All other Lumber 1 X 6 (Actually 3/4" X 5 1/2")



Sides

Sides 12 1/2 inches long
10 degree slope

Mark-up inside to allow birds
To get foot hold when leaving



Front

Front: 12 inches long


Hole opening 1 1/2 inches and 1 1/4 inches from top.

Floor approx. 6 inches from
bottom of opening. Allow door to
swing down and not hit floor.



Back

Back 13 inches long
Bevel back 10 degrees



Guard

Wood Predator guard

3 1/2 by 3 1/2 inches.


Hole 1 1/2 inches



Floor


Floor 4 inches by 3 1/2 inches
(floor: cut to fit)

Four corners cut off
Venting and drainage



Roof

Roof 8x10 inches
(Actually 7 1/4" x 10")



Sides

Vent gap 3/8 inch
On two sides


Drill 1/4 inch hole for nail to hold
Door closed

Use 1 1/4 inch screws in all
Places except on door hinge
Use two 1 5/8 inch screws

Right or Left Side (Side you want)
Of box pivots down for
Cleaning. Right side illustrated.

May need to shave door a little to
allow easy opening/closing.

Door should clear floor when open



Right Side

Handle 6 3/4 inches by 1 inch
To open and close door.

One screw each side 1 inch from bottom
1 5/8 inches long to pivot door down.

Recommended to predrill all screws!

Stan 22Aug2015