

# VACPAK





# VACPAK

LEAF COLLECTOR • LITTER COLLECTOR • GARBAGE TRUCK

**The Patent Pending VacPak is the Only Combination Garbage Truck and Leaf/Litter Collector that Can Simultaneously Perform Compaction and Collection.**

The VacPak's packing panel produces a whopping 32,000 pounds of packing force. This provides an enormous amount of leaf collection capability in the VacPak's 18 cubic yard body. It easily outperforms the competitors' large bulky machines that have little to no compaction capabilities. The bolt-on vacuum fan and boom is easily demounted when not needed, converting the unit back to a manual side loading refuse truck. Cart tippers can be quickly mounted on either side of the VacPak to allow efficient collection of downtown areas, alleyways, rural routes, and missed stops.

## DEBRIS BODY

Volumetric Capacity: 18 CU.YD.  
Compaction Panel: Packs both leaves & refuse  
Packing Cycle: ≤ 15 Seconds  
Packing Rate: 4 CU YD/Min  
Packing Force: 32,000 lbs  
Ejection: Full Eject  
Ejection Height: 36"  
Construction: AR400 Floor and Hopper; 50,000 PSI Side Wall  
Tailgate: Bubble Design, Sealed Water Tight to 9"

## DEBRIS COLLECTION

Single Operator Collection  
Single Engine Design  
Removeable Fan & Boom  
Suction Hose Diameter: 14"  
Boom: Mounted Under Hose

Boom Reach: 13' From Cab  
Boom Drop: 4' Below Tire Line  
Boom Rotation: Hydraulic Rotary Actuator Driven  
Transport: Boom Folds to Side of Body  
Fan: 31" Hardox Steel Radial Thresher  
Fan Drive: Hydraulic Motor, Direct Drive  
Fan Mounting: OHLA, Lubricated & Cooled by Hydraulic System. No Maintenance Interval.  
Cart Tippers: Installable on Both Sides (Curb Side When Fan & Boom Removed)  
Fan Mounting: Bolt-On, Mounted inside Hopper  
Simultaneous Collection & Compaction Possible

## HYDRAULIC SYSTEM

Reservoir: 35 Gal w/ Sight Level  
Pump: Direct Drive  
Dedicated Packer & Leaf/Litter Collector Sections  
Fittings: JIC 37° and ORB  
Suction Strainer: 100 Mesh

## IN-CAB CONTROLS

Joystick w/ Switch Bank  
No PLC, Direct Link  
Collection: Joystick Boom Control, Push-to-Start Fan Switch  
Compaction: Push-to-Start Switch  
Optional: Tailgate & Ejection Control In-Cab

## CHASSIS SPECS

Cab to Axle: 152"  
Wheelbase: 220"  
Axle Ratings:  
Front Axle: 12,000 lbs  
Rear Axle: 21,000 lbs  
GVWR: 33,000 lbs  
Dual Steering  
Rear Air Suspension  
Cummins ISL  
300 HP @ 2600 RPM  
860 LB-FT @ 1300 RPM  
Allison 3500 RDS

701 PERFORMANCE DR  
CEDAR FALLS, IA 50613  
WWW.CURBTENDERSWEEPERS.COM

The logo for CURBTENDER SWEEPERS, LLC features a large, stylized red letter 'C' with a white outline. To the right of the 'C', the words 'CURBTENDER' and 'SWEEPERS, LLC' are written in a bold, red, sans-serif font. The 'C' is positioned above the 'U' in 'CURBTENDER'.