



System Contents:

- WM-5.6-DVR** - 5.6" LCD Display with DVR
- LLC-1.4** - Low Light Color Camera
- AP-T9** - 9' Telescoping/Articulating Pole
- R-FNS** - Right Angle Adapter
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- A-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.



A-CASE



AP-T9



STANDARD WALKABOUT w/DVR



LLC-1.4



(2) BAT-2

R-FNS



WBC



WUH

SYSTEM PART NUMBERS:

IAD-PSW-A9¹

DISPLAYS

- IAD= Standard WalkAbout w/DVR
- ISD= Detached WalkAbout w/DVR
- IA= Standard WalkAbout
- IS= Detached WalkAbout

POLES

- A9=9' Articulating Pole
- A14=14' Articulating Pole
- 14=14' Gooseneck Pole

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT w/DVR



STANDARD WALKABOUT



DETACHED WALKABOUT



WalkAbout III Monitor (Alternate)

WalkAbout DVR

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1 hr per GB for H.264 videos

Camera		Poles		Cases	
Model	LLC-1.4	Model	AP-T9	Model	A-CASE
Construction	Submersible enclosure with hard-coated window	Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Size	53" x 17" x 6" (135 x 43 x 15cm)
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.	Weight loaded	37 lbs. (16.8kg)
		Collapsed/ Extended Length	4ft. 3in. / 8ft. 7in. (1.3M / 2.6M)		
		Weight	6.4 lbs. (2.9kg)		



System Contents:

- WM-5.6-MON** - 5.6" LCD Display
 - LLC-1.4** - Low Light Color Camera
 - T-FNS-11** - 11' Telescoping Pole
 - BAT-2** - Two (2) NiMH Rechargeable Batteries
 - WBC** - Battery Charger (Power Supply not shown)
 - S9-CASE** - Carrying Case for wand or pole
 - W-CASE** - Carrying Case for all other components
 - WUH** - Universal Chest Harness
 - SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.



STANDARD WALKABOUT

LLC-1.4

(2) BAT-2

WBC

WUH

SYSTEM PART NUMBERS:

IA-PSW11'

DISPLAYS

- IAD= Standard WalkAbout w/DVR
- ISD= Detached WalkAbout w/DVR
- IA= Standard WalkAbout
- IS= Detached WalkAbout

POLES

- 11=11' Telescoping Pole (in S9-CASE)
- 20=20' Telescoping Pole (in S20-CASE)
- W=5' Fixed length wand (in S9-CASE)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only..

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT

STANDARD WALKABOUT w/DVR

DETACHED WALKABOUT w/DVR



WalkAbout III Monitor		WalkAbout DVR (Alternate)
Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1 hr per GB for H.264 videos

Camera		Pole		Cases	
Model	LLC-1.4	Model	T-FNS-11	Model	W-CASE
Construction	Submersible enclosure with hard-coated window	Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Stores	WalkAbout III, camera and accessories
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Articulation	1 ft. flexible gooseneck can be flexed into any position.	Size	21" x 16" x 8" (53 x 41 x 20cm)
		Collapsed/ Extended Length	4ft. / 10ft. 11 in. (1.22M / 3.33M)	Weight loaded	17 lbs. (7.7kg)
		Weight	4.1 lbs. (1.9kg)	Model	S-9 CASE
				Stores	T-FNS-11
				Construction	Soft padded carry case for pole
				Size	48" x 8" x 2" (122 x 20 x 5cm)
				Weight loaded	5 lbs. (2.7kg)

System Contents:

- WM-5.6-MON** - 5.6" LCD Display
- LLC-1.4** - Low Light Color Camera
- B-FNS** - 2' Baton
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- W-CASE** - Carrying Case for all other components
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

- Telescoping Pole**
Extended reach with either an articulating or telescoping pole. Sizes range from 5' to 20'.
- D-BAT**
Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

IA - CBW¹

DISPLAYS

- IAD= Standard WalkAbout w/DVR
- ISD= Detached WalkAbout w/DVR
- IA= Standard WalkAbout
- IS= Detached WalkAbout

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



W-CASE



STANDARD WALKABOUT



B-FNS



LLC-1.4



(2) BAT-2



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



STANDARD WALKABOUT w/DVR



DETACHED WALKABOUT w/DVR



WalkAbout III Monitor		WalkAbout DVR (Alternate)
Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1 hr per GB for H.264 videos

Camera		Pole		Cases	
Model	LLC-1.4	Model	B-FNS	Model	W-CASE
Construction	Submersible enclosure with hard-coated window	Construction	Single section fixed length fiberglass pole with foam grip	Stores	WalkAbout III, camera and accessories
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1 / .13kg)	Collars	None	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Articulation	1 foot flexible gooseneck baton can be flexed into any position	Size	21" x 16" x 8" (53 x 41 x 20cm)
		Collapsed/ Extended Length	1ft. 3in. / 2ft. 1in. (.38M / .64M)	Weight loaded	17 lbs. (7.7kg)
		Weight	1.4 lbs. (.63kg)		



System Contents:


- WM-5.6-DVR** - 5.6" LCD Display with DVR
- WPC-2.5ZCB** - 10:1 Color Zoom Camera w/Control Box
- AP-T14M** - 14' Telescoping/Articulating Pole
- R-FNS** - Right Angle Adapter
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- T-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- TRIPOD** - With bracket for WalkAbout II
- A/V Cable & Vehicle (Power Adapter not shown)

Recommended Additions:

- THC-50D Dual mode thermal camera**
Locate elevated temperature components through smoke and darkness. Switch to visible light camera for better object identification
- Videoscope**
Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).
- Baton**
2 Foot fixed length pole for access in confined spaces.
- D-BAT**
Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

IAD - USZT - A14¹



IAD= Standard WalkAbout w/DVR C=LLC-1.4 T=Tripod A9=9' Articulating Pole
 ISD=Detached WalkAbout w/DVR Z=WPC-2.5ZCB A14=14' Articulating Pole
 IA=Standard WalkAbout 14=14' Gooseneck Pole
 IS= Detached WalkAbout

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



T-CASE



AP-T14



STANDARD WALKABOUT w/DVR



R-FNS



TRIPOD



WPC-2.5ZCB



WBC



(2) BAT-2



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT w/DVR



STANDARD WALKABOUT



DETACHED WALKABOUT



WalkAbout III Monitor (Alternate)

WalkAbout DVR

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1hr per GB for H.264 videos

Camera		Poles		Cases	
Model	WPC-2.5ZCB	Model	AP-T14	Model	T-CASE
Construction	Submersible enclosure with hard-coated window	Construction	6 Section telescoping pole, 5 internal aluminum and an external fiberglass section with foam grip	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	2.5"D x 4.0"L / .66 lbs (6.3 x 10 / 30kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Size	53" x 17" x 6" (135 x 43 x 15cm)
Features	24 Bright white LED illuminated, color camera, 480 TV Lines, 5.4° to 50° FOV	Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.	Weight loaded	40 lbs. (18kg)
		Collapsed/ Extended Length	4ft. 1in. / 14ft. 1in. (1.24M / 4.29M)		
		Weight	8.1 lbs. (3.67kg)		



System Contents:

- WM-5.6-DVR** - 5.6" LCD Display with DVR
- WPC-2.5Z** - 10:1 Color Zoom Camera
- AP-T14** - 14' Telescoping/Articulating Pole
- R-FNS** - Right Angle Adapter
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- T-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle (Power Adapter not shown)

Recommended Additions:

THC-50D Dual mode thermal camera

Locate elevated temperature components through smoke and darkness. Switch to visible light camera for better object identification

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

IAD - PSW - A14Z¹

DISPLAYS

IAD= Standard WalkAbout w/DVR
ISD= Detached WalkAbout w/DVR
IA= Standard WalkAbout
IS= Detached WalkAbout

POLES

A9= 9' Articulating Pole
A14= 14' Articulating Pole
14= 14' Gooseneck Pole

CAMERAS

none= LLC-1.4
Z= WPC-2.5ZCB

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



T-CASE



AP-T14



STANDARD WALKABOUT w/DVR



R-FNS



(2) BAT-2



WPC-2.5Z



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT w/DVR



STANDARD WALKABOUT



DETACHED WALKABOUT



WalkAbout III Monitor (Alternate)

WalkAbout DVR

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1hr per GB for H.264 videos

Camera		Poles		Cases	
Model	WPC-2.5Z	Model	AP-T14	Model	T-CASE
Construction	Submersible enclosure with hard-coated window	Construction	6 Section telescoping pole, 5 internal aluminum and an external fiberglass section with foam grip	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	2.5"D x 4.0"L / .66 lbs (6.3 x 10cm / 30kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Size	53" x 17" x 6" (135 x 43 x 15cm)
Features	24 Bright white LED illuminated, color camera, 480 TV Lines, 5.4° to 50° FOV	Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.	Weight loaded	37 lbs. (16.7kg)
		Collapsed/ Extended Length	4ft. 1in. / 14ft. 1in. (1.24M / 4.29M)		
		Weight	8.1 lbs. (3.67kg)		