



**PACIFIC WESTERN LLC**  
We put it up-right.

## INDUSTRIAL AIR CIRCULATOR



30ACH fan head shown with optional 2430PB pole and base.



Available in two styles:

- Assembled head (motor-blade-guard) in one UPS-able carton optional mount in separate UPS-able carton.
- Assembled head (motor/blade/guard) and mount in one UPS-able box.

### Fan Performance

Blade Size	Fan Head	Max Amps	CFM	
			High	Low
20"	20ACHA	1.4	3500	2900
24"	24ACH	2.2	7,000	5,900
30"	30ACH	2.5	8,200	6,200

<b>Motor</b>	2-speed 1/4 HP 1Ø 120 volt ball bearing totally enclosed permanently lubricated permanent split capacitor
<b>Switch</b>	Pull chain
<b>Cord</b>	12' long 3 conductor SJT type
<b>Blade</b>	Coated steel
<b>Guard</b>	Double locking powder coat finish
<b>Fan Head Tilt</b>	Pedestal - 10° down or 28° up Wall mount - 40° down or 0° up
<b>Column Adjustment</b>	48-7/8 to 60 inches
<b>Pedestal base</b>	27" diameter steel dome
<b>Column/Base Connect</b>	5 carriage bolts

Meets OSHA standards / 1 year limited warranty.  
MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling, or suspension mount.  
Safety cable included with I-beam, ceiling and suspension mounts.

### Assembled Head Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER	SHIPPING WEIGHT
		FAN HEAD	HEAD
20"	Head	<b>20ACHA</b>	51 lbs.
24"	Head	<b>24ACH</b>	51 lbs.
30"	Head	<b>30ACH</b>	51 lbs.

### Mount Ordering Summary

ORDER NUMBER	DESCRIPTION	SHIP WT
<b>2430PB</b>	Adjustable Pedestal	35
<b>2430WG</b>	Wall Mount	5
<b>2430I</b>	I-Beam Mount	8
<b>2430C</b>	Ceiling Mount	7
<b>2430S</b>	Suspension Mount	3

### Assembled Head Uni-pack Ordering Summary

BLADE SIZE	FAN TYPE	UNIPACK ORDER#	SHIPPING WEIGHT
24"	Pedestal Fan	<b>24ACHP</b>	73 lbs.
24"	Wall Mount Fan	<b>24ACHW</b>	42 lbs.
30"	Pedestal Fan	<b>30ACHP</b>	78 lbs.
30"	Wall Mount	<b>30ACHW</b>	47 lbs.

### Optional Accessories

TYPE	ORDER NUMBER
Wheel Kit	<b>PBWK</b>
Safety Cable	<b>2430SC</b>