



TECHNICAL DATA SHEET

BITU-OX 400 PREMIER GREEN CERTIFIED MULTI-USE SOLUTION

**DISTRIBUTED BY
GREEN WAY PRODUCTS, LLC**

DESCRIPTION:

BITU-OX 400 is SCS certified biodegradable and safe for waterways* and liquefies asphalt, oil and tar instantly upon contact. It also prevents and loosens rust as well as acts as a lubricant. It will leave a protective coating to prevent future rust corrosion. It will not evaporate or freeze so can be used at any temperature.

APPLICATION:

Spray away from face and spray on most surfaces for effective tar removal and long lasting lubrication. Test in inconspicuous area before cleaning entire surface. Spray as needed to clean tough grease, tar or grime that collects to leave a lasting protective coating. Pre-spray as a release agent. Use with power washer for extreme effectiveness. Wash away excess chemical on painted surfaces.

BITU-OX IS:

- *Waterway Safe
- Non-Reactive
- Non-Carcinogenic
- Readily Biodegradable*
- Derived from Renewable Resources
- Safe to use, store and dispose of.

BITU-OX DOES NOT CONTAIN:

- Petroleum distillates
- Glycol ethers
- Terpenes
- Synthetics
- Builders & reagents
- Caustics

CAUTION: KEEP OUT OF REACH OF CHILDREN!

INHALATION: If symptomatic, move to fresh air. Consult a physician if symptoms persist.

EYE CONTACT: Flush with water for 15 minutes. Contact a physician immediately.

SKIN CONTACT: Wash material off with soap and water. Rinse with water for 15 minutes. If irritation occurs, contact a physician.

INGESTION: Give one or two glasses of water to drink. Contact a physician immediately.

SPECIFICATION DATA:

Appearance: Clear Amber Liquid

No Odor

Relative Density - N/A

Flash Point: 400°F

Boiling Point: > 400°F

pH: N/A

Specific Gravity: 0.925 ± 0.015

*Product ingredients, except for surfactants, demonstrate an acute aquatic toxicity equal to or greater than 100 mg/L. Surfactants demonstrate an aquatic toxicity of greater than or equal to 10 mg/L, but contain no products of concern and are readily biodegradable.



www.bituox.com | 1.888.442.6191