

BIOSPRAY® SURFACE SANITIZER

NO POWER NEEDED!

BioSpray® and D2 Surface Cleaner - Portable Systems for Sanitation

BioSpray surface sanitation systems from Goodway Technologies are patented, portable systems for faster, safer and more efficient surface sanitation.



SPECIFICATIONS

| | BIOSPRAY-20 | BIOSPRAY-10 | BIOSPRAY-10C | BIOSPRAY-5 |
|--------------------|---|---|---|---|
| Input Power | None. Uses internal CO ₂ cylinder | None. Uses internal CO ₂ cylinder | None. Uses internal CO ₂ cylinder | None. Uses internal CO ₂ cylinder |
| Hose Length | 20' (6 m) | 20' (6 m) | 20' (6 m) | 10' (3 m) |
| Operating Pressure | 24-26 PSI (1,6-1,7 BAR) | 24-26 PSI (1,6-1,7 BAR) | 24-26 PSI (1,6-1,7 BAR) | 25 PSI (1,7 BAR) |
| Tank | 20lb (9 Kg) CO ₂ | 10lb (4,5 Kg) CO ₂ | 10lb (4,5 Kg) CO ₂ | 5lb (2,3 Kg) CO ₂ |
| Dimensions | 44" (111,7 cm) high x 28" (71,1 cm) wide x 18" (45,7 cm) deep | 40" (101,6 cm) high x 25" (63,5 cm) wide x 16" (40,6 cm) deep | 40" (101,6 cm) high x 24" (60,9 cm) wide x 19" (48,2 cm) deep | 22" (55,9 cm) high x 16" (40,6 cm) wide x 9" (22,9 cm) deep |
| Weight | 100 lbs (45,3 Kg) | 86 lbs (39 Kg) | 82 lbs (37,1 Kg) | 30 lbs (13,6 Kg) |

Consumption Rates

- **Service Rating:** Commercial
- **Electric Power Required:** No
- **Removable CO₂ Cylinder With Patented Technology:** Yes
- **Rinse Required:** No
- **Wipe Required:** No
- **Spray Design Type:** Continuous¹, Intermittent²
- **Total Spray Time between CO₂ Refill:** 90 minutes, 45 minutes, 22 minutes

- **Formula Usage²**
 - Sanitation:** 1.07 milliliter per square foot (11,51 milliliter per square meter)
 - Disinfection:** 3.63 milliliter per square foot (39,07 milliliter per square meter)
- **Coverage Speed²**
 - Sanitation:** 2.76 seconds per square foot (29,7 seconds per square meter)

Disinfection: 3.34 seconds per square foot (39,9 seconds per square meter)
Sanitation: 1305 square feet per hour (121,2 square meter per hour)
Disinfection: 1080 square feet per hour (100,3 square meter per hour)

- **Coverage Area²**
 - Per 20 lb. (9 Kg) CO₂ tank
 - Sanitation:** 1960 square feet (182 square meter)
 - Disinfection:** 1620 square feet (150 square meter)
 - Per 1L Bottle of D2
 - Sanitation:** 935 square feet (87 square meter)
 - Disinfection:** 275 square feet (25 square meter)

¹BioSpray® BIOSPRAY-20 model is designed to be freeze-resistant with continuous spray use. Continuous spray use is defined as continuous spray time with no non-spray time and is freeze-resistant rated for continuous spraying time equal to the full contents of one CO₂ drive cylinder. ²BIOSPRAY-10 models are designed to be freeze-resistant with intermittent spray use. Intermittent spray use is defined as spray time equal to or less than non-spray time and BIOSPRAY-10 are freeze-resistant tested at intermittent spraying of at least three seconds spray and three seconds non-spray.

³Coverage speed, formula usage, area, and times are based on using BIOSPRAY-20 maximum efficiency with environmental responsibility atomizing spray gun.