A FASTER WAY TO A **GREASE, GRIME AND GERM-FREE**

CE



GVC-18000 – Continuous

Steam Power

The GVC-18000 dry steam cleaner is ideal cleaning equipment for food and beverage production facilities. The machine makes cleaning and sanitizing production and packaging equipment easier, all thanks to its powerful dry steam.

Our system delivers high pressure up to 9,9 BAR (145 PSI) and heat up to 143.3 °C (290 °F) to break down soils like fats, sugars, heavy buildup, and allergens on contact helping you to consistently deliver the results you need as part of your plant SSOPs. It also helps to kill yeast, mold, pathogenic bacteria, and other dangerous or spoilage microorganisms.

Plus, dry steam cleaning provides the benefit of targeted cleaning in dry environments, water sensitive equipment, hard to reach areas, and other challenging applications where traditional dry cleaning methods simply can't produce the results you need.

GVC-18000: Heavy-Duty Dry Steam Cleaner, including 10 meters (33') hose with pistol grip, one-piece 50 cm (20") wand with detail lance, one-piece 1 meter (40") wand with detail lance, short detail lance, four 5,7 cm (2 1/4") circular nylon brushes, four 5,7 cm (2 1/4") circular brass brushes, four 5,7 cm (2 1/4") circular stainless steel brushes, four 3,8 cm (1 1/2") circular nylon brushes, four 3,8 cm (1 1/2") circular brass brushes, four 3,8 cm (1 1/2") circular stainless steel brushes, four circular nylon scrubbing brushes, four circular brass scrubbing brushes, four circular stainless steel scrubbing brushes, multi-brush tool, safety glasses, two chemical tanks and a 3,7 liters (1

Note: Call or visit goodway.com for additional accessories.

Stainless steel construction

- In operation refillable water tank
- Continuous fill hose connection
- Stainless steel boilers and water tank
- Adjustable dry steam volume
- Steam output at 26,4-34 liters/hour (7-9 gallons/hour) (depending on moisture content)

36,000 and 72,000 Watt units also available.

Adjustable moisture content from 5-15%

- Four chemical-injection settings
- Simultaneous vacuum option available Multiple cleaning tools

	GVC-18000
Input Power	22 amps, 480V, 50/60 Hz AC, three phase Maximum 18-KW
Power Supply Cord	10m (33'), 10-4
Max. Output Steam Pressure	0 up to 9,9 BAR (145 PSI)
Max. Output Steam Temperature	143.3 °C (290 °F)
Boilers	Two 9 liters (2.4 gallons) stainless steel
Output Steam Volume	26,7 Kg (59 lbs)/hr
Water Tank	39,3 L (10.4 gallons) stainless steel
Chemical Tanks	Two 4,9 L (1.3 gallons)
Dimensions	111,7 cm (44") high x 71,1 cm (28") wide x 104,1 cm (41") deep
Weight	88 Kg (194 lbs) net dry

FEATURES

	GVC-18000
Input Power	22 amps, 480V, 50/60 Hz AC, three phase Maximum 18-KW
Power Supply Cord	10m (33'), 10-4
Max. Output Steam Pressure	0 up to 9,9 BAR (145 PSI)
Max. Output Steam Temperature	143.3 °C (290 °F)
Boilers	Two 9 liters (2.4 gallons) stainless steel
Output Steam Volume	26,7 Kg (59 lbs)/hr
Water Tank	39,3 L (10.4 gallons) stainless steel
Chemical Tanks	Two 4,9 L (1.3 gallons)
Dimensions	111,7 cm (44") high x 71,1 cm (28") wide x 104,1 cm (41") deep
Weight	88 Kg (194 lbs) net dry

INNOVATIVE MAINTENANCE SOLUTIONS

Call: +90 (0542) 131 8386 Visit: www.novachemtech.com

Nova Chemtech Hijyen Teknolojileri Ltd. Şti.

Yeşilce Mah. Yunus Emre Cad. No: 8/1 Kağıthane 34418

Istanbul-TURKIYE

Phone: +90 212 912 3223 · info@novachemtech.net

GOODBYE TO DIRT, BACTERIA AND ALLERGENS!



We've paired the convenience of mobility with the power one would expect from a stationary unit. Take on virtually any large scale cleaning project with nearly 0,9 liters (0.25 gallons) of dry saturated steam per minute.

On demand, industrial strength dry steam eliminates bacteria, viruses and microorganisms. Reduce cleaning time and lower production down time. Clean your facility to the highest level of hygiene available in the cleaning industry. Powerful enough for production lines, yet gentle on machinery and electronics.

- Bakery
- Candy & Confectionery
- Chemical Processing
- Dairy
- Dry Ingredients

- Meat & Poultry Processing
- Pharmaceutical Production
- Produce
- Seafood
- · Winery & Brewery





Your tech support, service department is 2nd to noone. Their communication skills and follow up were great." - **Bob K**

FEATURES

- Stainless steel construction
- In operation refillable water tank
- Continuous fill hose connection
- Stainless steel boilers and water tank
- Adjustable dry steam volume
- Steam Output at 53-68,1 L (14 to 18 gallons)/hr (depending on moisture content)
- Adjustable moisture content from 5-15%
- Four chemical-injection settings
- Multiple cleaning tools

	0110.0100
	GVC-36000
Input Power	46 amps, 460-480V, 60 Hz AC, three phase. Maximum 36-KW
Power Supply Cord	10 m (33'), 6-4
Max. Output Steam Pressure	Adjustable 0- 9,9 BAR (0-145 PSI)
Max. Output Steam Temperature	143.3 °C (290 °F)
Output Steam Volume	53,5 kg (118 lbs)/hr
Boilers	Four 9 liters (2.4 gallons) stainless steel
Water Tank	40,1 liters (10.6 gallons) stainless steel
Chemical Tanks	Two 4,9 liters (1.3 gallons)
Dimensions	121,9 cm (48") high x 71,1 cm (28") wide x 109,2 (43") deep
Weight	225 lbs net dry

Call: +90 (0542) 131 8386 Visit: www.novachemtech.com

Nova Chemtech Hijyen Teknolojileri Ltd. Şti. Yeşilce Mah. Yunus Emre Cad. No: 8/1 Kağıthane 34418 Istanbul- TURKIYE Phone: +90 212 912 3223 • info@novachemtech.net