



Description : The Double C Frame Hydraulic Press (DCHP) is indicated for replacing mechanical presses (eccentric) with important advantages such as operational safety, increased productivity and tool life.

Applications : Cutting, Forming, Bending, Drawing, Assembling / Disassembling, Stretching,...

Capacity : 40, 60, 80 and 110 Ton

Technical Characteristics of Double C-Frame Hydraulic Press

CAPABILITIES		Type	DCHP 40T	DCHP 60T	DCHP 80T	DCHP 110T
ADVANCE	Tons		40	63	80	110
	KN		392	618	785	1079
RETURN	Tons		2	5	6	8
	KN		22	45	62	78
<b>SPEEDS</b>						
ADVANCE	mm/s		275	260	260	260
WORK	mm/s		17	15	12	15
RETURN	mm/s		210	220	200	205
<b>TABLE WITH PARALLEL T SLOT</b>						
WIDTH (A)	mm		600	600	750	750
LENGTH(B)	mm		450	450	600	600
CHIP OUTLET HOLE	mm		130	130	150	150
RIP t din			18 (M16)	18 (M16)	18 (M16)	22 (M20)
<b>HAMMER WITH PARALLEL T-SLOT</b>						
LENGTH (C)	mm		200	200	300	300
WIDTH (D)	mm		500	500	650	650
SPIN HOLE	mm		38	38	50	50
RIP t din			18 (M16)	18 (M16)	18 (M16)	22 (M20)
<b>DIMENSIONALS</b>						
PISTON STROKE	mm		250	250	350	350
MAXIMUM OPENING BETWEEN TABLE AND HAMMER (E)	mm		450	500	600	600
FIXED TABLE HEIGHT TO THE GROUND (F)	mm		850	850	850	850
CENTER OF THE CYLINDER TO THE BODY (G)	mm		340	340	400	400
MINIMUM OPENING BETWEEN TABLE AND HAMMER	mm		200	250	250	250
WIDTH (I)	mm		1000	1100	1200	1250
LENGTH (J)	mm		2170	2370	2570	2770
HEIGHT (L)	mm		2250	2400	2550	2700
VERTICAL FAIRING OPENING (M)	mm		470	470	620	620
FAIRING HORIZONTAL OPENING (H)	mm		765	765	915	1000
<b>MOTOR POWER</b>	HP		10	15	20	30
	kW		7,4	11	15	22
<b>TANK CAPACITY</b>	LT		160	260	350	600
<b>WEIGHT</b>	KL		2300	3200	4700	5400



MADE IN BRAZIL  
Araraquara - São Paulo - Brazil

Customizable: No  
Incoterms: Ex-works  
Delivery Time: 120 days after payment  
Conditions of payment: 100% in advance T/T  
Price: Ask for quotation

Sales Contact :  
Mr. Federico Falland  
+55 16 98174-0292  
sales@pressbrazil.com

