

Steel Door with Steel Frame

BS 476 : PART 22 : 1987 STANDARD

MODEL	CONFIGURATION	DOOR LEAF SIZE RANGE			STEEL FRAME		
		LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)	STEEL THICKNESS (mm)	FACE THICKNESS (mm)	WIDTH (mm)
BSST FD90	LSASD	2350	1050	42	1.5	65	165
	LSADD	2500	1100				

LSASD = Latch Single Action Single Door LSADD = Latch Single Action Double Door

MODEL	CONFIGURATION	DOOR LEAF SIZE RANGE			STEEL FRAME		
		LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)	STEEL THICKNESS (mm)	FACE THICKNESS (mm)	WIDTH (mm)
BSST FD120	LSASD	2350	1050	42	1.5	65	165
	LSADD	2500	1100				

LSASD = Latch Single Action Single Door LSADD = Latch Single Action Double Door

MODEL	CONFIGURATION	DOOR LEAF SIZE RANGE			STEEL FRAME		
		LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)	STEEL THICKNESS (mm)	FACE THICKNESS (mm)	WIDTH (mm)
BSST FD180	LSASD	2350	1050	42	1.5	65	165
	LSADD	2500	1100				

LSASD = Latch Single Action Single Door LSADD = Latch Single Action Double Door

MODEL	CONFIGURATION	DOOR LEAF SIZE RANGE			STEEL FRAME		
		LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)	STEEL THICKNESS (mm)	FACE THICKNESS (mm)	WIDTH (mm)
BSST FD240	LSASD	2350	1050	42	1.5	65	165
	LSADD	2500	1100				

LSASD = Latch Single Action Single Door LSADD = Latch Single Action Double Door

Steel Door with Steel Frame

TS EN 13501-2:2016-12

MODEL	CONFIGURATION	DOOR LEAF SIZE RANGE			STEEL FRAME		
		LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)	STEEL THICKNESS (mm)	FACE THICKNESS (mm)	WIDTH (mm)
BSST FD120(M)	LSASD	2350	1050	45	1.5	60	150
	LSADD	2500	1100				

LSASD = Latch Single Action Single Door LSADD = Latch Single Action Double Door