



VT66



Premium All-Position Steel Radial Highway Service.



Five-Rib tread design for premium handling and long life.



Specialty designed for steer axles and all-position usage.

Long Haul

Regional

Urban

On/Off Road

Recommended

Acceptable

SIZE	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter	Section Width	Tread Depth
					Dual		Single				
					lbs	psi	lbs	psi			
295/75R22.5	14	144/141	L	9.00	5842	104	6173	104	39.9	11.7	18
295/75R22.5	16	146/143	L	9.00	6008	120	6614	120	39.9	11.7	18
11R22.5	14	144/142	M	8.25	5830	110	6160	110	41.5	11	18
11R22.5	16	146/143	M	8.25	6005	120	6610	120	41.5	11	18
11R24.5	14	146/143	L	8.25	5995	110	6600	110	43.5	11	18
11R24.5	16	149/146	L	8.25	6610	120	7050	120	43.5	11	18
285/75R24.5	14	144/141	L	8.25	5665	104	6160	104	41.3	11.1	19
285/75R24.5	16	147/144	L	8.25	6008	120	6614	120	41.3	11.1	19
255/70R22.5	16	140/137	M	7.50	5071	120	5512	120	36.6	10	19