





Dometic T 2500H

2.0 kW generator for 230 volts AC, fuelled by petrol

  	Output voltage	230 V AC ±10 % (continuous)/pure sine wave 
	Total distortion factor	5 %
	Frequency	50 Hz ±5 %
	Max. starting current	24 A
	Continuous output	2,000 W
	Peak power	2,200 W
	Engine output	4.0 (5.5) kW (PS)
	Operating mode/fuel	Normal unleaded ROZ 91 petrol
	Power consumption	max. 1.2 l/h
	Sound level at 7 metres	60 dBA
	Guaranteed sound level	86 dBA
	Dimensions (W x H x D)	530 x 290 x 385 mm
	Width with suspension	640 mm
	Housing finish	Stainless steel
	Weight	50 kg
	12-volt output for battery charging	yes, with optional charging regulator
Quality features		Automatic low-oil cut-off, electrical starter, short circuit protection, soundproofed operation via external control panel
Test marks		E3
Product		Ref. No.
Dometic T 2500H		9102900005
/ Optional extras		
Plastic petrol tank with lock cap and fuel reserve float, 15 litres		9102900009
Plastic petrol tank with supports and feed-mouth incorporated, 15 litres		9102900010
20-litre stainless steel tank		9102900011
Hose set		9102900003
Flexible metal hose 25 mm, 2 m		9102900137
Flexible metal hose 25 mm, 5 m		9102900138
Battery charging regulator		9102900014
Floor chimney		9102900023
Change-over switch (generator / mains)		9102900013