

# NLR 26



***Sporting and Technical Regulations***

## Sporting Regulations

### 1. Classes & Rider Eligibility

#### **Super Series Power Trophy**

Riders MUST hold a valid

ACU Clubman or National Licence prior to riding at their first event of 2026.

SACU Clubman or National Licence prior to riding at their first event of 2026.

European FMN Licence subject to proof of insurance and written start permission to FIM Minimum Standards

### 2. Entries

How to enter

Via [www.nolimitsracing.co.uk](http://www.nolimitsracing.co.uk)

When to enter

Full Season - 1st December 2025 - 21st January 2026

Individual rounds - Please see the round entries calendar

Fees

Entry to this class as your main class will be £269-£529 circuit dependent.

Entry to this class as your 2nd class will be £170-£245 circuit dependent.

### 3. Programme

At each event, you will receive a minimum of 10 minutes scheduled timed practice and a minimum of 3 scheduled races.

### 4. Other Regulations

Useful Regulations

NLR26 Tyre Regulations

NLR26 Supplementary Regulations

### 5. Prizes

Prizes for this class are yet to be announced.

## Technical Regulations

All machines competing in any 2026 No Limits Super Series Power Trophy races must comply with these regulations. These rules are in addition to the ACU Standing Regulations as outlined in the ACU Handbook.

All No Limits Racing (NLR) Championships are open only to riders holding a valid ACU or SACU licence or a Licence from another FMN with proof of valid insurance and start permission.

These regulations are correct at the time of publication but are subject to amendment by the ACU or NLR. Any updates or changes will be communicated via an official NLR Bulletin

Anything not expressly permitted within these regulations is strictly prohibited.

Anything not expressly authorised or prescribed in these specifications must remain in standard form, with the exception of paintwork.

### 1. Eligible Machines

1.1 Open to production-based motorcycles originally homologated for road use.

Engine capacity limits:

Over 600cc up to 1000cc 4 stroke 4 cylinders

Over 675cc up to 1100cc 4 stroke 3 cylinders

Over 750cc up to 1200cc 4 stroke water cooled 2 cylinders

Over 830cc up to 1300cc 4 stroke air cooled 2 cylinders

The Ducati Panigale V4 and Aprilia RSV4RR 1100 are permitted in the 'Power' classes.

The displacement capacities must remain at the homologated size. Modifying the bore and stroke to reach class limits is not allowed.

Machines outside these specifications may be considered upon application to NLR.

1.2 Engine and frame numbers must be present and must not show signs of tampering or removal. Unstamped, new replacement components are allowed. Frames without numbers are acceptable only if the motorcycle was originally manufactured and supplied specifically for racing use.

### 2. Fuel

2.1 Only unleaded fuel, available from a roadside service station to current ACU regulations.

2.2 E85 biofuel is also acceptable from roadside outlets.

### 3 Tyres

3.1 NLR may implement a single tyre rule for the class. Details will be provided here once the rule is officially confirmed.

3.2 The cutting of extra tread grooves is forbidden.

3.3 Tyres will be examined during post-race technical control. Riders found using non-compliant tyres will be disqualified from championship points and awards. Repeated violations and disregard of the tyre regulations will result in further sanctions.

3.4 Wheel balance weights may be discarded or added.

3.5 If a race is declared as 'WET', a control rain tyre designated by NLR may be used. Please refer to the tyre regulations for further details.

3.6 Tyres available with pre order from No Limits Race Support.

### 4. Number Plates and Colours

4.1 Must conform to ACU regulations.

#### 4.2 Colours

Front : WHITE Background with BLACK Numbers

Side : WHITE Background with BLACK Numbers

### 5. Engine

#### 5.1. Fuel injection systems/carburettor

5.1.1 Fuel injection systems/carburettor refers to carburettors, throttle bodies, fuel injectors, variable length intake tract devices, fuel pump and fuel pressure regulator.

5.1.2 The original homologated fuel injection system must be used.

5.1.3 Bikes with carburettor systems must use them in an unmodified form, however jetting can be changed.

5.1.4 The fuel injectors must be stock and unaltered from the original specification and manufacture.

5.1.5 Throttle bodies intake insulators may be modified.

5.1.6 The injectors must be standard units as on the homologated motorcycle.

5.1.7 Bell mouths may be modified.

5.1.8 On Fuel Injected bikes the secondary vacuum slides may be fixed in the open position.

5.1.9 Butterfly cannot be changed or modified.

## 5.2. Cylinder Head

5.1.1 Cylinder head must be as homologated.

5.1.2 The following modifications are allowed:

- Grinding of the cylinder head surface on the side of the gasket;
- Modifications of the inlet and exhaust ports by taking off or adding material (welding is forbidden);
- Original homologated valves guides may be cut or modified.
- Polishing of the combustion chamber;
- Original valve seats must be used, but modifications are allowed to the shape;

5.1.3 Compression ratio is free, but the combustion chamber can be modified only by taking material off.

5.1.4 It is forbidden to add any material to the cylinder head unless as described above. The combustion chamber may be modified. Rocker arms (if any) must remain as homologated (material and dimensions).

5.1.5 Standard valves, valve springs and valve spring retainers must be used.

## 5.3. Camshaft

5.3.1 The method of drive must remain as homologated. The cam shaft is free to be modified or replaced. The duration is free but the lift must remain as homologated.

5.3.2 The cam chain or cam belt tensioning device(s) are free.

## 5.4. Cam Sprockets or gears

Cam sprockets or cam gears are free.

## 5.5. Cylinders

5.5.1 Cylinders must remain as homologated. Only the following modifications to the cylinders are allowed.

5.5.2 Cylinder head gasket surface may be machined to allow the adjustment of compression ratio or resurfacing to repair a warped cylinder surface deck.

5.5.3 Homologated materials and castings for cylinders must be used.

5.5.4 The surface finish of the cylinder bore must remain as homologated.

5.5.5 Cylinder capacity must remain at the homologated size.

5.5.6 2 stroke machines only the original ports may be modified.

#### 5.6. Pistons

Pistons must remain as homologated. Polishing and lightening is not allowed.

#### 5.7. Piston Rings

Piston rings must remain as homologated. No modifications are allowed.

#### 5.8. Piston Pins and Clips

Piston pins and clips must remain as homologated. No modifications are allowed.

#### 5.9. Connecting Rods

Connecting rods must remain as homologated. Polishing and lightening is not allowed.

#### 5.10. Crankshaft

5.10.1 Crankshaft must remain as homologated without modification. Polishing and lightening is not allowed.

5.10.2 Modifications of the flywheels are not allowed.

#### 5.11 Crankcase/Gearbox and all other Engine Cases (i.e. ignition case, clutch case)

5.11.1 It is not allowed to add a pump used to create a vacuum in the crankcase.

5.11.2 If a vacuum pump is installed on the homologated motorcycle then it may be used only as homologated.

5.11.3 Other engine cases must be made of the homologated material with the exclusion of the lateral side covers. (see below)

5.11.4 Lateral (side) covers may be altered, modified or replaced.

5.11.5 If altered or modified, the cover must have at least the same resistance to impact as the original one.

5.11.6 If replaced, the cover must be made in material of same or higher specific weight and the total weight of the cover must not be less than the original one.

5.11.7 Engine case guards in the form of strengthened engine side covers may be installed.

5.11.8 These covers must be no lighter in weight than the standard part.

5.11.9 All lateral covers/engine cases containing oil and which could be in contact with the ground during a crash, MUST be protected by a second cover made of composite material, type injection moulded nylon

5.11.10 All these devices must be designed to be resistant against sudden shocks and must be fixed properly and all devices are fitted by bolts onto the engine cover/case.

5.11.11 Holes may be added in dry clutch covers to allow additional cooling.

5.11.12 The countershaft cover may be removed.

5.11.13 The addition of a crankcase protector at the countershaft is allowed.

## 5.12. Transmission/Gearbox

5.12.1 Transmission/gearbox is free (Open).

5.12.2 The number of gears must remain as homologated.

5.12.3 Quick-shift and blipper systems are allowed.

5.12.4 Countershaft sprocket, rear wheel sprocket, chain pitch and size can be changed.

5.12.5 Chain guard as long as it is not incorporated in the rear fender may be removed.

## 5.13. Clutch

5.13.1 Clutch type (wet or dry) and the way of operation (by cable or hydraulic) must remain as homologated.

5.13.2 Friction and drive discs may be changed.

5.13.3 Clutch springs may be changed.

5.13.4 The clutch basket (outer) may be replaced.

5.13.5 The original clutch assembly may be modified for back torque limiting capabilities (slipper type).

5.13.6 It is allowed to change to an aftermarket clutch with back torque limiting capabilities (slipper type).

5.13.7 No power source (i.e. hydraulic or electric) can be used for gear selection, if not installed in the homologated model for road use.

5.13.8 Human power is excluded from the ban.

#### 5.14. Oil Pumps, water pumps and Oil Lines

5.14.1 Modifications are allowed but pump housing, mounting points and oil feed points must stay as original.

5.14.2 Oil lines may be modified or replaced.

5.14.3 Oil lines containing positive pressure, if replaced, must be of metal reinforced construction with swaged or treaded connectors.

5.14.4 The internal parts of the water pump may be changed or modified.

5.14.5 The drive ratio may be changed.

5.14.6 The external appearance must remain as homologated.

#### 5.15. Radiator and oil coolers

5.15.1 The radiator and its hoses may be changed only if they fit in the standard location and do not require any modifications to the main frame or to the fairings' outer appearance.

5.15.2 Modifications to the existing oil cooler are allowed only if it does not require any modifications to the main frame or to the fairings' outer appearance.

5.15.3 A heat exchange (oil/water) can be exchanged by an oil cooler.

5.15.4 Radiator fan and wiring may be changed, modified or removed.

5.15.5 Additional oil coolers are not allowed.

5.15.6 Oil cooler must not be mounted on or above the rear mudguard.

#### 5.16. Airbox

5.16.1 The basic air box must remain as originally produced by the manufacturer on homologated machine.



5.16.2 The top face only can be removed or drilled through.

5.16.3 The air filter element may be replaced.

5.16.4 The air box drains must be sealed.

5.16.5 All motorcycles must have a closed breather system.

5.16.6 Ram air tubes or ducts running from the fairing to the air box may be modified, replaced or removed.

5.16.7 If tubes/ducts are utilized, they must be attached to the original, unmodified air box inlets.

#### 5.17. Fuel Supply

5.17.1 Fuel pump and fuel pressure regulator must remain the same as on the homologated motorcycle.

5.17.2 The fuel pressure must be as homologated.

5.17.3 Fuel lines from the fuel tank up to the injectors (fuel hoses, delivery pipe assembly, joints, clamps, fuel canister) may be replaced.

5.17.4 The fuel line(s) going from the fuel tank to the fuel injection system must be located in such a way that they are protected from possible crash damage.

5.17.5 Quick connectors or dry brake quick connectors may be used.

5.17.6 Fuel vent lines may be replaced.

5.17.7 Fuel filters may be added.

#### 5.18. Exhaust System

5.18.1 Exhaust pipes and silencers may be modified or changed.

5.18.2 For safety reasons, the exposed edge(s) of the exhaust pipe(s) outlet(s) must be rounded to avoid any sharp edges.

5.18.3 Wrapping of exhaust systems is not allowed except in the area of the riders foot or an area in contact with the fairing for protection from heat.

5.18.4 The noise limit for will be 105 dB/A (with a 3 dB/A tolerance after the race).

### 5.19. Ignition/Engine Control System (ECU)

5.19.1 Ignition/Engine control system (ECU) is open. (Free to change)

5.19.2 The use of flash memory ('flash RAM') for fuel injection mapping is allowed.

5.19.3 An additional control unit to change the fuel mixture may be fitted.

5.19.4 Spark plugs and plug caps and wires may be replaced.

### 5.20. Generator, alternator, electric starter

5.20.1 Generator may be modified.

5.20.2 The electric starter must operate normally and always be able to start the engine during the practices and race (including the Parc Ferme).

### 5.21. Additional Equipment

5.21.1 The addition of a device for infra-red (IR) transmission of a signal between the racing rider and his team, used exclusively for lap timing, is allowed.

5.21.2 The addition of a GPS unit for lap timing/scoring purposes is allowed.

## 6. Electrical

### 6.1. Electrics and Switches

Connectors and switches are open (free).

### 6.2. Wiring Harness

6.2.1 The wiring harness may be altered or replaced.

6.2.2 Additional wiring harnesses may be added.

6.2.3 Cutting of the wiring harness is allowed.

### 6.3. Battery

The size and type of battery may be changed and relocated.

## 7. Frame and Body

### 7.1. Frame Body, Instrument support and Rear sub-frame

7.1.1 Frame must remain as originally produced by the manufacturer for the homologated machine.

7.1.2 Holes may be drilled on the frame only to fix approved components (i.e., fairing brackets, steering damper mount, sensors).

7.1.3 The sides of the frame-body may be covered by a protective part made of a composite material.

7.1.4 These protectors must fit the form of the frame.

7.1.5 Nothing else can be added or removed from the frame body.

7.1.6 All motorcycles must display a vehicle identification number on the frame body (chassis number).

7.1.7 Engine mounting brackets or plates must remain as originally produced by the manufacturer for the homologated machine.

7.1.8 Rear sub frame may be changed or altered, but the type of material must remain as homologated, or of higher specific weight.

7.1.9 The Instrument support frame can be changed or altered.

7.1.10 Additional seat brackets may be added, non-stressed protruding brackets may be removed if they do not affect the safety of the construction or assembly.

7.1.11 Bolt-on accessories to the rear sub-frame may be removed.

## 7.2. Front Forks

7.2.1 Front forks are free (Open).

7.2.2 The upper and lower fork clamps (triple clamp, fork bridges) may be changed.

7.2.3 Steering damper may be added or replaced with an aftermarket damper.

7.2.4 The steering damper cannot act as a steering lock limiting device.

## 7.3. Rear Fork (Swing arm)

7.3.1 The rear fork may be changed.

7.3.2 A chain guard must be fitted in such a way to reduce the possibility that any part of the riders' body must become trapped between the lower chain run and the rear wheel sprocket.

7.3.3 Rear axle chain adjuster can be modified or changed.

#### 7.4. Rear Suspension Unit

7.4.1 Rear suspension unit can be changed or modified.

7.4.2 The original attachments of the frame and rear fork must be as homologated.

7.4.3 Rear suspension unit spring(s) may be changed.

7.4.4 Rear suspension linkage may be changed.

#### 7.5. Wheels

Wheels are Open.

#### 7.6. Brakes

7.6.1 Front and rear brake discs may be changed.

7.6.2 Front Brake Master Cylinders and levers can be changed.

7.6.3 Front Brake Callipers can be changed.

7.6.4 The callipers must be designed to use pads with a pad area that is the same or greater than standard.

7.6.5 Internally ventilated discs are not allowed if not homologated in the original machine.

7.6.6 Replacement brake discs must be of ferrous material. (No carbon).

7.6.7 Rear brake calliper is open (Free).

7.6.8 Rear master cylinder is open (Free).

7.6.9 Front and rear hydraulic brake lines may be changed.

7.6.10 The split of the front brake lines for both front brake callipers must be made above the lower edge of the fork bridge (lower triple clamp).

## 7.7. Handle Bars and Hand Controls

7.7.1 Handle bars, throttle assembly and associated cables, hand controls and levers may be replaced.

7.7.2 Handle bars and hand controls maybe relocated.

7.7.3 Throttle controls must be self-closing when not held by hand.

7.7.4 Electric starter switch and engine stop switch must be located on the handle bars.

## 7.8. Foot Rest/Foot Controls

7.8.1 Foot rest/foot controls may be relocated, but the original mounting points must be used.

7.8.2 Foot rests may be rigidly mounted or a folding type which must incorporate a device to return them to the normal position.

7.8.3 The end of the foot rest must have at least an 8mm solid spherical radius.

7.8.4 Non folding footrests must have an end (plug) which is permanently fixed, made of aluminium, plastic, Teflon® or equivalent type of material (min. radius of 8mm).

7.8.5 The plug surface must be designed to reach the widest possible area of the footrest.

7.8.6 The Chief Technical Officer has the right to refuse any plug not satisfying this safety aim.

## 7.9. Fuel Tank

7.9.1 Fuel tank must remain as originally produced by the manufacturer for the homologated machine.

7.9.2 Fuel tanks with tank breather pipes must be fitted with non-return valves that discharge into a catch tank with a minimum volume of 250 cc made of a suitable material.

7.9.3 Fuel caps may be changed.

7.9.4 Fuel caps when closed, must be leak proof.

## 7.10. Fairing/Body Work

7.10.1 Fairing and body work may be replaced.

7.10.2 The material may be changed.

7.10.3 The Chief Technical Officer has the right to refuse any bodywork that does not appear safe and cosmetically tidy.

7.10.4 Wind screen may be replaced, transparent or 'light tint' is allowed, the rider must be able to see easily through it.

7.10.5 The original combination instrument/fairing brackets may be replaced.

7.10.6 All other fairing brackets may be altered or replaced.

7.10.7 The original air ducts running between the fairing and the air box may be altered or replaced.

7.10.8 The original air ducts into the air box may be altered or replaced.

7.10.9 Minimal changes are allowed to permit the use of an elevator (stand) for wheel changes and to add a small plastic protective cone to the frame or engine.

7.10.10 Front mudguard may be replaced. The use of carbon fibre or Kevlar® composites is allowed.

7.10.11 Front mudguard may be spaced upward for increased tyre clearance.

7.10.12 Rear mudguard fixed on the swing-arm may be replaced.

7.10.13 The use of carbon fibre or Kevlar® composites is allowed.

7.10.14 The existing rear mudguard under the seat may be removed.

7.10.15 A mudguard may be fitted directly onto the swing-arm (it may not cover more than 120 degrees of the wheel).

## 7.11. Seat

7.11.1 Seat, seat base and associated body work may be replaced.

7.11.2 The top portion of the rear body work around the seat may be modified to a solo seat.

7.11.3 Holes may be drilled in the seat or rear cowl to allow additional cooling.

7.11.4 Holes which are bigger than 10mm must be covered with metal gauze or fine mesh.

7.11.5 Mesh must be painted to match the surrounding material.

7.11.6 The appearance from both front rear and profile must conform in principle to the homologated shape.

7.11.7 All exposed edges must be rounded.

## 7.12. Fasteners

7.12.1 Standard fasteners may be replaced with fasteners of any material and design.

7.12.2 Aluminium fasteners may only be used in non-structural locations.

7.12.3 Titanium fasteners may be used in structural locations, but the strength and design must be equal to or exceed the strength of the standard fastener it is replacing.

7.12.4 Special steel fasteners may be used in structural locations, but the strength and design must be equal to or exceed the strength of the standard fastener it is replacing.

7.12.5 Fasteners may be drilled for safety wire, but intentional weight-saving modifications are not allowed.

## 7.13. Oil Containment

7.13.1 The lower fairing has to be constructed to hold, in case of an engine breakdown, at least half of the total oil and engine coolant capacity used in the engine (minimum 5 litres).

7.13.2 The lower edge of openings in the fairing must be positioned at least 50 mm above the bottom of the fairing.

7.13.3 All engine cases containing oil and which could be in contact with the ground during a crash must be protected by a second cover made of composite material, metal such as aluminium alloy, stainless steel, steel or titanium.

7.13.4 All these devices must be designed to be resistant against sudden shocks and all devices must be fixed by bolts onto the engine covers/cases.

7.13.5 The chief technical officer has the right to forbid any covers, if the evidence shows the cover is not effective.

## 8. Rear Safety Light

16.1 Functional red light mandatory; on track or in pit lane during wet conditions.

16.2 Must be visible  $\pm 15^\circ$  from machine centre line.

16.3 LED: 0.6–1.8 W, incandescent: 10–15 W.

16.4 Continuous operation on track; flashing allowed only in pit lane.

16.5 Chief Technical Officer may reject non-compliant systems.

## 9. Items the MUST be Removed

- Headlamp
- rear lamp
- turn indicators
- Mirrors
- Horn
- license plate bracket
- Toolbox
- helmet/luggage hooks
- passenger footrests/grab rails
- safety bars
- centre/side stands
- catalytic converters
- rear mudguards attached to the seat unit

## 10. Items the MUST be Altered.

- Motorcycles must be equipped with a functional ignition kill switch or button mounted at least on one side of the handlebar (within reach of the hand while on the hand grips) that is capable of stopping a running engine.
- It is recommended that machines be equipped with a red light on the instrument panel.
- This light must flash in the event of oil pressure drop.
- All drain plugs must be wired.
- External oil filter(s) screws and bolts that enter an oil cavity must be safety wired (i.e. on crankcases, oil lines, oil coolers, etc.)

## 11 Items the MAY be Removed



- Emission control items (anti-pollution) in or around the air box and engines (O2 sensors, air injection devices)
- Speedometer and related wheel spacers.
- Bolt on accessories on a rear sub frame.

12. Items the MAY be Altered or replaced from those fitted to the homologated machine.

- Any type of lubrication, brake or suspension fluid may be used.
- Bearings (ball, roller, taper, plain, etc.) of any type or brand may be used.
- Gaskets and gasket materials.
- Painted external surface finishes and decals.
- Tachometer – NB this must be working so that noise limits may be measured.

13. Class and Series Sponsors

If required by NLR, class and series title sponsors' decals or stickers must be prominently displayed on machines where applicable and will be checked during technical inspection. Decals that conflict with class or series sponsor branding may be requested to be removed.

14. Presentation

23.1 The organisers reserve the right to refuse any machine admission to the start if, upon arrival at technical inspection, it is deemed not to be in a presentable condition.

23.2 Machines must be maintained to a high standard. Competitors are responsible for regularly checking their machines before, during, and after events to ensure ongoing compliance.

15. Parc Ferme /Disputes/Challenges

This is covered in the ACU handbook and minor queries should be directed through the riders' representatives. Check ACU Handbook for correct procedures.

16. General

Non-compliant motorcycles may be excluded at Technical Control discretion. If there are any queries relating to these regulations contact No Limits Racing administrators - [info@nolimitsracing.co.uk](mailto:info@nolimitsracing.co.uk) or the Chief Technical Officer - [technical@nolimitsracing.co.uk](mailto:technical@nolimitsracing.co.uk).