

# ULTRA START

AND SECURITY

PRO SERIES

## U1281M-PRO & U2281M-PRO

ADVANCED REMOTE STARTER & ALARM STARTER FOR MANUAL TRANSMISSION VEHICLES



THE U1281M-PRO & U2281M-PRO ARE SPECIFICALLY DESIGNED FOR INSTALLATION INTO MANUAL TRANSMISSION VEHICLES. THE XR-PRO SERIES FEATURES AN INDUSTRY LEADING BULLET-PROOF STYLE METAL REMOTE WITH ULTRASTARTS ADVANCED EXTREME RANGE TECHNOLOGY (XR).

THE XR-PRO SERIES IS IN A LEAGUE OF ITS OWN WITH FEATURES LIKE A DIRECT LINK DATA PORT, OUTPUT OVERLOAD PROTECTION AND AN INTELLIGENT AUTO TACH / TACHLESS LEARNING SYSTEM.

THE U1281M-PRO & U2281M-PRO OFFERS ALL THE FEATURES OF OUR U1272-PRO PLUS OUR EXCLUSIVE XR RANGE 4 BUTTON METAL REMOTE'S, GIVING THE LONG RANGE YOU NEED WITH UP TO 2500FT\* OF OPERATING DISTANCE. THIS HIGHLY ADVANCED MODEL ALSO OFFERS ADDITIONAL OUTPUTS FOR SLIDING DOORS AND OTHER CUSTOM APPLICATIONS. ALSO INCLUDED IS A TEMPERATURE SENSOR PORT ALLOWING THE UNIT TO SENSE TEMPERATURE ALLOWING THE UNIT TO AUTOMATICALLY START YOUR VEHICLE ONLY WHEN THE DESIRED TEMPERATURE IS REACHED.

### SPECIFICATIONS

#### RF

- METAL XR PRO SERIES REMOTES
- XR ULTRA EXTREME RANGE 1-WAY

- UP TO 2500FT\*
- TCS TEMPERATURE COMP SYSTEM

- RF ANT WITH BUILT IN VALET SWITCH
- DUAL HYPER BRIGHT INDIGO LEDS

#### FEATURES

- MANUAL TRANSMISSION OPERATION
- DOOR LOCK & UNLOCK OUTPUTS
- FACTORY ALARM ARM OUTPUT
- FACTORY ALARM DISARM OUTPUT
- BYPASS MODULE CONNECTOR
- DLDP DIRECT LINK DATA COM PORT
- 5 ON-BOARD EXTREME DUTY RELAYS
- DIESEL MODE WITH GLOW PLUG INPUT

- ULTRA AUTO TACH DETECTION
- ULTRA AUTO TACHLESS MODE
- SELECTABLE RUN TIMES
- HOOD PIN AND BRAKE INPUTS
- SELECTABLE (+/-) PARK LIGHT OUTPUT
- PROGRAMMABLE AUX OUTPUTS
- OUTPUT OVERLOAD PROTECTION
- BOOT LOADER SOFTWARE UPGRADES
- TEMPERATURE SENSOR PORT

- COLD WEATHER TIMER MODE
- DRIVER'S DOOR PRIORITY
- PANIC MODE
- HYBRID VEHICLE MODE

#### ALARM FEATURES

##### U2281M-XR-PRO

- DUAL STAGE DIGITAL SHOCK SENSOR

- REMOTE ADJUST SENSOR SETTINGS
- (+ / -) DOOR TRIGGER INPUTS
- FALSE ALARM PREVENTION

- SYSTEM
- INTELLIGENT SELF DIAGNOSTICS
- AUX DUAL STAGE SENSOR

- PLUG
- STARTER DISABLE OUTPUT