

Gottwald HMK 280 E. 2 ROPES



Year: 2002



Lifting Capacity: 100t

Working hours: 51.000 Hrs.

2 ROPES

GOOD WORKING CONDITIONS

Gottwald HMK 280 E. 2 ROPES

GOTTWALD HMK 280 E							
Radius	Capacities (t)						
							
	normal load	spreader I	spreader II	spreader II Twinstit	grab	special load	heavy load
	66 2/3 %	66 2/3 %	66 2/3 %	66 2/3 %	50 %	75 %	66 2/3 %
(m)	(t)	(t)	(t)	(t)	(t)	(t)	(t)
11	63.0	35.0	40.0	50.0	32.0	100.0	100.0
12	63.0	35.0	40.0	50.0	32.0	100.0	100.0
13	63.0	35.0	40.0	50.0	32.0	100.0	100.0
14	63.0	35.0	40.0	50.0	32.0	100.0	100.0
15	63.0	35.0	40.0	50.0	32.0	100.0	100.0
16	63.0	35.0	40.0	50.0	32.0	100.0	100.0
17	63.0	35.0	40.0	50.0	32.0	100.0	100.0
18	63.0	35.0	40.0	50.0	32.0	100.0	100.0
19	63.0	35.0	40.0	50.0	32.0	100.0	100.0
20	63.0	35.0	40.0	50.0	32.0	100.0	100.0
21	63.0	35.0	40.0	50.0	32.0	100.0	100.0
22	63.0	35.0	40.0	50.0	32.0	100.0	95.9
23	63.0	35.0	40.0	50.0	32.0	98.3	89.5
24	63.0	35.0	40.0	50.0	32.0	91.7	83.5
25	63.0	35.0	40.0	50.0	32.0	86.2	78.5
26	63.0	35.0	40.0	50.0	32.0	81.3	74.0
27	63.0	35.0	40.0	50.0	32.0	76.3	69.5
28	63.0	35.0	40.0	50.0	32.0	72.5	66.0
29	62.7	35.0	40.0	50.0	32.0	68.9	62.7
30	59.5	35.0	40.0	49.1	32.0	65.4	59.5
31	56.6	35.0	40.0	46.2	32.0	62.2	56.6
32	53.9	35.0	40.0	43.5	32.0	59.2	53.9
33	51.4	35.0	40.0	41.0	32.0	56.5	51.4
34	49.0	35.0	38.6	38.6	32.0	53.8	49.0
35	46.5	35.0	36.1	36.1	32.0	51.1	46.5
36	44.5	35.0	34.1	34.1	32.0	48.9	44.5
37	43.0	34.4	32.6	32.6	32.0	47.2	43.0
38	41.3	32.7	30.9	30.9	30.8	45.4	41.3
39	40.0	31.4	29.6	29.6	29.7	43.9	40.0
40	38.5	29.9	28.1	28.1	28.6	42.3	38.5
41	37.1	28.5	26.7	26.7	27.7	40.8	37.1
42	35.8	27.2	25.4	25.4	26.7	39.3	35.8
43	34.4	25.8	24.0	24.0	25.8	37.8	34.4
44	33.3	24.7	22.9	22.9	25.0	36.6	33.3
45	32.0	23.4	21.6	21.6	24.2	35.2	32.0
46	30.8	22.2	20.4	20.4	23.1	33.8	30.8
47	29.7	21.1	19.3	19.3	22.3	32.6	29.7
48	28.5	19.9	18.1	18.1	21.4	31.3	28.5
49	27.3	18.7	16.9	16.9	20.5	30.0	27.3
50	26.0	17.4	15.6	15.6	19.5	28.6	26.0