



Dog Hollow Speedway by J&E Motorsports  
76 Hamill Road, Northern Cambria, PA 15714  
814-696-9031

## 2024 FOUR-CYLINDER RULES

---

**TECH PERSONS & RACE DIRECTOR HAVE THE SAY OVER ALL RULES. THERE WILL BE NO ARGUMENTS. IF SO, YOU WILL BE DISQUALIFIED.**

**DRIVER IS RESPONSIBLE FOR ALL PIT CREW MEMBERS. IF ANY FIGHTING, ARGUING, OR DISRUPTIONS OCCUR, THE CAR / DRIVER WILL BE DISQUALIFIED AND SUSPENDED FOR TWO WEEKS.**

---

\*\*\*\*All requirements listed below MUST be met unless an exception is clearly stated.

\*\*\*\*Tech has the right to internally inspect any engine part after the feature, even if the engine pumps legal.

---

FWDs will run under SCDRA rules except for the highlighted differences.

### BASICS

1. Must be a stock 4-cylinder car.
2. No turbo or rotary engines allowed.
3. Stock-type fuel injection or stock manufactured carburetor only (Motorcraft, etc.).  
ONE 0.800-inch maximum throttle body spacer may be used. No Holley, Weber, or other racing carburetors allowed. Carburetor must be stock for engine.
4. Motor must be stock appearing and in stock location.
5. Motor must match car (Example: Honda must have Honda engine).
6. Any air or oil filters (K&N, etc.).
7. Intake must be a stock intake.
8. No cold air intakes for fuel injections – must be stock type breather system. A flexible rubber or plastic hose may be used in place of the stock air box tube. No smooth metal or smooth plastic tubing allowed. A cone type filter is allowed and may be connected directly to throttle body or the allowed tubes.
9. Aftermarket radiators okay – radiators can be braced for support.
10. Aftermarket (racing) headers are allowed.



Dog Hollow Speedway by J&E Motorsports  
76 Hamill Road, Northern Cambria, PA 15714  
814-696-9031

11. Computer may be chipped and / or tuned. A standalone ECU and aftermarket harness are allowed.  
Ignition coil must remain OEM.

### **WEIGHT**

1. All cars must weigh 2200 lbs. with car and driver after the race.  
Exceptions: 50 lb. weight break for HANS or like device  
50 lb. weight break for containment seat.

### **BODY / WHEELS / TIRES:**

1. Any front wheel drive car.
2. No all-wheel drive cars or all-wheel steer cars.
3. Must have stock rear and front suspensions as from factory; slotting of factory mounting holes allowed.
4. No racing springs (lowering) or shocks allowed. Springs may be heated, clamped, or use spring rubbers.  
Springs must be within 2 inches of factory installed height.
5. Rear control arms should be stock but may be braced / strengthened / repaired. No aftermarket.
6. Stock type aftermarket suspension bushings are allowed.
7. Stock production cars only.
8. Mirrors are NOT allowed.
9. Must have a quality welded minimum 4-point roll cage inside the car with a minimum of 0.95-inch thickness tubing.  
Dog Hollow Speedway Tech has final say in safety of the cage.
10. Minimum 3 driver door bars / 2 side door bars – 6 or more point cages okay.
11. No push bars past firewall. Roll cage may extend forward behind bumpers. Bumpers must be covered in some way with no exposed sharp corners.
12. Aftermarket racing wheels allowed – 7 inches maximum. NO bead locks.
13. Street legal DOT tires required. No drag radials, mud grip lug tires, racing tires, or racing recapped tires allowed. Directional tires are allowed. Tires can be mixed and matched for stagger.
14. Aftermarket nosepieces allowed.



Dog Hollow Speedway by J&E Motorsports  
76 Hamill Road, Northern Cambria, PA 15714  
814-696-9031

15. 6-inch metal support to extend out behind nosepiece or to hold grill in place allowed.
16. No push bars to extend outside of bumpers or beyond nosepiece.
17. Some sheet metal will be allowed for repairs. Cars should remain as close to stock appearing as possible.  
Adding sheet metal to bodies may result in a weight penalty being assessed.
18. Gutting of body is allowed.

### **SAFETY**

1. Window nets are MANDATORY. Sprint-style window nets will NOT be permitted.
2. Racing (not motorcycle) helmet, SA 2005 or newer is required.
3. Minimum single-layer fire suit required (SA 3.2A specification recommended).
4. Fireproof gloves strongly recommended (SFI 3.3 specification recommended).
5. A 4- or 5-point harness, properly mounted per manufacturers' specifications, is required.  
Must meet manufactured expiration date. Any worn, abraded, or torn belts shall be replaced.
6. A minimum 5 lb. fire extinguisher is recommended and should be securely mounted within driver's reach.
7. Only racing-type seats, properly mounted per manufacturers' specifications, are allowed. A full containment seat is strongly recommended. Cars equipped with full containment seats will receive a 50 lb. weight break.
8. A head and neck restraint system (SFI 16.1 compliant) is strongly recommended. Drivers using a head and neck restraint will receive a 50 lb. weight reduction.
9. A firewall must be in place between driver compartment and fuel cells, fuel lines, or tanks.

### **MISCELLANEOUS**

1. Tech has final ruling on all questions of legality. A pre-race inspection will be made to ensure SAFETY only.
2. Questions of legality can and will be answered during the pre-race inspection if asked by entrant. No guarantee of legality shall be expressed or implied during pre-race inspection. Legality will be determined in POST-race inspection.
3. Competitors must present cars for inspection prior to participating in any racing event.



Dog Hollow Speedway by J&E Motorsports  
76 Hamill Road, Northern Cambria, PA 15714  
814-696-9031

4. No radios allowed.
5. RACEceivers or a like device is mandatory at all times on track.
6. AMB MyLaps Transponders are also required.
7. Progressive Ignition distributors, manufactured distributors, or unidentifiable distributors are illegal.
8. 16-volt batteries are permitted.