

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Wax-Fix, model adhesive**

Revision date: 10.03.2020

Product code: 110-210

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Wax-Fix, model adhesive

**Further trade names**

Article No.: 110-210-00

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Health services.

**1.3. Details of the supplier of the safety data sheet**

Company name:	DENTAURUM GmbH & Co. KG	
Street:	Turnstr. 31	
Place:	D-75228 Ispringen	
Telephone:	+49 7231 803 0	Telefax: +49 7231 803 295
e-mail:	info@dentaurum.de	
Internet:	www.dentaurum.com	

**Further Information**

Emergency telephone:		
07:00 - 16:15 (Mo - Do), 07:00 - 13:15 (Fr)	+49 7231 803 184	
16:15 - 18:00 (Mo - Do), 13:15 - 18:00 (Fr)	+49 7231 803 0	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:  
Flammable liquid: Flam. Liq. 2  
Serious eye damage/eye irritation: Eye Irrit. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Hazard Statements:  
Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl acetate  
propan-2-ol; isopropyl alcohol; isopropanol

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
------	---

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wax-Fix, model adhesive**

Revision date: 10.03.2020

Product code: 110-210

Page 2 of 9

P240	smoking.
P243	Ground and bond container and receiving equipment.
P271	Take action to prevent static discharges.
P305+P351+P338	Use only outdoors or in a well-ventilated area.
P370+P378	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	In case of fire: Use Foam, Carbon dioxide (CO <sub>2</sub> ), Water mist, Water spray jet, Extinguishing powder to extinguish.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Acrylic acid ester copolymer soluted in ethyl acetate

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
141-78-6	ethyl acetate			50-80 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20-40 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.

**After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms: Headache. drowsiness. Dizziness. Nausea.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. after ingestion: Have victim drink large quantities of water, with active charcoal if possible.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Wax-Fix, model adhesive

Revision date: 10.03.2020

Product code: 110-210

Page 3 of 9

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder. Water fog. Water spray.

##### **Unsuitable extinguishing media**

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Do not breathe vapour.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion  
Do not allow to enter into soil/subsoil.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Ensure adequate ventilation of the storage area. Do not breathe vapour.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Vapours may form explosive mixtures with air.

Take action to prevent static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect against direct sunlight. Keep away from heat.

##### **Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wax-Fix, model adhesive

Revision date: 10.03.2020

Product code: 110-210

Page 4 of 9

#### 7.3. Specific end use(s)

Health services.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe vapour. Avoid contact with eyes and skin.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not smoke.

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

Recommendation:

Dermatril Single-use gloves. NBR (Nitrile rubber). 0,11 mm penetration time (maximum wearing period): 0 min. REF 162-907-00 (7/S), REF 162-908-00 (8/M), REF 162-909-00 (9/L)

-----  
Camapren 720, CR (polychloroprenes, Chloroprene rubber). 0,65 mm penetration time (maximum wearing period): 10 min, KCL

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wax-Fix, model adhesive

Revision date: 10.03.2020

Product code: 110-210

Page 5 of 9

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
 Colour: light yellow  
 Odour: like: Solvent/Thinner.

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined  
 Initial boiling point and boiling range: not determined

Flash point: < -5 °C DIN 51755

#### Flammability

Solid: not applicable  
 Gas: not applicable

Lower explosion limits: not determined  
 Upper explosion limits: not determined

#### Auto-ignition temperature

Solid: not applicable  
 Gas: not applicable

Decomposition temperature: not determined

#### Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,87 g/cm<sup>3</sup>

Water solubility: practically insoluble  
 (at 20 °C)

#### Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: approx. 15 mPa·s  
 (at 20 °C)

Vapour density: not determined

Evaporation rate: not determined

### 9.2. Other information

Solid content: not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable, Ignition hazard.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.  
 Reacts with : Oxidizing agents, strong.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wax-Fix, model adhesive

Revision date: 10.03.2020

Product code: 110-210

Page 6 of 9

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

#### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

none

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

##### Irritation and corrosivity

Causes serious eye irritation.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

##### STOT-single exposure

May cause drowsiness or dizziness. (Ethyl acetate), (propan-2-ol; isopropyl alcohol; isopropanol)

##### STOT-repeated exposure

Based on available data, the classification criteria are not met.

##### Aspiration hazard

Based on available data, the classification criteria are not met.

##### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### SECTION 12: Ecological information

#### 12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 > 100 mg/l	96 h			
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h			

#### 12.2. Persistence and degradability

The product has not been tested.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wax-Fix, model adhesive

Revision date: 10.03.2020

Product code: 110-210

Page 7 of 9

#### **12.3. Bioaccumulative potential**

The product has not been tested.

#### **12.4. Mobility in soil**

The product has not been tested.

#### **12.5. Results of PBT and vPvB assessment**

The product has not been tested.

#### **12.6. Other adverse effects**

No information available.

#### **Further information**

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Send to a hazardous waste incinerator facility under observation of official regulations .

##### **List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	UN 1133
<b><u>14.2. UN proper shipping name:</u></b>	Adhesives
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	5 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

#### **Marine transport (IMDG)**

<b><u>14.1. UN number:</u></b>	UN 1133
<b><u>14.2. UN proper shipping name:</u></b>	Adhesives
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	II

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Wax-Fix, model adhesive**

Revision date: 10.03.2020

Product code: 110-210

Page 8 of 9

Hazard label: 3



Special Provisions: -  
 Limited quantity: 5 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
 Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 8.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wax-Fix, model adhesive**

Revision date: 10.03.2020

Product code: 110-210

Page 9 of 9

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road )  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*