

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: G-CEM ONE Adhesive Enhancing Primer
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V.
Interleuvenlaan 33
B-3001 Leuven
Tel. +32/(0)16/74.10.00

Fax +32/(0)16/40.26.84 msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02

2 GHS05

· Signal word Danger

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

### Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 1)

#### · Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P260* Do not breathe dusts or mists.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

*P321* Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 64-17-5	ethyl alcohol	25-<50%
EINECS: 200-578-6	Flam. Liq. 2, H225	1
Index number: 603-002-00-5		
CAS: 1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	≥10-<20%
EINECS: 217-388-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	5-<10%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1
CAS: 128-37-0	Butylated hydroxytoluene	1-<2.5%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

#### Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 2)

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

#### · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 3)

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
64-17-5 et	64-17-5 ethyl alcohol		
WEL Long	WEL Long-term value: 1920 mg/m³, 1000 ppm		
· DNELs	· DNELs		
128-37-01	128-37-0 Butylated hydroxytoluene		
Dermal	DNEL dermal	0.5 mg/kg bw/day (man)	
Inhalative	DNEL inhalation	3.5 mg/m3 (man)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· Respiratory protection: Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 4)

#### · Protection of hands:



### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties		
· General Information · Appearance:		
Appearance. Form:	Liquid	
Colour:	According to product specification	
· Odour:	Alcohol-like	
· Odour threshold:	Not determined.	
· pH-value at 20 °C:	1.5	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	Undetermined.	
· Flash point:	30 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	Undetermined.	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	0.98 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	

(Contd. on page 6)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

		(Contd. of page
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	31.0 %	
Water:	30.0 %	
VOC (EC)	430.3 g/l	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

Trente tott	The state to the state of the s		
· LD/LC50	· LD/LC50 values relevant for classification:		
64-17-5 et	64-17-5 ethyl alcohol		
Oral	LD50	7,060 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	20,000 mg/l (rat (f+m))	
128-37-0	128-37-0 Butylated hydroxytoluene		
Oral	LD50	>6,000 mg/kg (rat (f+m)) (OECD 401)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 6)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

#### 128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1993
- · 14.2 UN proper shipping name
- · ADR 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL SOLUTION)

• IMDG, IATA FLAMMABLE LIQUID, N.O.S. (ETHANOL SOLUTION)

(Contd. on page 8)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 7) · 14.3 Transport hazard class(es)  $\cdot ADR$ · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA III14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 30 · EMS Number: *F-E,<u>S-E</u>* · Stowage Category A· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LO) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category 3 D/E· Tunnel restriction code · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL · UN "Model Regulation": SOLUTION), 3, III

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 8)

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1: Skin corrosion/irritation – Category I

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

#### · Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* \* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part.

(Contd. on page 10)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Adhesive Enhancing Primer

(Contd. of page 9)

Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GB -



Version number 1 Revision: 27.07.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: G-CEM ONE Paste A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00

- Fax + 32/(0)16/40.26.84
- msds@gc.dental
- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Skin Irrit. 2 H315 Causes skin irritation. Eve Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms



· Signal word Warning

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 1)

#### · Hazard-determining components of labelling:

*Urethane Dimethacrylate (UDMA)* 

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

*P273* Avoid release to the environment.

*P280* Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	≥10-<20%
EINECS: 217-388-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 72869-86-4	Urethane Dimethacrylate (UDMA)	10-<25%
EINECS: 276-957-5	Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
CAS: 13463-67-7	titanium dioxide	0.5-<1%
EINECS: 236-675-5	substance with a Community workplace exposure limit	
CAS: 1879-09-0	6-tert-butyl-2,4-xylenol	0.1-<0.2%
EINECS: 217-533-1	Acute Tox. 2, H310; STOT RE 2, H373; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	0.1-<0.2%
EINECS: 278-355-8	Repr. 2, H361f	
Index number: 015-203-00-X		

Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 2)

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

#### · After skin contact:

*Immediately wash with water and soap and rinse thoroughly.* 

Seek medical treatment.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

*Use fire extinguishing methods suitable to surrounding conditions.* 

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB ·

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 3)

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 13463-67-7 titanium dioxide

WEL Long-term value: 10\* 4\*\* mg/m³
\*total inhalable \*\*respirable

· DNELs

13463-67-7 titanium dioxide

Inhalative DNEL inhalation 10 mg/m3 (man)

1879-09-0 6-tert-butyl-2,4-xylenol

Inhalative DNEL inhalation 0.14 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020


Trade name: G-CEM ONE - Paste A

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



0.11	cal properties
9.1 Information on basic physical and c	hemical properties
General Information Appearance:	
Form:	Pasty
Colour:	Light yellow
Odour:	Ester-like
Odour threshold:	Not determined.
pH-value at 20 °C:	6.5
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Undetermined.
Flash point:	93 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	$1.9 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 6)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 5)

· Solvent content:

**VOC (EC)** 0.0 g/l

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
72869-86-	72869-86-4 Urethane Dimethacrylate (UDMA)		
Oral	LD50	>5,000 mg/kg (rat female) (OECD 401)	
13463-67-	7 titanium	dioxide	
Oral	LD50	>5,000 mg/kg (mouse) (OECD 420)	
Inhalative	LC50/4 h	50/4 h >6.82 mg/l (rat male)	
1879-09-0	1879-09-0 6-tert-butyl-2,4-xylenol		
Oral	LD50	910 mg/kg (rat (f+m)) (OECD 401)	
Dermal	LD50	<200 mg/kg (rabbit) (OECD 402)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB ·

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 6)

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

#### 72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	not regulated
14.2 UN proper shipping name	
ADR, IMDG, IATA	not regulated
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	not regulated
14.4 Packing group	
ADR, IMDĞ, IATA	not regulated
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 7)

· UN "Model Regulation":

not regulated

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

- · Relevant phrases
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity oral Category 4
- Acute Tox. 2: Acute toxicity dermal Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- Skin Sens. 1B: Skin sensitisation Category 1B
- Repr. 2: Reproductive toxicity Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2
- $\label{lem:aquatic chronic 2: Hazardous to the aquatic environment long-term\ aquatic\ hazard-Category\ 2$
- Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3

(Contd. on page 9)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste A

(Contd. of page 8)

- ·Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* \* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GB ·



Print<mark>ing date 27.0</mark>7.<mark>20</mark>20 Version number 1 Revision: 27.07.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: G-CEM ONE Paste B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax +32/(0)16/40.26.84

- msds@gc.dental

   Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms







GHS05 GHS07

CHS

· **Signal word** Danger

(Contd. on page 2)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 1)

#### · Hazard-determining components of labelling:

*Urethane Dimethacrylate (UDMA)* 

#### · Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P260 Do not breathe dusts or mists.

*P280 Wear protective gloves/protective clothing/eye protection/face protection.* 

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

*P321* Specific treatment (see on this label).

*P362+P364 Take off contaminated clothing and wash it before reuse.* 

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 72869-86-4	Urethane Dimethacrylate (UDMA)	25-<50%
EINECS: 276-957-5	Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
CAS: 1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	5-<10%
EINECS: 217-388-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	2.5-<5%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 80-15-9	α,α -dimethylbenzyl hydroperoxide	0.5-<1%
EINECS: 201-254-7	Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin	
Index number: 617-002-00-8		
	Acute Tox. 4, H312	
CAS: 1879-09-0	6-tert-butyl-2,4-xylenol	≥0.2-<0.25%
EINECS: 217-533-1	Acute Tox. 2, H310; STOT RE 2, H373; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Index number: 617-002-00-8  CAS: 1879-09-0  EINECS: 217-533-1	Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312  6-tert-butyl-2,4-xylenol Acute Tox. 2, H310; STOT RE 2, H373; Aquatic Chronic 2, H411;	≥0.2-<0.2

· Additional information: For the wording of the listed hazard phrases refer to section 16.

– GI

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 2)

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

· General information:

*Immediately remove any clothing soiled by the product.* 

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

(Contd. on page 4)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 3)

#### · 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### · DNELs

#### 1879-09-0 6-tert-butyl-2,4-xylenol

Inhalative DNEL inhalation 0.14 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 4)

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Ph	ysical and	l chemical	properties
---------------	------------	------------	------------

9.1 Information on basic physical and chemical properties		
· General Information	1 1	
· Appearance:		
Form:	Pasty	
Colour:	White	
· Odour:	Ester-like	
· Odour threshold:	Not determined.	
· pH-value at 20 °C:	1.5	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	: Undetermined.	
· Flash point:	93 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
Density at 20 °C:	$1.5 \text{ g/cm}^3$	
Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 5)

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC (EC) 0.0 g/l

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	· LD/LC50 values relevant for classification:			
72869-86-4	72869-86-4 Urethane Dimethacrylate (UDMA)			
Oral	LD50	>5,000 mg/kg (rat female) (OECD 401)		
80-15-9 α,	80-15-9 α,α -dimethylbenzyl hydroperoxide			
Oral	LD50	382 mg/kg (rat (f+m))		
Dermal	LD50	500 mg/kg (rat (f+m))		
Inhalative	LC50/4 h	220 mg/l (rat (f+m))		
1879-09-0	6-tert-buty	yl-2,4-xylenol		
Oral	LD50	910 mg/kg (rat (f+m)) (OECD 401)		
Dermal	LD50	<200 mg/kg (rabbit) (OECD 402)		

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### 72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information			
· 14.1 UN-Number · ADR, IMDG, IATA	UN3082		
· 14.2 UN proper shipping name			
· ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE		
	LIQUID, N.O.S. (Urethane Dimethacrylate (UDMA))		
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID		
	N.O.S. (Urethane Dimethacrylate (UDMA), α,α -dimethylbenzy		
	hydroperoxide), MARINE POLLUTANT		
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID		
	N.O.S. (Urethane Dimethacrylate (UDMA))		

(Contd. on page 8)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 7) · 14.3 Transport hazard class(es)  $\cdot ADR$ · Class 9 (M6) Miscellaneous dangerous substances and articles. · Label · IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles. · Label · 14.4 Packing group · ADR, IMDG, IATA III· 14.5 Environmental hazards: · Marine pollutant: No Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. · Hazard identification number (Kemler code): 90 F-A,S-F· EMS Number: · Stowage Category A· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information:  $\cdot ADR$ · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category 3 · Tunnel restriction code  $\cdot$  IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml (Contd. on page 9)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 8)

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (URETHANE DIMETHACRYLATE (UDMA)), 9, III

#### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

- · Relevant phrases
- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 2: Acute toxicity - dermal - Category 2

Acute Tox. 3: Acute toxicity - inhalation - Category 3

(Contd. on page 10)

Printing date 27.07.2020 Version number 1 Revision: 27.07.2020

Trade name: G-CEM ONE - Paste B

(Contd. of page 9)

Skin Corr. 1: Skin corrosion/irritation – Category 1
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

#### · Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* Data compared to the previous version altered.

This version replaces all previous versions.

#### Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

CD.





Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

\*

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: G-MULTI PRIMER
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V.
Interleuvenlaan 33
B-3001 Leuven
Tel. +32/(0)16/74.10.00
Fax +32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

\*

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device. The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

2 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

2,2'-ethylenedioxydiethyl dimethacrylate

(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate

(Contd. on page 2)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 1)

#### · Hazard statements

H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*Avoid breathing dust/fume/gas/mist/vapours/spray.* 

P272 Contaminated work clothing should not be allowed out of the workplace.

*P280* Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 64-17-5	ethyl alcohol	90-<100%
EINECS: 200-578-6	Flam. Liq. 2, H225	
Index number: 603-002-00-5		
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	1-<2.5%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate	1-<2.5%
EINECS: 203-652-6	Skin Sens. 1, H317	
CAS: 1565-94-2	(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-	0.5-<1%
EINECS: 216-367-7	propanediyl)] bismethacrylate	
	Eye Dam. 1, H318; Skin Sens. 1, H317	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Generally the product does not irritate the skin.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 2)

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

*If symptoms persist consult doctor.* 

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

*Use fire extinguishing methods suitable to surrounding conditions.* 

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Allow to evaporate.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 3)

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

### 64-17-5 ethyl alcohol

WEL Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 4)

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical proper	rties
---	-------

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

· pH-value:

Form: Liquid
Colour: Colourless
Odour: Alcohol-like
Odour threshold: Not determined.

· Change in condition

Melting point/freezing point: -114.5 °C

Undetermined.

Not determined.

*Initial boiling point and boiling range:* 78 °C

Undetermined.

· Flash point: 13 °C

Not applicable.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 425 °C

Undetermined.

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

(Contd. on page 6)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

	(Cont	d. of page
Explosion limits:		
Lower:	3.5 Vol %	
	Not determined.	
Upper:	15 Vol %	
	Not determined.	
Vapour pressure at 20 °C:	59 hPa	
•	Not determined.	
Density at 20 °C:	0.8 g/cm³	
•	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water at 20 °C:	1.000  g/l	
	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	92.0 %	
VOC (EC)	736.2 g/l	
9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
64-17-5 eti	hyl alcohol		
Oral	LD50	7,060 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	20,000  mg/l  (rat  (f+m))	

- · Primary irritant effect:
- · Skin corrosion/irritation No further relevant information available
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 6)

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION IT. HUMSPOIL INVINUED	<b>SECTION</b>	14: Tra	insport in	formation
-------------------------------	----------------	---------	------------	-----------

•	14.1	UN-	Num	ber
---	------	-----	-----	-----

· ADR, IMDG, IATA UN1170

· 14.2 UN proper shipping name

· ADR 1170 ETHANOL SOLUTION mixture · IMDG, IATA ETHANOL SOLUTION mixture

(Contd. on page 8)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

	(Contd. of pa
14.3 Transport hazard class(es)	
ADR	
***	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33 F.F.G.D.
EMS Number:	F- $E$ , $S$ - $D$
Stowage Category	A
14.7 Transport in bulk according to Anne	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
_	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1170 ETHANOL SOLUTION MIXTURE, 3, II

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 8)

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eve irritation.

H335 May cause respiratory irritation.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

- · Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* \* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part.

(Contd. on page 10)

Printing date 02.08.2018 Version number 3 Revision: 12.09.2017

Trade name: G-MULTI PRIMER

(Contd. of page 9)

Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GB