

Printing date 31.05.2019 Revision: 11.04.2019

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Composite Wetting Resin

· Article number: 13575

· Index number: SDS 67-001.08

· Relevant identified uses of the substance or mixture and uses advised against Professional Dental Liquid Resin

· Application of the substance / the mixture Professional Dental Liquid Resin

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support@utradent.com

EC Responsible Person

Ultradent Products GmbH

Am Westhover Berg 30

51149 Cologne Germany

Email: infoDe@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

· Further information obtainable from: Customer Service

· Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The Regulation EC 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) shall not apply to a medical device in the finished state used in direct physical contact with the human body according to Art. 1.5 (d). Therefore, the product is exempted from the CLP labeling requirements, and no SDS is required by Regulation 1907/2006, Art. 2 (6c), REACH. Therefore, all given data, classification, and information on this SDS are provided solely on a voluntary basis.

- · Hazard pictograms GHS07
- · Signal word Warning
- · Hazard-determining components of labelling:

Triethylene Glycol Dimethacrylate

Diurethane Dimethacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

(Contd. of page 1)

- P102 Keep out of reach of children.
- P103 Read label before use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
	Triethylene Glycol Dimethacrylate	>10-≤25%
EINECS: 203-652-6	♦ Skin Sens. 1, H317	
	Diurethane Dimethacrylate	>10-≤25%
EINECS: 276-957-5	💠 Skin Sens. 1, H317	
CAS: 2530-85-0	Silane	<i>≤10%</i>
EINECS: 219-785-8	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 128-37-0	Butylated Hydroxytoluene	<1%
EINECS: 204-881-4	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; <page-header> Acute Tox. 4, H302</page-header>	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Seek medical treatment in case of complaints.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If swallowed in large quantities seek medical attention.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Foam, dry chemical, carbon dioxide

(Contd. on page 3)

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

(Contd. of page 2)

Use fire extinguishing methods suitable to surrounding conditions.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters:
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from exposure to the light.

Protect from heat and direct sunlight.

See product labelling.

· Specific end use(s) Professional Dental Liquid Resin

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

128-37-0 Butylated Hydroxytoluene

WEL (Great Britain) Long-term value: 10 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

(Contd. on page 4)

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

(Contd. of page 3)

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eve protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

() Dlanar and	0.00	0.0000000000000000000000000000000000000		an areda are
y Physical		4 F UI 11 I FUI I		novitos
9 Physical	tuitu Ci	t C I I I I C II I	ν	

· Information on basic physical and chem · General Information	ical properties
· Appearance:	
Form:	Gel
Colour:	Yellow tint
· Odour:	Acrylic
· Odour threshold:	Not determined.
· pH-value:	Not applicable (non-aqueous)
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.54 g/cm^3
Relative density	Not determined.
	(Contd. on maga

(Contd. on page 5)

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

		(Contd. of page
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC (EC)	0.00 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid:

Light

Heat

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	•	
· LD/LC5	0 values rel	evant for classification:
109-16-	0 Triethylen	ne Glycol Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
	LC50 Fish	16.4 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (mouse)
72869-8	6-4 Diureth	ane Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
128-37-	0 Butylated	Hydroxytoluene
Oral	LD50	10,700 mg/kg (Guinea pig)
		1,040 mg/kg (mouse)
		890 mg/kg (rat)
	LC50 Fish	5.3 mg/l (Fish)
Dermal	LD50	>2,000 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

(Contd. on page 6)

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

(Contd. of page 5)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

Toxicity	
· Aquatic toxicity:	
109-16-0 Triethylen	ne Glycol Dimethacrylate
Biodegradability	28 days (Aerobic) (Biodegradability testing)
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)
EC50	>100 mg/l (Algae) (Toxicity to algae)
72869-86-4 Diureth	ane Dimethacrylate
Biodegradability	28 days (Aerobic) (Biodegradability testing)
EC50	>0.6 mg/l (Algae) (Toxicity to algae)
	>1.2 mg/l (daphnia) (Toxicity to aquatic invertebrates)
128-37-0 Butylated	Hydroxytoluene
Aqua toxicity (static	0.48 mg/l (daphnia) (Toxicity to aquatic invertebrates)

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Do not allow product to reach sewage system.
- European waste catalogue

HP 13 Sensitising

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GR'

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

(Contd. of page 6)

UN-Number		
ADR, ADN, IMDG, IATA	not regulated	
UN proper shipping name ADR, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
ADR, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex I	I of Marpol	
and the IBC Code	Not applicable.	
UN "Model Regulation":	not regulated	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory Affairs
- · Contact: Customer Service
- · Abbreviations and acronvms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 8)

Printing date 31.05.2019 Revision: 11.04.2019

Trade name: Composite Wetting Resin

(Contd. of page 7)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1