



Safety Data Sheet

Copyright, 2017, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	18-9028-4	Version number:	13.00
Revision date:	02/06/2017	Supersedes date:	02/09/2016
Transportation version number:	1.00 (26/07/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M ESPE ADPER SCOTCHBOND 1 XT

Product Identification Numbers

70-2010-3675-6

7000054284

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Dental Product

Restrictions on Use

For use only by dental professionals

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

This product is a medical device as defined in Directive 93/42/EEC (MDD), which is invasive or used in direct physical contact with the human body, and therefore is exempt from the requirements of classification and labelling according to Regulation (EC) No. 1272/2008 (CLP; Article 1, paragraph 5). Although not required, the classification and label information, as applicable, is provided below.

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Skin Sensitization, Category 1B - Skin Sens. 1B; H317

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	% by Wt
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	10 - 20
2-Hydroxyethyl methacrylate	868-77-9	5 - 15
2-Hydroxy-1,3-propanediyl bismethacrylate	1830-78-0	5 - 10
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate	72869-86-4	1 - 5

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

2.3. Other hazards

For information on hazards and safe use, please consider the corresponding sections of this document.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Ethanol	64-17-5	200-578-6		25 - 35	Flam. Liq. 2, H225 Eye Irrit. 2, H319
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	216-367-7		10 - 20	Skin Sens. 1B, H317
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	None			10 - 20	Substance not classified as hazardous
2-Hydroxyethyl methacrylate	868-77-9	212-782-2	01-2119490169-29	5 - 15	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 - Nota D
2-Hydroxy-1,3-propanediyl bismethacrylate	1830-78-0	217-388-4		5 - 10	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335
2-Propenoic acid, polymer with methylenebutanedioic acid	25948-33-8			5 - 10	Substance not classified as hazardous
Non-Hazardous Ingredients	Mixture			< 5	Substance not classified as hazardous
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate	72869-86-4	276-957-5		1 - 5	Skin Sens. 1B, H317
Diphenyliodonium hexafluorophosphate	58109-40-3	261-134-5		< 1	Acute Tox. 2, H300
Ethyl 4-dimethylaminobenzoate	10287-53-3	233-634-3		< 1	Substance not classified as hazardous

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

3M ESPE ADPER SCOTCHBOND 1 XT**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethanol	64-17-5	UK HSC	TWA:1920 mg/m ³ (1000 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
2-Hydroxyethyl methacrylate		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	1.3 mg/kg bw/d
2-Hydroxyethyl methacrylate		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	4.9 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
2-Hydroxyethyl methacrylate		Agricultural soil	0.476 mg/kg d.w.
2-Hydroxyethyl methacrylate		Freshwater	0.482 mg/l
2-Hydroxyethyl methacrylate		Freshwater sediments	3.79 mg/kg d.w.
2-Hydroxyethyl methacrylate		Intermittent releases to water	1 mg/l
2-Hydroxyethyl methacrylate		Marine water	0.482 mg/l
2-Hydroxyethyl methacrylate		Marine water sediments	3.79 mg/kg d.w.
2-Hydroxyethyl methacrylate		Sewage Treatment Plant	10 mg/l

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Appearance/Odour	Slight acrylate odour, white to clear
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Boiling point/boiling range	78 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	18.5 °C [<i>Test Method:Closed Cup</i>]
Autoignition temperature	410 °C
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	1.075 [<i>Ref Std:WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.075 g/ml

9.2. Other information

Molecular weight	<i>No data available.</i>
Percent volatile	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin. Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

3M ESPE ADPER SCOTCHBOND 1 XT

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Additional information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Dermal	Rabbit	LD50 > 2,000 mg/kg
Ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg
Ethanol	Inhalation-Vapour (4 hours)	Rat	LC50 124.7 mg/l
Ethanol	Ingestion	Rat	LD50 17,800 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Ingestion	Rat	LD50 > 5,110 mg/kg
2-Hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
2-Hydroxy-1,3-propanediyl bismethacrylate	Ingestion	similar compounds	LD50 300-2000 mg/kg
2-Propenoic acid, polymer with methylenebutanedioic acid	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Propenoic acid, polymer with methylenebutanedioic acid	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Diphenyliodonium hexafluorophosphate	Ingestion	Rat	LD50 32 mg/kg
Ethyl 4-dimethylaminobenzoate	Dermal	Rat	LD50 > 2,000 mg/kg

3M ESPE ADPER SCOTCHBOND 1 XT

Ethyl 4-dimethylaminobenzoate	Ingestion	Rat	LD50 > 2,000 mg/kg
-------------------------------	-----------	-----	--------------------

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Ethanol	Rabbit	No significant irritation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Not available	Minimal irritation
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Rabbit	No significant irritation
2-Hydroxyethyl methacrylate	Rabbit	Minimal irritation
Diphenyliodonium hexafluorophosphate	Rabbit	No significant irritation
Ethyl 4-dimethylaminobenzoate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Ethanol	Rabbit	Severe irritant
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Not available	Moderate irritant
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Rabbit	No significant irritation
2-Hydroxyethyl methacrylate	Rabbit	Moderate irritant
Diphenyliodonium hexafluorophosphate	Rabbit	Mild irritant
Ethyl 4-dimethylaminobenzoate	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Ethanol	Human	Not classified
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Guinea pig	Sensitising
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Human and animal	Not classified
2-Hydroxyethyl methacrylate	Human and animal	Sensitising
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	In Vitro	Not mutagenic
2-Hydroxyethyl methacrylate	In vivo	Not mutagenic
2-Hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diphenyliodonium hexafluorophosphate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

3M ESPE ADPER SCOTCHBOND 1 XT

Name	Route	Species	Value
Ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethanol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	prematuring & during gestation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-Hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-Hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-Hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
Ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
2-Propenoic acid, polymer with methylenebutanedioic	Ingestion	nervous system	Not classified	Rat	NOAEL 5,000 mg/kg	

3M ESPE ADPER SCOTCHBOND 1 XT

acid						
Diphenyliodonium hexafluorophosphate	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
Ethanol	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
Ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	endocrine system liver nervous system kidney and/or bladder	Not classified	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2-Propenoic acid, polymer with methylenebutanedioic acid	Ingestion	endocrine system hematopoietic system liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
2-Propenoic acid, polymer with methylenebutanedioic acid	Ingestion	heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
2-Hydroxy-1,3-	1830-78-0	Guppy	Experimental	96 hours	LC50	43.2 mg/l

3M ESPE ADPER SCOTCHBOND 1 XT

propanediyl bismethacrylate						
Diphenyliodonium hexafluorophosphate	58109-40-3	Water flea	Experimental	48 hours	EC50	9.5 mg/l
Ethanol	64-17-5	Water flea	Experimental	48 hours	EC50	9,300 mg/l
Ethanol	64-17-5	Green algae	Experimental	96 hours	EC50	1,000 mg/l
Ethanol	64-17-5	Rainbow trout	Experimental	96 hours	LC50	42 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
Ethyl 4-dimethylamino benzoate	10287-53-3	Fathead minnow	Estimated	96 hours	LC50	8.8 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Green Algae	Experimental	72 hours	EC50	345 mg/l
Ethanol	64-17-5	Water flea	Experimental	11 days	NOEC	9.6 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-Hydroxyethyl methacrylate	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate	72869-86-4		Data not available or insufficient for classification			
2-Propenoic acid, polymer with methylenebutanedioic acid	25948-33-8		Data not available or insufficient for classification			
Amorphous silica (7631-86-9) surface modified with organofunctional silane and methacryloxypropyltrimethoxysilane (2530-85-0)	None		Data not available or insufficient for classification			
(1-methylethylidene)bis[4,1-phenyleneoxy(1565-94-2		Data not available or insufficient for classification			

3M ESPE ADPER SCOTCHBOND 1 XT

2-hydroxy-3,1-propanediyl] bismethacrylate						
--	--	--	--	--	--	--

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethyl 4-dimethylamino benzoate	10287-53-3	Estimated Biodegradation	28 days	BOD	29 % weight	OECD 301C - MITI test (I)
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Estimated Biodegradation	28 days	BOD	33 % weight	OECD 301C - MITI test (I)
2-Hydroxy-1,3-propanediyl bismethacrylate	1830-78-0	Experimental Biodegradation	28 days	BOD	84 % weight	OECD 301F - Manometric respirometry
2-Propenoic acid, polymer with methylenebutanedioic acid	25948-33-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diphenyliodonium hexafluorophosphate	58109-40-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethanol	64-17-5	Experimental Biodegradation	14 days	BOD	89 % weight	OECD 301C - MITI test (I)
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate	72869-86-4	Estimated Biodegradation	28 days	BOD	52 % weight	OECD 301C - MITI test (I)
2-Hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life	10.9 days (t _{1/2})	Other methods
2-Hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	14 days	BOD	95 % weight	OECD 301C - MITI test (I)
Amorphous silica (7631-86-9) surface modified with organofunctional silane and	None	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M ESPE ADPER SCOTCHBOND 1 XT

methacryloxypropyltrimethoxysilane (2530-85-0)						
--	--	--	--	--	--	--

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethyl 4-dimethylamino benzoate	10287-53-3	Estimated Bioconcentration		Bioaccumulation factor	19	Estimated: Bioconcentration factor
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Hydroxy-1,3-propanediyl bismethacrylate	1830-78-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Propenoic acid, polymer with methylenebutanedioic acid	25948-33-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diphenyliodonium hexafluorophosphate	58109-40-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethanol	64-17-5	Experimental Bioconcentration		Log Kow	-0.31	Other methods
7,7,9(or 7,9,9)-Trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate	72869-86-4	Estimated Bioconcentration		Bioaccumulation factor	5	Estimated: Bioconcentration factor
2-Hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.47	Other methods
Amorphous silica (7631-86-9) surface modified with organofunctional silane and	None	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M ESPE ADPER SCOTCHBOND 1 XT

methacryloxypropyltrimethoxysilane (2530-85-0)						
--	--	--	--	--	--	--

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
ethyl alcohol	64-17-5	0	
Non-Hazardous Ingredients	Mixture	0	

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

180106* Chemicals consisting of or containing dangerous substances.

SECTION 14: Transportation information

70-2010-3675-6

ADR/RID: DANGEROUS GOODS IN EXCEPTED QUANTITIES, CLASS 3, II, (--).

IMDG-CODE: UN1133, ADHESIVES, 3, II, IMDG-Code segregation code: NONE, Dangerous Goods in excepted Quantities, EMS: FE,SD.

ICAO/IATA: DANGEROUS GOODS IN EXCEPTED QUANTITIES OF CLASS 3, UN1133, II.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information.

15.2. Chemical Safety Assessment

A chemical safety assessment has been carried out for the relevant substances in this material by the registrant in accordance with regulation REGULATION (EC) No 1907/2006

SECTION 16: Other information**List of relevant H statements**

H225	Highly flammable liquid and vapour.
H300	Fatal if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Revision information:

Professional Mixing and Application: Section 16: Annex information was added.
 Section 01: SAP Material Numbers information was added.
 Section 3: Composition/ Information of ingredients table information was added.
 Section 3: Composition/ Information of ingredients table information was deleted.
 Section 8: 8.2. Exposure controls information information was added.
 Section 8: 8.2.3. Environmental exposure controls information information was added.
 Section 8: DNEL table row information was added.
 Section 8: PNEC table row information was added.
 Section 11: Acute Toxicity table information was modified.
 Section 11: Carcinogenicity Table information was modified.
 Section 11: Germ Cell Mutagenicity Table information was modified.
 Section 11: Reproductive Toxicity Table information was modified.
 Section 11: Serious Eye Damage/Irritation Table information was modified.
 Section 11: Skin Corrosion/Irritation Table information was modified.
 Section 11: Skin Sensitization Table information was modified.
 Section 11: Target Organs - Repeated Table information was modified.
 Section 11: Target Organs - Single Table information was modified.
 Section 12: Component ecotoxicity information information was modified.
 Section 12: Persistence and Degradability information information was modified.
 Section 12: Biocumulative potential information information was modified.
 Section 15: Chemical Safety Assessment information was modified.
 Annex: Prediction of exposure statement information was added.

Annex

1. Title	
Substance identification	2-Hydroxyethyl methacrylate; EC No. 212-782-2; CAS Nbr 868-77-9;
Exposure Scenario Name	Hand-mixing of preparations, e.g. plasters, resins, two-component adhesives.
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 0 -Other Process or activity ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Application of substances/mixtures by dentist to patient's mouth on the dental hard tissue. Manual application of product.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Indoors with good general ventilation;

Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Protective Gloves - Chemical resistant; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk