

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

I Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: PeakTM Universal Bond
- · Article number: SDS 206-001.13, 71057
- Relevant identified uses of the substance or mixture and uses advised against Professional Dental Adhesive
- · Application of the substance / the mixture Professional Dental Adhesive
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

onlineordersupport@ultradent.com

EC Responsible Person

Ultradent Products GmbH

Am Westhover Berg 30

51149 Cologne Germany

Email: infoDE@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

- · Further information obtainable from: Customer Service
- · Emergency telephone number:

During normal opening times: +1 (801) 553-4862 CHEMTREC (NORTH AMERICA) :(800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms GHS02, GHS05, GHS07
- · Signal word Danger

· Hazard-determining components of labelling:

Methacrylic Acid

2-Hydroxyethyl Methacrylate

Trade Secret

Organophosphine Oxide

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

- · Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 64-17-5	Ethyl Alcohol	>10-≤25%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225	
CAS: 868-77-9	2-Hydroxyethyl Methacrylate	>10- ≤ 25%
EINECS: 212-782-2	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 79-41-4	Methacrylic Acid	≥5-≤10%
EINECS: 201-204-4	 Acute Tox. 3, H331; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312 Specific concentration limit: STOT SE 3; H335: C ≥ 1 % 	
	Trade Secret	≥1-<5%
	🔷 Skin Corr. 1A, H314	

(Contd. on page 3)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

	Organophosphine Oxide Skin Sens. 1A, H317; Aquatic Chronic 4, H413	(Contd. of page 2) ≥0.1-<1%
CAS: 56-95-1	Chlorhexidine Diacetate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥0.025-<0.25%
	Butylated Hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥0.025-<0.25%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Foam, dry chemical, carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters:
- · Protective equipment:

General: Evacuate all personnel; use protective equipment for fire fighting. Use self-contained breathing apparatus when the product is involved in fire.

Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

(Contd. of page 3)

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling:

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

See product labelling.

Keep container tightly sealed.

· Specific end use(s) Professional Dental Adhesive

8 Exposure controls/personal protection

· Control parameters

T 10 / 1/	1 10 0, 1	.1 .	•, •	, ,1 1 1
· Ingredients wit	n limit valu <i>o</i> s	s that roamre	MANITATING	at the workplace:
THE CUICIUS WILL	i iiiiiii ruiiics	, mun require	III OII II OI III E	ui iiic woinpiucc.

64-17-5 Ethyl Alcohol

WEL Long-term value: 1920 mg/m³, 1000 ppm

79-41-4 Methacrylic Acid

WEL Short-term value: 143 mg/m³, 40 ppm Long-term value: 72 mg/m³, 20 ppm

128-37-0 Butylated Hydroxytoluene

WEL Long-term value: 10 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Ddour:
Acrylic

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 60 °C

· Flammability Flammable.

· Lower and upper explosion limit

Lower: 3.5 Vol %
 Upper: 15 Vol %
 Flash point: 24 °C
 Ignition temperature: 425 °C

• **Decomposition temperature:** Not determined.

· pH Not applicable (non-aqueous)

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 59 hPa

· Density and/or relative density

• Density at 20 °C: 1.1 g/cm³
• Relative density Not determined.

(Contd. on page 6)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

	(Contd. of page
· Vapour density	Not determined.
Other information	
· Appearance:	
Form:	Liquid
Important information on protection of heal	th and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	<20.00 %
Solids content:	<15.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard clas	Sses
· Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	e gases
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

GB

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

(Contd. of page 6)

Informatio Acute toxi		s as defined in Regulation (EC) No 1272/2008	
	values relevant for	classification:	
	te Toxicity Estimate	•	
•	LD50	17,667 mg/kg	
Dermal	LD50	8,333 mg/kg (rabbit)	
Inhalative	LC50/4 h	118 mg/l	
64-17-5 E1	thyl Alcohol		
Oral	LD50	5,600 mg/kg (Guinea pig)	
		3,400 mg/kg (mouse)	
		7,060 mg/kg (rat)	
	LC50 Fish	>10,000 mg/l (Fish)	
Inhalative	LC50/4 h	39 mg/l (mouse)	
		20,000 mg/l (rat)	
868-77-9 2	-Hydroxyethyl Mei	9 , ,	
Oral	LD50	3,275 mg/kg (mouse)	
		>5,000 mg/kg (rat)	
	LC50 Fish	>100 mg/l (Fish)	
Dermal	LD50	>3,000 mg/kg (rabbit)	
	LC50(Daphnia ma	gna) 24.1 mg/l (daphnia)	
79-41-4 M	ethacrylic Acid		
Oral	LD50	1,250 mg/kg (mouse)	
		1,060 mg/kg (rat)	
		1,200 mg/kg (rabbit)	
	LC50 Fish	86 mg/l (Fish)	
Dermal	LD50	1,000 mg/kg (Guinea pig)	
		500 mg/kg (rabbit)	
Inhalative	LC50/4 h	7.1 mg/l (rat)	
162881-26	-7 Organophosphii	ne Oxide	
Oral	LD50	>2,000 mg/kg (rat)	
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)	
Dermal	LD50	>2,000 mg/kg (rat)	
56-95-1 Cl	hlorhexidine Diace	tate	
Oral	LD50	2,000 mg/kg (mouse)	
		1,180 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
	Butylated Hydroxyt		
Oral	LD50	10,700 mg/kg (Guinea pig)	
		1,040 mg/kg (mouse)	
		890 mg/kg (rat)	

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

| Dermal | LD50 | >2,000 mg/kg (rat) | (Contd. of page 7)

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation.
- Information on other hazards
- · Endocrine disrupting properties

128-37-0 Butylated Hydroxytoluene

List II

12 Ecological information

· Toxicity

· Aquatic toxicity:	
64-17-5 Ethyl Alcohol	
Algae Toxicity	1,000 mg/l (Algae)
868-77-9 2-Hydroxyethyl Methac	rylate
EC50	345 mg/kg (Algae)
79-41-4 Methacrylic Acid	
EC50	17,000 mg/kg (Algae)
	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
162881-26-7 Organophosphine C	Dxide
EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)
Toxicity to Aquatic Plants (static)	>0.26 mg/l (Plant) (Toxicity to algae)
128-37-0 Butylated Hydroxytolue	ene
Aqua toxicity (static)	0.48 mg/l (daphnia) (Toxicity to aquatic invertebrates)

- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Dispose of contents/container in accordance with international, federal, state, and local regulations.

(Contd. on page 9)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

(Contd. of page 8)

• Uncleaned packaging:
• Recommendation: Disposal must be made according to official regulations.

UN number or ID number ADR, IMDG, IATA	UN2924
UN proper shipping name ADR IMDG, IATA	2924 FLAMMABLE LIQUID, CORROSIVE, N.O. (METHACRYLIC ACID, STABILIZED, Ethyl Alcohol) FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHACRYL
Transport hazard class(es)	ACID, STABILIZED, Ethyl Alcohol)
ADR	
Class Label	3 Flammable liquids. 3+8
IMDG	
Class	3 Flammable liquids.
Label	3/8
Class Label	3 Flammable liquids. 3 (8)
Packing group	
ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code) EMS Number: Stowage Category	Warning: Flammable liquids. 2: 38 F-E,S-C A

(Contd. on page 10)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.,
	(METHACRYLIC ACID, STABILIZED, ETHYL ALCOHOL), 3 (8
	III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · *Directive 2012/18/EU*
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases from Section 3

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service

(Contd. on page 11)

Printing date 01.07.2022 Version number 1 Revision: 01.07.2022

Trade name: PeakTM Universal Bond

(Contd. of page 10)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

* * Data compared to the previous version altered.

GR



Printing date 15.06.2020 Revision: 03.10.2018

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Ultra-Etch™ & Opal™ Etch

· Article number: 10947

· Index number: SDS 7-001.20

· Relevant identified uses of the substance or mixture and uses advised against

Professional Dental Acid Etching Solution

· Application of the substance / the mixture Professional Dental Acid Etching Solution

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support @ultradent.com

EC Responsible Person
Ultradent Products GmbH
Am Westhover Berg 30
51149 Cologne Germany

Email: infoDE@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

· Further information obtainable from: Customer Service

· Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



Acute Tox. 4 H332 Harmful if inhaled.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The Regulation EC 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) shall not apply to a medical device in the finished state used in direct physical contact with the human body according to Art. 1.5 (d). Therefore, the product is exempted from the CLP labeling requirements, and no SDS is required by Regulation 1907/2006, Art. 2 (6c), REACH. Therefore, all given data, classification, and information on this SDS are provided solely on a voluntary basis.

- · Hazard pictograms GHS05, GHS07
- · Signal word Danger

(Contd. on page 2)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

(Contd. of page 1)

· Hazard-determining components of labelling:

Phosphoric Acid

· Hazard statements

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 7664-38-2		<40%		
EINECS: 231-633-2	Acute Tox. 1, H330; Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302			
	Dimethicone	<1%		
	♦ Repr. 2, H361f; STOT RE 2, H373			

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

If swallowed in large quantities seek medical attention.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Dry Chemical

Carbon dioxide

Alcohol resistant foam

Water spray

Use fire extinguishing methods suitable to surrounding conditions.

· Special hazards arising from the substance or mixture

Phosphine, oxides of phosphorous, hydrogen gas

During heating or in case of fire poisonous gases are produced.

Advice for firefighters:

General: Evacuate all personnel.

Use fire extinguishing methods suitable to surrounding conditions.

· Protective equipment:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling:

Safety glasses should be used by the patient and doctor. Use equipment for eye protection tested and approved under appropriate standards such as ANSI Z87.1

(Contd. on page 4)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

(Contd. of page 3)

Avoid contact with eyes, skin, and clothing.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Provide ventilation for receptacles.

Information about storage in one common storage facility:

Store away from water.

Store away from metals.

· Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place.

See product labelling.

Keep container tightly sealed.

· Specific end use(s) Professional Dental Acid Etching Solution

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

7664-38-2 Phosphoric Acid

WEL (Great Britain) Short-term value: 2 mg/m³

Long-term value: 1 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.

Do not eat or drink while working.

When using do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



(Contd. on page 5)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses should be used and by the patient and doctor. Use equipment for eye protection tested and approved under appropriate standards such as ANSI Z87.1



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical	and	chem	ical	propert	ies

· Information on basic physical and chen · General Information	nical properties
· Appearance:	
Form:	Gel
Colour:	Blue
· Odour:	Odourless
· Odour threshold:	Not determined.
· pH-value at 20 °C:	<1
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 100 °C
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.3 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
· Evaporation rate	Not determined.

(Contd. on page 6)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

	(Contd. of pag
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	<60 %
VOC (EC)	0.00 %
Solids content:	<20.0 %
· Other information	Refractive Index 34-37 Brix

10 Stability and reactivity

- · Reactivity Stable
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid:

Water, Moist Air

Extreme heat and open flames.

- · Incompatible materials: Strong caustics, most metals
- · Hazardous decomposition products: Phosphine, oxides of phosphorous, hyrogen gas
- Additional information:

Reacts with bases to form phosphate salts and is corrosive (especially when hot) to many metals and alloys. Liberates exposive hydrogen gas when reacting with chlorides and stainless steel, and reacts violently with sodium tetrahydroborate. Forms flammable gases with sulfides, mercaptans, cyanides and aldehydes. Also forms toxic fumes with cyanides, sulfides, fluorides, organic peroxides and halogenated organics

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:					
ATE (Acute Toxicity Estimates)					
Oral	LD50	4,358 mg/kg (rat)			
Inhalative	LC50/4 h	$0.92 \ mg/l$			

7664-38-2 Phosphoric Acid					
Oral	LD50	1,530 mg/kg (rat)			
Dermal	LD50	2,740 mg/kg (rabbit)			
Inhalative	LC50/4 h	0.42225 mg/l (rabbit)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

(Contd. on page 7)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

(Contd. of page 6)

· Serious eye damage/irritation

Causes severe skin burns and eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste ca

HP6 Acute Toxicity

HP8 Corrosive

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · ADR, IMDG, IATA

UN1805

(Contd. on page 8)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

	(Contd. of page
UN proper shipping name ADR IMDG, IATA	1805 PHOSPHORIC ACID, SOLUTION mixture PHOSPHORIC ACID, SOLUTION mixture
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	8 Corrosive substances.
Label	8
Packing group ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80
EMS Number:	F- A , S - B
Segregation groups	Acids
Stowage Category Segregation Code	A SG36 Stow "separated from" SGG18-alkalis.
Segregation Code	SG49 Stow "separated from" SGG6-cyanides
Transport in bulk according to Annex II of Marp	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1805 PHOSPHORIC ACID, SOLUTION MIXTURE,

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)

Printing date 15.06.2020 Revision: 03.10.2018

Trade name: Ultra-Etch™ & Opal™ Etch

(Contd. of page 8)

· Chemical safety assessment:

Device is a strong acid and is extremely toxic. It is to be used only as directed with PPE, and only by licensed dental professionals.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Regulatory Affairs

· Contact: Customer Service

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 1: Acute toxicity - inhalation - Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

GB2