

CARESTREAM DENTAL X-ray Developer

Carestream Health, Inc.

Chemwatch Hazard Alert Code: 3

Issue Date: **11/07/2022**Print Date: **04/05/2023**S.REACH.GB.EN

Part Number: 5060686 Version No: 1.1 Safety data sheet according to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	CARESTREAM DENTAL X-ray Developer			
Chemical Name	Not Applicable			
Synonyms	ailable			
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains Hydroquinone)			
Chemical formula	Not Applicable			
Other means of identification	Not Available			

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Photographic chemical Restricted to professional users. Use according to manufacturer's directions.
Uses advised against No specific uses advised against are identified.	

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Carestream Health, Inc.				
Address	50 Verona Street Rochester, NY 14608 United States				
Telephone	-328-2910				
Fax	ot Available				
Website	www.carestream.com				
Email	WW-EHS@carestreamhealth.com				

1.4. Emergency telephone number

Association / Organisation	CHEMTREC (North America)			
Emergency telephone numbers	+1-800-424-9300			
Other emergency telephone numbers	CHEMTREC (International) +1-703-527-3887			

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 [1]	H400 - Hazardous to the Aquatic Environment Acute Hazard Category 1, H318 - Serious Eye Damage/Eye Irritation Category 1, H360FD - Reproductive Toxicity Category 1B, H317 - Sensitisation (Skin) Category 1, H341 - Germ Cell Mutagenicity Category 2, H351 - Carcinogenicity Category 2
Lamandi	1. Classified by Chamwatah; 2. Classification drawn from C.P. Cl. P. Dogylation, LIK \$1,2040/720 and LIK \$1,2020/4567

2.2. Label elements

Hazard pictogram(s)







Signal word	Danger
-------------	--------

Hazard statement(s)

H400	Very toxic to aquatic life.				
H318	Causes serious eye damage.				
H360FD	May damage fertility. May damage the unborn child.				

Part Number: 5060686 Page 2 of 13 Issue Date: 11/07/2022 Version No: 1.1 Print Date: 04/05/2023

CARESTREAM DENTAL X-ray Developer

H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.

Supplementary Phrases

Not Applicable

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.				
P280	Wear protective gloves, protective clothing, eye protection and face protection.				
P261	void breathing mist/vapours/spray.				
P273	Avoid release to the environment.				
P272	P272 Contaminated work clothing should not be allowed out of the workplace.				

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P308+P313	IF exposed or concerned: Get medical advice/ attention.			
P310	Immediately call a POISON CENTER/doctor/physician/first aider.			
P302+P352	IF ON SKIN: Wash with plenty of water.			
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			
P391	1 Collect spillage.			

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

Eye contact may produce serious damage*.

Hydroquinone	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)		
Sodium borate Listed in the European Chemicals Agency (ECHA) Candidate List of Substances of Very High Concern for Authorisation			
Sodium borate	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)		

SECTION 3 Composition / information on ingredients

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	SCL / M-Factor	Nanoform Particle Characteristics
1.7732-18-5* 2.231-791-2 3.Not Available 4.Not Available	70-80	<u>Water</u>	Not Applicable	Not Available	Not Available
1.123-31-9* 2.204-617-8 3.604-005-00-4 4.Not Available	1-5	Hydroquinone	Hazardous to the Aquatic Environment Acute Hazard Category 1, Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Oral) Category 4, Sensitisation (Skin) Category 1, Germ Cell Mutagenicity Category 2, Carcinogenicity Category 2; H400, H318, H302, H317, H341, H351 [1]	0	Not Available
1.1330-43-4* 2.215-540-4 3.005-011-00-4 4.Not Available	1-<3	Sodium borate	Reproductive Toxicity Category 1B; H360FD [1]	0	Not Available
1.10117-38-1* 2.233-321-1 3.Not Available 4.Not Available	10-15	Potassium sulfite	Not Applicable	0	Not Available
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L: *EU IOELVs available; [e] Substance identified as having endocrine disrupting properties			lassification drawn	

SECTION 4 First aid measures

Part Number: 5060686 Page 3 of 13 Issue Date: 11/07/2022 Version No: 1.1 Print Date: 04/05/2023

CARESTREAM DENTAL X-ray Developer

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- ► Foam.
- Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

5.2. Special nazards ansing from the substrate or mixture		
Fire Incompatibility	None known.	
5.3. Advice for firefighters		
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 	
Fire/Explosion Hazard	Non combustible. Not considered a significant fire risk, however containers may burn.	

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Environmental hazard - contain spillage. Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Part Number: 5060686 Page 4 of 13 Issue Date: 11/07/2022 Version No: 1.1 Print Date: 04/05/2023

CARESTREAM DENTAL X-ray Developer

SECTION 7 Handling and storage

7.1. Precautions for safe handl	ing
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. DO NOT allow clothing wet with material to stay in contact with skin
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known
Hazard categories in accordance with Regulation (EC) No 1272/2008	E1: Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	E1 Lower- / Upper-tier requirements: 100 / 200

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Water	Dermal 0.4 mg/kg bw/day (Systemic, Chronic) Inhalation 0.544 mg/m³ (Systemic, Chronic) Dermal 5 mg/kg bw/day (Systemic, Acute) Inhalation 8.8 mg/m³ (Systemic, Acute) Dermal 0.2 mg/kg bw/day (Systemic, Chronic) * Inhalation 0.083 mg/m³ (Systemic, Chronic) * Oral 0.056 mg/kg bw/day (Systemic, Chronic) * Dermal 2.5 mg/kg bw/day (Systemic, Acute) * Inhalation 2.2 mg/m³ (Systemic, Acute) * Oral 2.5 mg/kg bw/day (Systemic, Acute) *	Not Available
Hydroquinone	Dermal 3.33 mg/kg bw/day (Systemic, Chronic) Inhalation 2.1 mg/m³ (Systemic, Chronic) Dermal 1.66 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.05 mg/m³ (Systemic, Chronic) * Oral 0.6 mg/kg bw/day (Systemic, Chronic) *	0.57 μg/L (Water (Fresh)) 0.057 μg/L (Water - Intermittent release) 1.34 μg/L (Water (Marine)) 4.9 μg/kg sediment dw (Sediment (Fresh Water)) 0.49 μg/kg sediment dw (Sediment (Marine)) 0.64 μg/kg soil dw (Soil) 0.71 mg/L (STP)
Sodium borate	Dermal 316.4 mg/kg bw/day (Systemic, Chronic) Inhalation 6.7 mg/m³ (Systemic, Chronic) Dermal 159.5 mg/kg bw/day (Systemic, Chronic) * Inhalation 3.4 mg/m³ (Systemic, Chronic) * Oral 0.79 mg/kg bw/day (Systemic, Chronic) * Oral 0.79 mg/kg bw/day (Systemic, Acute) *	2.9 mg/L (Water (Fresh)) 2.9 mg/L (Water - Intermittent release) 13.7 mg/L (Water (Marine)) 5.7 mg/kg soil dw (Soil) 10 mg/L (STP)
Potassium sulfite	Inhalation 374 mg/m³ (Systemic, Chronic) Inhalation 111 mg/m³ (Systemic, Chronic) * Oral 14 mg/kg bw/day (Systemic, Chronic) *	1.67 mg/L (Water (Fresh)) 0.17 mg/L (Water - Intermittent release) 125.5 mg/L (STP)

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Part Number: 5060686 Page 5 of 13 Issue Date: 11/07/2022 Version No: 1.1 Print Date: 04/05/2023

CARESTREAM DENTAL X-ray Developer

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
UK Workplace Exposure Limits (WELs).	Hydroquinone	Hydroquinone	0.5 mg/m3	Not Available	Not Available	Not Available
UK Workplace Exposure Limits (WELs).	Sodium borate	Disodium tetraborate, anhydrous	1 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Hydroquinone	3 mg/m3	20 mg/m3	120 mg/m3
Sodium borate	6 mg/m3	88 mg/m3	530 mg/m3

Ingredient	Original IDLH	Revised IDLH
Water	Not Available	Not Available
Hydroquinone	50 mg/m3	Not Available
Sodium borate	Not Available	Not Available
Potassium sulfite	Not Available	Not Available

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: Air Speed: 0.25-0.5 m/s solvent, vapours, degreasing etc., evaporating from tank (in still air) (50-100 f/min) aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray 0.5-1 m/s (100-200 drift, plating acid fumes, pickling (released at low velocity into zone of active generation) f/min.) direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active 1-2.5 m/s (200-500 generation into zone of rapid air motion) f/min) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of 2.5-10 m/s (500-2000 f/min.) very high rapid air motion).

8.2.1. Appropriate engineering controls

Within each range the appropriate value depends on: Lower end of the range Upper end of the range 1: Room air currents minimal or favourable to capture 1: Disturbing room air currents 2: Contaminants of low toxicity or of nuisance value only 2: Contaminants of high toxicity 3: Intermittent, low production. 3: High production, heavy use

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used

4: Small hood - local control only

8.2.2. Individual protection measures, such as personal protective equipment





4: Large hood or large air mass in motion







- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Eve and face protection

See Hand protection below

Skin protection

NOTE:

Hands/feet protection

▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Fig. The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective

Issue Date: 11/07/2022 Part Number: 5060686 Page 6 of 13 Version No: 1.1

CARESTREAM DENTAL X-ray Developer

Print Date: 04/05/2023

equipment, to avoid all possible skin contact.

Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374. AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection See Other protection below Overalls. P.V.C apron. Other protection Barrier cream. ► Skin cleansing cream.

► Eye wash unit.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Colourless		
Physical state	Liquid	Relative density (Water = 1)	1.24
Odour	No Odour	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	10.6	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	> 100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	2.40	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	0.6	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

Part Number: 5060686 Version No: 1.1

CARESTREAM DENTAL X-ray Developer

Issue Date: **11/07/2022**Print Date: **04/05/2023**

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on toxicological effects

CARESTREAM DENTAL X-ray

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	If applied to the eyes, this material causes severe eye damage.
Chronic	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.

Developer	Not Available	Not Available
Water	TOXICITY	IRRITATION
Water	Oral (Rat) LD50: >90000 mg/kg ^[2]	Not Available
	TOXICITY	IRRITATION
Hydroquinone	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
	Oral (Rat) LD50: 320 mg/kg ^[2]	
	TOXICITY	IRRITATION
Sodium borate	TOXICITY Dermal (rabbit) LD50: >2000 mg/kg ^[2]	IRRITATION Eye: adverse effect observed (irritating) ^[1]
Sodium borate		
Sodium borate	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]
Sodium borate Potassium sulfite	Dermal (rabbit) LD50: >2000 mg/kg ^[2] Oral (Rat) LD50: 2403-4207 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1]
	Dermal (rabbit) LD50: >2000 mg/kg ^[2] Oral (Rat) LD50: 2403-4207 mg/kg ^[2] TOXICITY	Eye: adverse effect observed (irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1] IRRITATION

TOXICITY

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

IRRITATION

CARESTREAM DENTAL X-ray Developer & Hydroquinone

Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely

distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Acute Toxicity	X	Carcinogenicity	✓
Skin Irritation/Corrosion	×	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×

Part Number: 5060686 Page 8 of 13
Version No: 1.1

CARESTREAM DENTAL X-ray Developer

Issue Date: **11/07/2022** Print Date: **04/05/2023**

Respiratory or Skin sensitisation

Mutagenicity

Aspiration Hazard

Legend: X – Data either not available or does not fill the criteria for classification

— Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

CARECTREAM RENTAL V	Endpoint	Test Duration (hr)	Species	Value	Source
CARESTREAM DENTAL X-ray Developer	Not Available	Not Available	Not Available	Not Available	Not Available
Water	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	ErC50	72h	Algae or other aquatic plants	0.335mg/l	1
	LC50	96h	Fish	0.044mg/l	2
Hydroquinone	EC50	72h	Algae or other aquatic plants	<0.033mg/l	2
	EC50	48h	Crustacea	0.061mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	0.002mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
On Phone Language	LC50	96h	Fish	1900mg/l	4
Sodium borate	EC50(ECx)	96h	Algae or other aquatic plants	2.6-21.8mg/l	4
	EC50	96h	Algae or other aquatic plants	2.6-21.8mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	LC50	96h	Fish	147-215mg/l	2
	EC50	72h	Algae or other aquatic plants	43.8mg/l	2
Potassium sulfite	EC50	48h	Crustacea	89mg/l	2
	NOEC(ECx)	504h	Crustacea	>10mg/l	2
	EC50	96h	Algae or other aquatic plants	63-126mg/l	2
Legend:			HA Registered Substances - Ecotoxicological Informati Aquatic Hazard Assessment Data 6. NITE (Japan) - Bi		

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Water	LOW	LOW
Hydroquinone	LOW	LOW

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
Hydroquinone	LOW (BCF = 65)

12.4. Mobility in soil

Ingredient	Mobility
Hydroquinone	LOW (KOC = 434)

12.5. Results of PBT and vPvB assessment

Part Number: **5060686** Page **9** of **13**

Version No: 1.1

CARESTREAM DENTAL X-ray Developer

Issue Date: **11/07/2022**Print Date: **04/05/2023**

	P	В	Т	
Relevant available data	Not Available	Not Available	Not Available	
PBT	X	×	×	
vPvB	×	×	×	
PBT Criteria fulfilled?				
vPvB			No	

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal

Recover silver before disposal. European Waste Catalogue EWC: 09 01 99 Wastes not otherwise specified.

Dispose of in accordance with local regulations

- Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ► Reuse
- ► Recycling
- ► Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- ► Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Waste treatment options

Not Available

Sewage disposal options

Not Available

SECTION 14 Transport information

The dangerous goods information given below is based solely on the product formulation, and does not consider the product packaging configuration.

Depending on inner packaging quantities and packaging instructions, this product may meet specific regulatory exemptions or exclusions for the various modes of transport.

Please consult the product packaging for further details or go to the "Dangerous Goods Worksheets for Chemical Products" folder, located at: ship.carestream.com.

Labels Required



Marine Pollutant



HAZCHEM

•3Z

Land transport (ADR-RID)

14.1. UN number or ID number	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains Hydroquinone)

Part Number: 5060686 Page 10 of 13 Issue Date: 11/07/2022 Version No: 1.1 Print Date: 04/05/2023

274 335 375 601

5 L

3 (-)

CARESTREAM DENTAL X-ray Developer

Class 14.3. Transport hazard class(es) Subsidiary risk Not Applicable 14.4. Packing group 14.5. Environmental hazard Environmentally hazardous Hazard identification (Kemler) 90 Classification code 9 Hazard Label 14.6. Special precautions for

Air transport (ICAO-IATA / DGR)

Special provisions

Tunnel Restriction Code

Limited quantity

user

4.1. UN number	3082		
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains Hydroquinone)		
	ICAO/IATA Class	9	
4.3. Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable	
ciass(es)	ERG Code	9L	
4.4. Packing group	III		
14.5. Environmental hazard	Environmentally hazardous		
	Special provisions		A97 A158 A197 A215
	Cargo Only Packing Instructions		964
	Cargo Only Maximum Qty / Pack		450 L
4.6. Special precautions for user	Passenger and Cargo Packing Instructions		964
4001	Passenger and Cargo Maximum Qty / Pack		450 L
	Passenger and Cargo Limited Quantity Packing Instructions		Y964
	Passenger and Cargo Limited Maximum Qty / Pack		30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3082		
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains Hydroquinone)		
14.3. Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable		
14.4. Packing group	III		
14.5. Environmental hazard	Marine Pollutant		
14.6. Special precautions for user	EMS Number F-A, S-F Special provisions 274 335 969 Limited Quantities 5 L		

Inland waterways transport (ADN)

14.1. UN number	3082		
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains Hydroquinone)		
14.3. Transport hazard class(es)	9 Not Applicable		
14.4. Packing group	III		
14.5. Environmental hazard	Environmentally hazardous		
	Classification code	M6	
14.6. Special precautions for	Special provisions	274; 335; 375; 601	
user	Limited quantity	5 L	
	Equipment required	PP	
	Fire cones number	0	

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Part Number: **5060686** Page **11** of **13**

CARESTREAM DENTAL X-ray Developer

Issue Date: **11/07/2022**Print Date: **04/05/2023**

Not Applicable

Version No: 1.1

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Water	Not Available
Hydroquinone	Not Available
Sodium borate	Not Available
Potassium sulfite	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Water	Not Available
Hydroquinone	Not Available
Sodium borate	Not Available
Potassium sulfite	Not Available

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Water is found on the following regulatory lists

Not Applicable

Hydroquinone is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List Great Britain GB mandatory classification and labelling list (GB MCL) International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic UK Workplace Exposure Limits (WELs).

Sodium borate is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
Great Britain GB Biocidal Active Substances
Great Britain GB mandatory classification and labelling (GB MCL) technical reports

Great Britain GB mandatory classification and labelling list (GB MCL)
UK REACH Candidate List of substances of very high concern (SVHC) for
Authorisation
UK Workplace Exposure Limits (WELs).

Potassium sulfite is found on the following regulatory lists

Great Britain GB Biocidal Active Substances

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category

F1

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
Water	7732-18-5*	Not Available	Not Available
Harmonisation (C&I		Pictograms Signal Word	

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Not Classified	Not Available	Not Available
2	Flam. Liq. 3; Acute Tox. 3; Skin Corr. 1A; Acute Tox. 2; Eye Irrit. 2	GHS05; Dgr; GHS02; GHS06	H318; H226; H314; H301; H411; H335

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
Hydroquinone	123-31-9*	604-005-00-4	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Acute Tox. 4; Skin Sens. 1; Eye Dam. 1; Muta. 2; Carc. 2; Aquatic Acute 1	GHS08; GHS05; GHS09; Dgr	H302; H317; H318; H341; H351; H400
2	Skin Sens. 1B; Eye Dam. 1; Carc. 2; Aquatic Acute 1; Aquatic Chronic 1; Acute Tox. 4; Skin Irrit. 2; Acute Tox. 3; Resp. Sens. 1; Muta. 1B; Repr. 1B; STOT SE 1; STOT RE 1	GHS08; GHS09; GHS05; Dgr	H317; H318; H351; H410; H400; H312; H315; H301; H334; H340; H360; H370; H372

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
Sodium borate	1330-43-4*	005-011-00-4	Not Available

Part Number: 5060686 Page 12 of 13 Issue Date: 11/07/2022 Version No: 1.1 Print Date: 04/05/2023

CARESTREAM DENTAL X-ray Developer

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Repr. 1B	GHS08; Dgr	H360
2	Acute Tox. 4; Eye Dam. 1; Acute Tox. 4; Repr. 1B	GHS08; Dgr	H360FD; H302; H318; H332

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
Potassium sulfite	10117-38-1*	Not Available	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Not Classified	Not Available	Not Available
2	Eye Irrit. 2; Skin Irrit. 2; STOT SE 3; Aquatic Chronic 3	GHS07; Wng	H319; H315; H335; H412

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory Status

National inventory Status	
National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (Water; Hydroquinone; Sodium borate; Potassium sulfite)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	11/07/2022
Initial Date	29/03/2022

Full text Risk and Hazard codes

Full text RISK and Hazard code	5
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or

Part Number: 5060686 Page **13** of **13** Issue Date: 11/07/2022 Version No: 1.1

CARESTREAM DENTAL X-ray Developer

Print Date: 04/05/2023

other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.