MONACO COLLECTION

AUTOMOTIVE

Natural Leather

TECHNICAL DATASHEET	TEST METHOD PRÜFVERFAHREN METHOD TEST MÉTODO DE PRUEBA	MEASUREMENT UNIT MAßEINHEIT UNIT OF MEASUREMENT UNIDAD DE MEDIDA	GUARANTEED GARANTIERT INSURED GARANTIZADA
FLAMMABILITY **BRENNVERHALTEN** **COMBUSBITILITÉ** **INFLAMABILIDAD**	FMVSS 302	IMO RES A652(16) FIRE RETARDANT	< 100 mm/min.
COLOUR FASTNESS TO RUBBING | DRY 1500 CYCLES **ABRIEBFESTIGKEIT** | TROCKEN 1500 ZYKLEN **RÉSISTANCE AUX FROTTEMENTS** | A SEC 1500 CYCLES **SOLIDEZ DEL COLOR AL FROTE** | A SECO 1500 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
COLOUR FASTNESS TO RUBBING | WET 300 CYCLES **ABRIEBFESTIGKEIT** | NASS 300 ZYKLEN **RÉSISTANCE AUX FROTTEMENTS** | HUMIDE 300 CYCLES **SOLIDEZ DEL COLOR AL FROTE** | MOJADO 300 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
COLOUR FASTNESS TO RUBBING | SWEAT 100 CYCLES **ABRIEBFESTIGKEIT** | SCHWEIß 100 ZYKLEN **RÉSISTANCE AUX FROTTEMENTS** | SUEUR 100 CYCLES **SOLIDEZ DEL COLOR AL FROTE** | SUDOR 100 CICLOS	UNI EN ISO 11640:1998 ISO 11641 pH8	GREY SCALE	≥ 4
FLEXING ENDURANCE | DRY 50.000 CYCLES **BIEGEFESTIGKEIT** | TROCKEN 50.000 ZYKLEN **RÉSISTANCE À LA FLEXION** | A SEC 50.000 CYCLES **RESISTENCIA A LA FLEXIÓN** | A SECO 50.000 CICLOS	UNI EN ISO 5402		NO DAMAGE
ADHESION OF FINISH-DRY **HAFTFESTIGKEIT DER ZURICHTUNG TROCKEN** **ADHÉRENCE DE LA FINITION À SEC** **ADHERENCIA DE ACABADO SECO**	UNI EN ISO 11644	N/cm	≥ 4
TEAR STRENGTH | SINGLE EDGE TEAR **REIßFESTIGKEIT HOSE** | EINKANTENRISS **RÉSISTANCE AU DÉCHIREMENT** | BORD UNIQUE **RESISTENCIA AL DESGARRO** | DESGARRO SIMPLE	UNI EN ISO 3377-1	N	≥ 20
TENSILE STRENGTH AND ELONGATION **HÖCHSTZUGKRAFT UND DEHNUNG BEI HÖCHSTZUGKRAFT** **RESISTANCE À LA TENSION ET L'ALLONGEMENT** **RESISTENCIA A LA TRACCIÓN Y ELONGACIÓN**	UNI EN ISO 3376:2006	N	≥ 130
ARTIFICIAL AGEING **HEIßLICHTALTERUNG** **VIEILLISSEMENT ARTIFICIEL** **ENVEJECIMIENTO ARTIFICIAL**	4h at 70°C	GREY SCALE	≥ 4
COLOUR FASTNESS TO ARTIFICIAL LIGHT | EXPOSITION ENERGY 16.000 kj/sqm **UV-BESTÄNDIGKEIT** | EXPOSITIONS ENERGIE 16.000 kj/qm **RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE** | ÉNERGIE D'EXPOSITION 16.000 kj/m² **SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL** | EXPOSICIÓN A ENERGÍA 16.000 kj/m²	UNI EN ISO 105 B02 (MET.5)	GREY SCALE	≥ 4

ORIGIN RAW MATERIAL

EUROPEAN BOVINE NAPPA LEATHER, SLIGHTLY CORRECTED NATURAL GRAIN SOFT FEEL AND SILKY TOUCH WITH A SEMI-MATTE FINISH; CAR SUITABLE

1.1 - 1.3 mm THICKNESS | 4.5 - 5.0 sqm AVERAGE

REACH COMPLIANT - RESPECTS THE ENVIRONMENT USING APPLICATION OF NEW TECHNOLOGIES IN THE PRODUCTION PROCESS

CLEAN AND CARE RECOMMENDATIONS

TO REMOVE DUST USE A VACUUM CLEANER.

AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.

ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.

WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

DELIVERY AND SHIPPING

4/5 DAYS DELIVERY TIME

EXPRESS SERVICE - READY TO SHIP IN 48h

WORLDWIDE SHIPPING AVAILABLE