

### **FLOODPLAIN DEVELOPMENT PERMIT APPLICATION**

- Please submit the floodplain development permit application with appropriate building permit to www.carnationwa.gov
- Plan sets shall accompany this original permit application.
- An Elevation Certificate is required with permit application.

The undersigned hereby makes application for a permit to develop in a designated special flood hazard area (SFHA). The work to be performed is described below and in attachments hereto. The undersigned agrees that all such work shall be done in accordance with the requirements of the Carnation Municipal Code, Chapter 15.64 with all other applicable local, state and federal regulations, and with all necessary required federal and/or state permits and/or certifications attached.

Date: Parcel #	Owners Name: Owners Address: City/State/Zip: Telephone:
A. DESCRIPTION OF WORK:  1. PROPOSED DEVELOPMENT DESCRIPTIONS:  New Construction	2. TYPE OF CONSTRUCTION: (CHECK ALL THAT APPLY)  New or Existing Residential Square Footage:  Addition Square Footage:  Renovation Interior Exterior  Repair  Accessory Structure (i.e. garage, shed etc.) Sq. Footage:  New Non-Residential Square Footage:  Temporary  Includes Attached Garage Square Footage:  Utility Installation
requirements shall apply) Building Official will verify proposed	ed by the B/O and/or IBC?
C. NON-RESIDENTIAL CONSTRUCTION: 1. Proposed Flood Protection Method: □Floodproofing	(Use of construction materials to floodproof the building)
D. OTHER:  1. No. of permanent openings (flood vents) within 1ft. above a 2. Total area of new foundation Tota 3. Net area of all permanent openings (flood vents): 4. Elevation of the next higher floor will be at an elevation of Total area of all permanent openings (flood vents): 4.	al area of existing building footprint ☐ N/A
No Floodplain Development Permit will be issued until a This permit is sought (in perpetuity; or if Plans, reports, and specifications of the proposed work application/permit and are attached. Construction is on/or before	temporary, number or months or years)
Signature of Applicant:	Date:

# CARNATION CARNATION

### Floodplain Development Permit Application Information Sheet

### **Process:**

By the time you receive this document it is assumed you are interested in developing within the floodplain. To facilitate this process, you or your representative should contact the Community Economic Development Department at (425) 333-4192 and secure flood zone information and a Base Flood Elevation that will pertain to your site development. Once you have this information, you can then fill out the application and prepare the drawings for submittal to secure a floodplain development permit. Before preparing the needed drawings, please carefully review the items listed below for guidance in meeting the National Floodplain Insurance Program (NFIP) requirements. Once the drawings and application have been submitted to the Community & Economic Development through the Permitting Portal at www.carnationwa.gov, and the application fee paid, the city will review the documents for conformance and either request additional information or take action on the permit. During construction, certifications may be required of elevations of finished floors, equipment, or other elements of the project as may be conditioned in the permit. The required certification forms, if applicable, will be provided to you along with the permit. These will have to be fully and correctly completed by a Washington State registered land surveyor and turned into the city before proceeding with work or securing occupancy.

### **Submittal:**

The application must be accompanied by plans incorporating the following items. Some projects do not include a structure, substantial improvement, and/or do not require some of the following information. Provide the items as applicable.

- 1. Provide existing and proposed topographic survey of the site, and the floodplain and/or floodway delineation. Identify the highest adjacent natural grade next to the building prior to construction (in the AO zones) or the Base Flood Elevation (BFE) of the site (in the AE zones) at a scale 1" = 20' minimum. You can obtain the BFE or flood zone in which your site is located by viewing the FEMA maps on the Floodplain Information page at www.carnationwa.gov.
- 2. Identify which building diagram number from the FEMA Elevation Certificate (EC) you propose to construct. (See attached diagrams)
- 3. Provide the proposed "top of next higher floor" elevation of the structure as described on the Building Diagram and provide survey datum used as well (NGVD 29 or NAVD 88).
- 4. Provide the appropriate size and location of required foundation and/or flood vents. Provide a cross section of the foundation, the location of flood vents, and the internal/external proposed finished grades. Identify existing and proposed final elevations for both the internal and external ground next to the foundation walls. Identify the elevation of the "top of the bottom floor", basement and garage elevations. (See Building Diagrams)
- 5. Identify the type of flood resistant materials to be used to the required "flood protected" elevation of the structure, including garage, if applicable. The "flood protected" elevation is the BFE plus two feet. For non-residential structures, provide the proposed floodproofing elevation.
- 6. If fill is proposed and compensatory storage is required, calculations must be submitted to verify sufficient compensatory storage is being provided.



- 7. If a subdivision or other development contains either 50 lots or 5 acres, then the base flood elevation data must be provided by the developer, prior to the issuance of a permit. Additional flood studies may be required.
- 8. The building plans shall indicate the building's utilities, ventilation, ductwork, machinery and equipment, such as furnaces, water heaters, heat pumps, air conditioners, plumbing, and elevators and their associated equipment, will be properly elevated to or above the "flood protected" elevation or that the components located below the "flood protected" elevation will be protected with FEMA approved flood resistant material such that floodwater is prevented from entering or accumulating within the system components (impermeable and watertight) to the flood protected elevation at a minimum.
- 9. Fully enclosed areas below the lowest floor that are usable solely for parking of vehicles, building access or storage in an area other than a basement and which are subject to flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a registered professional engineer or architect, or meet or exceed the following minimum criteria:
  - a. There must be a minimum of two openings on different sides of each enclosed area. If a building has more than one enclosed area, each area must have openings on exterior walls to allow floodwater to directly enter.
  - b. A minimum of two openings having a total net area of not less than one square inch for every square foot of <u>enclosed area</u> (including attached garage if constructed) subject to flooding shall be provided. The bottom of all openings shall be no higher than one foot above grade. Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic unrestricted entry and exit of floodwaters.
- 10. Any new or substantially improved residential building constructed in an A zone must have its lowest floor at or above the BFE. Many of the buildings have structurally attached garages with floor slabs below the BFE. Because such a below-BFE attached garage is an enclosed area below the BFE, openings are required either in the exterior walls of the garage or in the garage doors themselves to meet the NFIP openings criteria. Openings are required because they prevent flood damage to the garage and subsequently to the structurally attached residence. Garage doors without openings specifically designed to allow for the free flow of floodwaters do not meet the openings requirement. The human intervention necessary to open garage doors when flooding threatens is not an acceptable means of meeting the openings requirements. Gaps that may be present between the door segments and between the garage door and the garage doorjamb do not guarantee the automatic entry and exit of floodwaters.
- 11. If the proposed development is located in an identified floodway then a "no-rise" certification completed by a registered professional engineer must be submitted prior to the issuance of a permit or the start of construction
- 12. The City *recommends* elevating all existing structures 2' above the BFE or refurbishing them with flood resistant materials.

13. A floodplain habitat assessment and mitigation plan shall be required unless the CED director makes and documents a determination of no adverse effect on any species listed under the Federal Endangered Species Act. Unless a project requires a permit that may be applied for with a JARPA Permit or Amy Corp. of Engineers 404 Permit, strict compliance with the City's stormwater, sensitive areas and shoreline management regulations ensures that there will be no adverse effect on any species listed under the Endangered Species Act.

•	•	3	•	
Please check the box Requires a JARF	if your project trigge	ers in any of the fo	itat Assessment will be Illowing permits.	required.
Please check the box if your pro	oject will seek variation	from strict complia	nce with any of the follow	ving:
Carnation Municipal Cod	e 15.64 Drainage, Eros	sion Control, Stormv	vater Management	
Chapter 14.04.190, Critic	al Areas			
Chapter 14.06, Shoreline	Master Plan			

#### FLOODPLAIN DEVELOPMENT PERMIT

<u> </u>	NUTTIONS OF APPROVAL:
1.	Required elevation of the "top of the

1. Required elevation of the "top of the next higher floor" shall	be: (AE) feet (NGVD '29)
2. Required elevation of the "top of the next higher floor" shall	be: <b>(AO)</b> feet (NGVD '29)
Highest adjacent natural grade next to the structure prior to gra	ading is:
<ol><li>Required elevation of flood resistant materials, utilities etc., residential structures (the flood protected elevation) shall be:</li></ol>	
4. A "Construction drawings" elevation verification (top of the no completed and submitted to the City for review and approval al documents. This certificate shall be completed by a Washingto	ong with all required construction
5. A "Building Under Construction" elevation verification (top of completed and submitted to the City for review and approval pre- certificate shall be completed by a Washington State Licensed	rior to any vertical construction. This
6. A "Finished Construction" EC □shall □ N/A be submitted for occupancy or final inspection of the building(s), whichever come completed by a Washington State Licensed Professional Survey FINAL INSPECTION SHALL BE GRANTED PRIOR TO SUBMITTED CONSTRUCTION" CERTIFICATION.	es first. This certificate shall be eyor. NO HUMAN OCCUPANCY OR
<ol> <li>A Floodproofing Certificate, certified by a professional enging submitted at the time of completion, prior to a final inspection one comes first.</li> </ol>	
8. A Letter of Map Revision issued by the FEMA □shall □ N/A completion of the project, as a condition of proposed alteration	
9. Other attached applicable provisions □shall □ N/A be requir	red.
CITY APPROVAL:	
Because cost of improvements is less than 50% of assessed does not require the applicant to comply with the floodplain re regulations.	
☐ Minor interior remodel only. Value of construction:	Value of Structure:
Plans Examiner/Building Official:	Date:
City Engineer and/or Designee:	Date:
The Permittee agrees to save indemnify and hold harmless the	e City of Carnation, its City Council

The Permittee agrees to save, indemnify and hold harmless the City of Carnation, its City Council, boards, officers, employees and agents from all liabilities imposed by law by reason of injury to or death of any person(s) or damage to property, including without limitation, liability for trespass, nuisance or inverse condemnation, which may arise out of the work covered by this permit, and does agree to defend the City, its officers, employees and agents against any claim or action asserting such liability. Accepting this permit or starting any work hereunder shall constitute acceptance and agreement to all of the conditions and requirements of this permit and the ordinance and specifications authorizing issuance of such permit.

**EXPIRATION DATE:** This permit expires with the building permits or in the absence of a building permit, 12 months from date of issuance.

I have read, understand, and agree to abide by the instructions and conditions as stated in this permit. I will ensure that the proper City Official completes all certifications required below. These construction/improvements may require you to purchase flood insurance. Please check with your insurance agent! Signature of Permittee: \_\_\_\_\_ Date: \_\_\_\_\_ Printed Name of Permittee: City/State/Zip: APPLICATION DENIED: \_\_\_\_\_\_ DATE: \_\_\_\_\_ REASONS FOR DENIAL: **ELEVATION CERTIFICATIONS** The "Under Construction" elevation verification has been reviewed and approved: ☐ Structure elevated to or above the flood protected elevation (BFE + 2') ☐ Structure built with waterproofed materials to the flood protected elevation or more. ☐ Structure built with water resistant materials to the flood protected elevation or more. ♦ Plans Examiner/Building Official: \_\_\_\_\_\_ Date: \_\_\_\_\_ ♦ City Engineer and/or Designee: Date: The <u>"Finished Construction"</u> elevation certificate has been received on It has been reviewed and  $\square$  returned for more information on \_\_\_\_\_ (date) approved on \_\_\_\_\_ (date). \_\_\_\_\_ Date: \_\_\_ City Engineer and/or Designee: **FIELD CERTIFICATION** All floodplain regulations and conditions of approval have been satisfied and inspected by the Building Department including utilities, ductwork, machinery, and equipment, such as furnaces, water heaters, heat pumps, air conditioners, and elevators and their associated equipment, is/are properly elevated to or above the "flood protected" elevation or that the components located below the "flood protected" elevation will be protected such that floodwater is prevented from entering or accumulating within the system components (watertight) to the flood protected elevation at a minimum.

Inspector: \_\_\_\_\_ Date: \_\_\_\_\_

