



November 6, 2020
File: 2548.001bltr.doc

Hines Interests Limited Partnership
101 California Street, Suite 1000
San Francisco, California 94111

Attn: Mr. Charlie Tilleman

Re: Response to Review Comments
Petaluma Junction
Petaluma, California

This letter summarizes our response to geotechnical-related review comments for the proposed Petaluma Junction development. The review comments were prepared by the City of Petaluma and are summarized in their letter dated October 6, 2020. The City's review included one comment pertaining to our Preliminary Geotechnical Report dated December 18, 2017, as summarized below:

Based on review of other development applications in the immediate vicinity, Bay Mud soils may be located on the project site since they have been identified on nearby sites. Bay Mud soils are susceptible to subsidence under heavy loads. The geotechnical report prepared in 2017 does not indicate the presence of Bay Mud. Staff is looking for clarification on the presence or absence of this soil type and how that may impact the geotechnical recommendations contained in the report.

Regional geologic mapping indicates the site is underlain by Holocene-age terrace deposits and is north of the mapped area underlain by Bay Mud (also referred to in the mapping as "Estuarine Deposits"). Our Preliminary Geotechnical Report includes reference subsurface data consisting of five cone penetration tests (CPTs) which were completed at the site by Engeo. One of the CPTs (CPT 3) completed near the northwest side of the site encountered approximately 10 feet of relatively soft and potentially compressible soils. While the CPT method does not allow for soil sampling, the data suggests the material is likely Bay Mud. The soils encountered in the other four CPTs were characterized as overconsolidated silty clay and clayey silt which suggests the materials are alluvial terrace deposits which are stiffer and less compressible and are not Bay Mud.

Based on the available data, it does appear that the northwest portion of the site may be underlain by Bay Mud. It should be noted that our Preliminary Geotechnical Report is intended to address geologic hazards and other anticipated geotechnical challenges to aid the project team during planning and in evaluating feasibility. Additional borings and laboratory testing will be completed as part of a future geotechnical investigation which will provide design-level geotechnical recommendations and criteria. This will include obtaining samples of subsurface soils and evaluating the potential for soft soil and settlement under new buildings, site grading and other improvements. A detailed evaluation of settlement was not performed as part of the

November 6, 2020

preliminary report since borings and laboratory testing are not yet complete, and building layouts, structural loads, site grading/new fill loads and other project details are not yet defined. As noted in our preliminary report, settlement analyses and various alternatives for mitigating potential building settlements will be addressed as part of a future design-level geotechnical investigation.

We trust that this letter contains the information you require at this time. If we can be of further assistance or should there be any questions or concerns regarding this report, please call.

Very truly yours,
MILLER PACIFIC ENGINEERING GROUP

REVIEWED BY:



Rusty Arend
Geotechnical Engineer No. 3031
(Expires 6/30/21)



Scott Stephens
Geotechnical Engineer No. 2398
(Expires 6/30/21)



December 18, 2017
File: 2548.001altr.doc

Hines Interests Limited Partnership
101 California Street, Suite 1000
San Francisco, California 94111

Attn: Mr. Brendan Cronshaw

Re: Update to Preliminary Geotechnical Report
Petaluma Junction
Petaluma, California

Introduction and Project Description

This letter presents our supplemental, preliminary geotechnical recommendations for the Petaluma Junction development in Petaluma, California. The proposed mixed-use development encompasses an approximately 4.5-acre, vacant parcel (APN 007-131-003) located southwest of the Sonoma-Marín Area Rail Transit's (SMART) Petaluma Downtown Station. The project area is shown on the Site Location Map, Figure 1.

Based on our review of preliminary plans¹ and discussions with the project team, we understand the project is expected to include developing the site with two four-story buildings with about 300 units for multi-family residential and retail use. A separate six-story parking structure is also planned as part of the development. Preliminary plans indicate the buildings will be constructed at or near existing grades and no significant below-grade structures are anticipated. While detailed structural information is not available at this time, the new buildings are expected to induce moderate to heavy foundation loads. Ancillary improvements may include exterior hardscape and asphalt paving, new underground utilities, site drainage, landscaping, and other improvements "typical" of such developments.

Our work was performed in accordance with our Agreement for Professional Services dated November 20, 2017. Engeo previously prepared a Preliminary Geotechnical Report² for the site dated October 5, 2016 which provided preliminary conclusions and recommendations for use in project planning. This previous report is attached for reference in Appendix A. Several project features have changed since issuance of Engeo's report, including the use of taller, heavier structures. The purpose of our services is to review the Engeo report along with other available, published geologic and geotechnical information, and to provide any supplemental preliminary recommendations that should be incorporated into the project planning and design.

¹ Architects Orange, "Site & 1st Floor Plan, Petaluma Station, Petaluma, California", November 8, 2017.

² Engeo, "Preliminary Geotechnical Report, 315 D Street, Petaluma, California", October 5, 2016.

Site Reconnaissance and Surface Conditions

We conducted a site reconnaissance on November 27, 2017 to observe surface conditions within the project area. As shown on the Site Plan, Figure 2, the site is bordered to the southeast by D Street, to the northeast by the SMART Petaluma Downtown Station, to the northwest by East Washington Street and to the southwest by Copeland Street. The ground surface is relatively level throughout the site with surface elevations ranging from about 10 to 14 feet (based on Google Earth imagery). The property is enclosed by a fence and site access is provided through gates located off of East Washington Street and D Street.

Two abandoned railroad spur lines parallel the northeastern property boundary adjacent to the SMART parking lot. It appears the property is currently being used as storage for SMART as there are railroad ties, crossing signs and other materials staged throughout the project area. Several stockpiles of soil, asphalt, old storm drain pipes and other construction debris are present at various locations. The ground surface is covered with grass and sparse shrubbery and up to several feet of ballast has been placed in some areas.

Previous Subsurface Exploration

Several investigations have been conducted within the vicinity of the site by Miller Pacific and other Consultants as part of the proposed project or other nearby projects. As part of our update to the Preliminary Geotechnical Report, we reviewed the following documents:

Engeo, *Preliminary Geotechnical Report, 315 D Street, Petaluma, California*, October 5, 2016.

Miller Pacific Engineering Group, *Geotechnical Investigation, Adobe Road Winery, 1 C Street, Petaluma, California*, December 2, 2016.

Miller Pacific Engineering Group, *Geotechnical Investigation, Petaluma Trestle Rehabilitation, Petaluma, California*, November 30, 2011.

Miller Pacific Engineering Group, *Slope Stability Analysis, McNear Peninsula, Petaluma, California*, May 18, 2004.

Miller Pacific Engineering Group, *Geotechnical Investigation, Petaluma Flood Control Project, Petaluma, California*, June 20, 1996.

Pinnacle Environmental Inc., *Phase 1 Environmental Site Assessment of a Commercial Property, 315 D Street, Petaluma, California, 91952*, April 21, 2016.

Pinnacle Environmental Inc., *Subsurface Phase II Environmental Site Assessment Report of a Commercial Property, 315 D Street, Petaluma, California 94952*, July 26, 2016.

U.S. Army Corp of Engineers, *Petaluma River, City of Petaluma, California, Section 205, Detailed Project Report for Flood Control, Appendix A, Basis of Design*, November, 1994.

The approximate locations of the nearby borings and cone penetration tests (CPTs) from these previous investigations are shown on the Existing Exploration Plan, Figure 3. The CPT, boring logs, and laboratory testing from the previous investigations are included under Appendix B.

Conclusions

Based on the results of previous subsurface exploration within the site vicinity, we judge that construction of the proposed improvements is feasible from a geotechnical standpoint. The preliminary conclusions and recommendations contained in the Engeo report are generally appropriate for the project site conditions and should be relied upon by the project team as project planning and design advance. The following paragraph includes current seismic design criteria and updated, preliminary foundation design recommendations that should supersede the recommendations in the Engeo Report.

CBC Seismic Criteria

Minimum mitigation of ground shaking includes seismic design of new structures in conformance with the provisions of the most recent edition (2016) of the California Building Code. The magnitude and character of these ground motions will depend on the particular earthquake and the site response characteristics. Based on the interpreted subsurface conditions and close proximity of several nearby faults, we recommend the CBC coefficients and site values shown in Table 1 be used to calculate the design base shear of the new construction.

Table 1 – 2016 California Building Code Seismic Design Criteria

Parameter	Design Value
Site Class	B
Site Latitude	38.237°N
Site Longitude	-122.636°W
Spectral Response (short), S_s	1.560 g
Spectral Response (1-sec), S_1	0.612 g
Site Coefficient, F_a	1.0
Site Coefficient, F_v	1.5

Reference: USGS US Seismic Design Maps (<http://earthquake.usgs.gov/designmaps/us/application>), accessed on December 18, 2017.

Preliminary Foundation Design Criteria

Engeo’s report indicates the proposed commercial, residential, and parking structures can likely be founded on post-tensioned or stiffened mat foundations bearing on geogrid-reinforced engineered fill. These preliminary recommendations were based upon the use of relatively lightly-loaded, wood framed buildings of two stories or less. The proposed project has since been modified to include new structures up to six stories in height which will likely induce moderate to heavy foundation loads. A post-tensioned or stiffened mat foundation may remain a feasible

alternative for the proposed structures provided that estimated building settlements are within acceptable limits. An evaluation of building settlements should be performed as part of final design once additional subsurface exploration and detailed structural information is available. If estimated building settlements are not within acceptable limits, load-balancing or a deep foundation system may be required.

Load balancing may be considered as a means of reducing the potential settlements for the new buildings. This approach would include overexcavating beneath the structure and replacing a portion of the soil that is removed with lightweight material consisting of lava rock, cellular concrete or geofoam. To minimize settlement, the buildings would be designed so that the foundation bearing pressures do not exceed the weight of the soil removed from the excavation. For estimating the required depth of overexcavation, a unit weight of 125 pounds per cubic foot should be used for the existing fill and near-surface soils. The unit weight of the lightweight materials typically varies from about 50 to 65 pounds per cubic foot for lava rock, 25 to 35 pounds per cubic foot for cellular concrete, and 2 to 3 pounds per cubic foot for geofoam.


A deep foundation system may also be utilized to support the new structures and to reduce building settlements. Various deep foundation alternatives are judged to be appropriate, including torque-down piles, auger-cast piles, drilled piers or driven piles. The deep foundations would need to extend through the existing fill and near-surface soils and into the underlying dense/stiff soils. For planning purposes, we anticipate deep foundations would be installed to depths of about 50 feet with estimated capacities of about 70 kips per foundation element. The actual depth and capacity of deep foundations would be determined after a design-level geotechnical investigation is completed.

We trust that this letter contains the information you require at this time. If we can be of further assistance or should there be any questions or concerns regarding this report, please call.

Very truly yours,
MILLER PACIFIC ENGINEERING GROUP




Rusty Arend
Geotechnical Engineer No. 3031
(Expires 6/30/19)



Scott Stephens
Geotechnical Engineer No. 2398
(Expires 6/30/19)

Attachments: Figures 1 to 3, Appendices A and B



SITE COORDINATES

LAT. 38.2370°
LON. -122.6360°

SITE LOCATION

(NO SCALE)



REFERENCE: Google Earth, 2017



A CALIFORNIA CORPORATION, © 2017, ALL RIGHTS RESERVED
FILENAME: 2548.001 Figures.dwg

504 Redwood Blvd.
Suite 220
Novato, CA 94947
T 415 / 382-3444
F 415 / 382-3450
www.millerpac.com

SITE LOCATION MAP


Petaluma Junction
Petaluma, California

Drawn
RCA
Checked

1
FIGURE

Project No. 2458.001

Date: 2/1/2017



MPEG
MILLER PACIFIC
ENGINEERING GROUP

A CALIFORNIA CORPORATION, © 2016, ALL RIGHTS RESERVED
 FILE: 2548.001 Figures.dwg

504 Redwood Blvd.
 Suite 220
 Novato, CA 94947
 T 415 / 382-3444
 F 415 / 382-3450
 www.millerpac.com

SITE PLAN

Petaluma Junction
 Petaluma, California

Project No. 2548.001 Date: 8/3/2016

Designed
 Drawn
 Checked
 RCA
 SAS

2
 FIGURE



LEGEND:

	APPROXIMATE CPT LOCATION BY ENGeo, 2016
	APPROXIMATE BORING LOCATION BY MILLER PACIFIC, 2016
	APPROXIMATE CPT LOCATION BY MILLER PACIFIC, 2011
	APPROXIMATE BORING LOCATION BY MILLER PACIFIC, 2004
	APPROXIMATE BORING LOCATION BY MILLER PACIFIC, 1999
	APPROXIMATE BORING LOCATION BY MILLER PACIFIC, 1996
	APPROXIMATE CPT LOCATION BY MILLER PACIFIC, 1996
	APPROXIMATE BORING LOCATION BY ARMY CORP OF ENGINEERS, 1994



MPEG
MILLER PACIFIC
ENGINEERING GROUP

A CALIFORNIA CORPORATION, © 2016, ALL RIGHTS RESERVED
 FILE: 2548.001 Existing Exploration

504 Redwood Blvd.
 Suite 220
 Novato, CA 94947
 T 415 / 382-3444
 F 415 / 382-3450
 www.millerpac.com

EXISTING EXPLORATION PLAN

Petaluma Junction
 Petaluma, California

Project No. 2458.001 Date: 11/27/2017

Designed	
Drawn	RCA
Checked	SAS

3
 FIGURE



APPENDIX A
PRELIMINARY GEOTECHNICAL REPORT BY ENGEO

PRELIMINARY GEOTECHNICAL REPORT

315 D STREET
PETALUMA, CALIFORNIA

The logo for ENGEEO is rendered in large, white, 3D block letters. The letters are set against a background of a green, rolling hillside under a blue sky. The 'E' and 'O' are particularly prominent. The logo is positioned in the center of the page, overlapping a blue horizontal band that also contains the slogan 'Expect Excellence'.

Expect Excellence

Submitted to:
Mr. Todd Kurtin
Lomas Partners LLC
13848 Weddington Street
Sherman Oaks, CA 91401

Prepared by:
ENGEEO Incorporated

October 5, 2016

Project No:
13253.000.000

Project No.
13253.000.000

October 5, 2016

Mr. Todd Kurtin
Lomas Partners LLC
13848 Weddington Street
Sherman Oaks, CA 91401

Subject: 315 D Street
Petaluma, California

PRELIMINARY GEOTECHNICAL REPORT

Dear Mr. Kurtin:

With your authorization, we completed this preliminary geotechnical report for the 315 D Street project located in Petaluma, California. In preparation of this report, we reviewed our previous field exploration at the neighboring Haystack project to the south of the site, performed a site reconnaissance, conducted a field exploration involving the advancement of cone penetration tests, and obtained near surface samples for laboratory testing. Following review of the field explorations and laboratory test data, we present our conclusions and preliminary recommendations regarding the proposed mixed-use development.

Our findings indicate that the study area is suitable for the proposed development provided the preliminary conclusions and recommendations, and guidelines provided in this report are implemented during project planning. Potential geologic hazards in the study area include potentially liquefiable soil, potentially compressible soil, existing fill, expansive soil, and shallow groundwater. Additional geotechnical exploration services will be required for design-level recommendations. We are pleased to have been of service to you on this project and are prepared to consult further with you and your design team as the project progresses.

Sincerely,

ENGEO Incorporated

Caroline Haatveit

Caroline Haatveit, EIT

Leroy Chan
Leroy Chan, GE
ch/tpb/lc/jf



Theodore P. Bayham
Theodore P. Bayham, GE, CEG



TABLE OF CONTENTS

Letter of Transmittal

1.0	INTRODUCTION	1
1.1	PURPOSE AND SCOPE	1
1.2	SITE LOCATION AND DESCRIPTION	1
1.3	PROPOSED DEVELOPMENT	1
2.0	GEOLOGY AND SEISMICITY	2
2.1	REGIONAL GEOLOGY AND SITE SOILS.....	2
2.2	SITE SEISMICITY	2
3.0	FIELD EXPLORATION.....	3
3.1	CONE PENETRATION TESTING.....	3
3.2	LABORATORY TESTING	3
4.0	SUBSURFACE CONDITIONS	4
4.1	GROUNDWATER.....	4
5.0	SEISMIC HAZARDS.....	4
5.1.1	Ground Rupture	5
5.1.2	Ground Shaking	5
5.1.3	Liquefaction	5
5.1.4	Lateral Spreading.....	6
5.1.5	Lurching.....	6
6.0	DISCUSSION AND CONCLUSIONS	6
6.1	LIQUEFACTION-INDUCED GROUND SETTLEMENT	7
6.2	COMPRESSIBLE SOILS	7
6.3	EXISTING FILLS	8
6.4	EXPANSIVE SOIL.....	8
6.5	SHALLOW GROUNDWATER.....	8
7.0	2013 CBC SEISMIC DESIGN PARAMETERS.....	9
8.0	PRELIMINARY FOUNDATION RECOMMENDATIONS	9
8.1	SECONDARY SLAB-ON-GRADE CONSTRUCTION.....	10
9.0	PRELIMINARY EARTHWORK RECOMMENDATIONS	10
9.1	LIQUEFACTION HAZARD MITIGATION MEASURES.....	10
9.2	EXISTING FILL.....	11
9.3	SELECTION OF MATERIALS	11
9.4	FILL PLACEMENT.....	11

TABLE OF CONTENTS (Continued)

9.5 TEMPORARY DEWATERING FOR UTILITY CONSTRUCTION12
10.0 PRELIMINARY PAVEMENT DESIGN.....12
11.0 DESIGN-LEVEL GEOTECHNICAL EXPLORATION.....13
12.0 LIMITATIONS AND UNIFORMITY OF CONDITIONS.....13

SELECTED REFERENCES

FIGURES

APPENDIX A – Cone Penetration Test (CPT) Logs (Middle Earth Geo Testing)

APPENDIX B – CLiq Preliminary Liquefaction Analysis

APPENDIX C – Laboratory Test Results

1.0 INTRODUCTION

1.1 PURPOSE AND SCOPE

The purpose of this preliminary geotechnical report is to provide preliminary conclusions and recommendations for the proposed mixed-use development in Petaluma, California. The information presented in this report may be used for general land planning purposes.

The scope of our services included:

- Reviewing available literature and geologic maps for the immediate area;
- Reviewing previous field explorations and laboratory test results of the neighboring Haystack project immediately south of the project site;
- Performing a field exploration, which included retaining a subcontractor to advance five cone penetration tests to a depth of approximately 50 feet below ground surface, and collecting near-surface soil samples for laboratory testing;
- Engineering analyses to evaluate site conditions; and,
- Preparing a report summarizing our initial recommendations for proposed site development and recommendations for additional studies.

We prepared this report exclusively for Lomas Partners LLC and their design team consultants. We should review any changes made in the character, design or layout of the development to modify the conclusions and recommendations contained in this report, as necessary. This document may not be reproduced in whole or in part by any means whatsoever, nor may it be quoted or excerpted without our express written consent.

1.2 SITE LOCATION AND DESCRIPTION

The 315 D Street property is approximately 4½ acres in size and is located in Petaluma, California (Figure 1). The site is rectangular and bounded by East Washington Street to the west, Copeland Street to the south, East D Street to the east, and the Petaluma Downtown rail station to the north. The site is relatively level and is currently being used for equipment and stockpile storage for the Sonoma-Marín Area Rail Transit (SMART).

1.3 PROPOSED DEVELOPMENT

Based on the conceptual plans provided by Brian Daigle Architect, the proposed project will include mixed-used two to three story buildings fronting the perimeter streets, and an interior one- to two-level parking garage. Subterranean levels are not anticipated, and the proposed

development will primarily be situated close to existing grades. A new street will bisect the project perpendicular to Copeland Street.

Details regarding planned structural loads and site grading are not available at this time. For this report, we assume grading will be minor and structural loads for the proposed structures will be lightly loading wood-frame type construction. .

2.0 GEOLOGY AND SEISMICITY

2.1 REGIONAL GEOLOGY AND SITE SOILS

The site is located within the Coast Ranges geomorphic province of California. The Coast Ranges are characterized by a series of northwest-trending ridges and valleys that have experienced extensive uplift, folding, and faulting continuing through recent geologic time. Regional geologic mapping of the vicinity (Bezore, 2002) shows the site to be located just outside of the fringe of the Wilson Grove Formation underlain by Holocene terrace and estuarine deposits.

2.2 SITE SEISMICITY

The project is located in a region that contains active earthquake faults; however, no active faults are known to cross the property and the site is not located within an Alquist-Priolo Earthquake Fault Zone. Fault rupture through the site, therefore, is not anticipated. An active fault is defined by the State Mining and Geology Board as one that has had surface displacement within Holocene time (about the last 11,000 years) (Hart, 1997). Numerous small earthquakes occur every year in the San Francisco Bay Region, and larger earthquakes have been recorded and can be expected to occur in the future. The site has been mapped as highly susceptible to liquefaction by USGS. This indicates that site soil may be liquefiable based on mapped geology and depth to groundwater and a site-specific study of liquefaction hazard is required prior to site development.

Based on the United States Geological Survey's (USGS) 2008 National Seismic Hazard Maps, the closest active fault in the area is the Rodgers Creek fault, which is approximately 5.3 miles northeast of the site. Figure 6 shows the approximate locations of mapped active faults and significant historic earthquakes recorded within the San Francisco Bay Region. The following table lists the closest mapped active faults and their proximity to the site.

TABLE 2.2-1
Summarized Nearest Active Faults

Fault Name	Approximate Distance from Project Site (miles)	Maximum Moment Magnitude (Ellsworth)
Rodgers Creek	5.3	7.1
San Andreas	14.6	7.9
West Napa	17.6	6.5
Hayward	17.8	7.1

The Uniform California Earthquake Rupture Forecast (UCERF3, 2013) evaluated the 30-year probability of a Moment Magnitude 6.7 or greater earthquake occurring on the known active fault systems in the San Francisco Bay Area. The UCERF3 generated an overall probability of 72 percent for a Moment Magnitude 6.7 or greater earthquake in the San Francisco Region as a whole.

3.0 FIELD EXPLORATION

3.1 CONE PENETRATION TESTING

To characterize the subsurface condition, we conducted a field exploration on August 25, 2016, that consisted of advancing five cone penetration tests (CPTs) extending to depths of approximately 50 feet below ground surface (bgs). The approximate locations of the CPTs are shown on Figure 2. Our CPTs were advanced until they encountered practical refusal. The CPT data can be found in Appendix A of this report.

We retained a CPT subcontractor who performed the CPTs in general accordance with ASTM D-5778. Measurements collected during testing include the tip resistance to penetration of the cone (Q_c), the resistance of the surface sleeve (F_s), and dynamic pore pressure (U). The CPT logs and supporting empirical data are located in Appendix A. During our field exploration, we also obtained near-surface soil samples for lab testing of near-surface soils.

Pore pressure dissipation tests were conducted in order to determine approximate depths to groundwater. Pore pressure dissipation data is summarized in Section 4.1, below. The CPT holes were backfilled with cement-bentonite grout.

3.2 LABORATORY TESTING

We performed laboratory testing, including Atterberg Limits and sieve testing, on select samples recovered during our field exploration. The laboratory test results are presented in Appendix C.

4.0 SUBSURFACE CONDITIONS

The subsurface conditions encountered in our CPTs consist of approximately 3 feet of existing fills underlain by alluvial soil deposits. The alluvial soil deposits are comprised of alternating layers of clay and silty clay with interbedded layers of silty sand and sandy silt to depths of between 36 and 48 feet below ground surface. Below these depths, the CPTs generally encountered very stiff or dense soil deposits.

4.1 GROUNDWATER

Based on the pore pressure test data, groundwater is estimated at a depth of between approximately 6½ and 9½ feet below the ground surface. Summary of pore pressure dissipation test data are provided in Table 4.1-1:

TABLE 4.1-1
Pore Pressure Dissipation Test Summary

Exploration Location	Estimated Depth to Groundwater (feet)
1-CPT1	9½
1-CPT2	6½
1-CPT3	*
1-CPT4	7
1-CPT5	*

*Test not completed

Fluctuations in groundwater levels should be expected during seasonal changes or over a period of years because of precipitation changes, perched zones, changes in drainage patterns, or irrigation. For preliminary design purposes, we consider a groundwater level on the order of 5 feet bgs.

5.0 SEISMIC HAZARDS

Potential seismic hazards resulting from a nearby moderate to major earthquake can generally be classified as primary and secondary. The primary effect is ground rupture, also called surface faulting. The common secondary seismic hazards include ground shaking, liquefaction, densification and lateral spreading. Based on topographic and lithologic data, the risk of regional subsidence/uplift, landslides, tsunamis, or seiches is considered low to negligible at the site.

The following sections present a discussion of these hazards as they apply to the site.

5.1.1 Ground Rupture

As described above, the site is not located within an Earthquake Fault Special Study Zone. Therefore, it is our opinion that ground rupture is unlikely at the subject property.

5.1.2 Ground Shaking

An earthquake of moderate to high magnitude generated within the San Francisco Bay Region could cause considerable ground shaking at the site, similar to that which has occurred in the past. To mitigate the shaking effects, all structures should be designed using sound engineering judgment and the current California Building Code (CBC) requirements, as a minimum. Seismic design provisions of current building codes generally prescribe minimum lateral forces, applied statically to the structure, combined with the gravity forces of dead-and-live loads. The code-prescribed lateral forces are generally considered to be substantially smaller than the comparable forces that would be associated with a major earthquake. Therefore, structures should be able to: (1) resist minor earthquakes without damage, (2) resist moderate earthquakes without structural damage but with some nonstructural damage, and (3) resist major earthquakes without collapse but with some structural as well as nonstructural damage. Conformance to the current building code recommendations does not constitute any kind of guarantee that significant structural damage would not occur in the event of a maximum magnitude earthquake; however, it is reasonable to expect that a well-designed and well-constructed structure will not collapse or cause loss of life in a major earthquake (SEAOC, 1996).

5.1.3 Liquefaction

Liquefaction is the loss of strength to soil layers due to cyclic loading or seismic shaking. Generally, loose coarse-grained material will undergo liquefaction under a seismic event. Based on observations of soil behavior under seismic shaking and laboratory testing, some fine-grained material, such as silt and clay, can also undergo liquefaction, or cyclic softening dependent on the plasticity index (PI). In order for a soil to be potentially liquefiable, it must be saturated; therefore, for this site, we conservatively considered soil at a depth of 5 feet below the ground surface to be susceptible to liquefaction based on our exploration data from CPT pore pressure dissipation tests.

We analyzed the potential for liquefaction and resulting settlement using the CPT data with the software program CLiq (version 1.7.6.34) applying the methodologies published by Robertson (2009) and Zhang et al. (2002). We used a design groundwater depth of 5 feet, the Maximum Considered Earthquake Geometric Mean Peak Ground Acceleration (PGAM) mapped for the site based on the 2013 California Building Code of 0.60g, and a moment magnitude of 7.94 based on a theoretical rupture of the San Andreas fault. In our analyses, we assumed an I_c (soil behavior index) cutoff of 2.6 to represent the boundary of sand and fine-grained soil; we also considered the potential of fine-grained soil to liquefy (or cyclically soften).

We present the results of our preliminary liquefaction analysis in Appendix B, and discuss the results in Section 6.0.

It should be noted that our preliminary analysis suggests that majority of the soil layers that are potentially susceptible to seismic deformation has a relatively fines-content based on CPT interpretations. Representative samples of these material were not collected due to the method of exploration conducted within this scope, therefore, we recommend additional laboratory testing to update the liquefaction analyses be performed during a design-level study.

5.1.4 Lateral Spreading

Lateral spreading is a failure within a continuous soil layer (typically due to liquefaction) that causes the overlying soil mass to move toward a free face or down a slope. Generally, effects of lateral spreading are most significant at the free face or the crest of a slope and diminish with distance from the slope.

Because the site is relatively level and over 500 feet away from free face of the Petaluma River, existing exploration in the area have suggested that the layers of potentially-liquefiable material appears discontinuous, we believe the potential for lateral spreading is low. We recommend that this is further assessed during a design-level exploration, once the susceptibility for liquefaction is further explored.

5.1.5 Lurching

Ground lurching is a result of the rolling motion imparted to the ground surface during energy released by an earthquake. Such rolling motion can cause ground cracks to form. The potential for the formation of these cracks is considered greater at contacts between deep alluvium and bedrock. Such an occurrence is possible at the site as in other locations in the Bay Area, but based on the site location, it is our opinion that the offset is expected to be minor.

6.0 DISCUSSION AND CONCLUSIONS

From a geologic and geotechnical standpoint, the study area appears to be suitable for the proposed development. The preliminary recommendations in this report should be considered in the initial planning for the study area. Additional explorations will be required to develop design-level recommendations for site grading and foundations.

Potential geologic hazards in the study area include the following:

- potentially liquefiable soil
- potentially compressible soil
- existing fill
- expansive soil
- shallow groundwater

We discuss each of these potential hazards and other geotechnical issues relevant to the study below.

6.1 LIQUEFACTION-INDUCED GROUND SETTLEMENT

Results of the preliminary liquefaction-induced settlement are shown in Table 6.1-1. Analysis output from analytical software Cliq is provided in Appendix B.

TABLE 6.1-1
Total Liquefaction-Induced Settlement Estimates ($I_c = 2.60$)

Exploration Location	Estimated Total Vertical Settlement
1-CPT1	3½
1-CPT2	2
1-CPT3	2
1-CPT4	1
1-CPT5	3

We calculated liquefaction-induced settlements that are between 1 and 3½ inches of total vertical settlement. For planning purposes, we recommend the site be designed for 3½ inches total liquefaction-induced settlement and with differential liquefaction-induced settlements of 1¾ inches over a distance of 30 feet. Once further characterized is completed for the site following a design-level study, this settlement estimate may be able to be modified.

Based on our experience with neighboring projects, this material that has been determined here to be potentially liquefiable may contain a significant amount of fine-grained material and may be less susceptible to liquefaction-induced settlement than has been presented above. We recommend a design-level exploration that involves borings and laboratory testing for further characterization and analyses of the potentially liquefiable material.

As discussed by Youd and Garris (1995), liquefiable soil that is not overlain by a sufficiently thick layer of soil that is not liquefiable is more prone to ground surface disruptions such as fissures and sand boils. Building foundations bearing on shallow liquefiable soil could be subject to localized bearing capacity failures or excessive settlement due to ground loss. The thickness of non-liquefiable soil necessary to reduce this risk is a function of the thickness of the liquefiable soil layer below. Based on the study by Youd and Garris, there may be an insufficient thickness of non-liquefiable soil to prevent sand boils. Without mitigation there is a risk of sand boils forming in isolated areas within the proposed building footprint. These effects could also result in limited areas of pavement buckling, utility breaks or settlement greater than the amounts discussed in Table 6.1-1 above.

6.2 COMPRESSIBLE SOILS

Compressible soils may settle in response to new loads introduced by new fill, structures or equipment; this settlement, if it occurs may occur as elastic or consolidation settlement. Elastic settlement is a function of soil stiffness while consolidation settlement is highly dependent on the

amount of water-filled voids within the soil. The rate of settlement is highly dependent on the permeability of the soil and the presence of water. Consequently, sandy soil will settle almost immediately, whereas clayey soil below the water table will settle much more slowly.

In most of our CPTs, the clay that was encountered was overconsolidated, with the exception of 1-CPT3 located at the southwestern corner of the site, where a layer of potentially compressible clay at approximate 8 to 15 feet below ground surface was encountered. This localized layer was interpreted to be normally consolidated and, therefore, would potentially be compressible subjected to magnitude of new loading from the proposed structures.

We recommend that additional borings and laboratory testing be concentrated in this area of the site during a design-level exploration for further characterization and analysis of this potentially compressible material and its potential effect on the proposed development. The amount of consolidation settlement is subject to the loading conditions and should be assessed further once loading conditions are known during a design-level exploration.

6.3 EXISTING FILLS

Evidence of existing fill, approximately 3 feet in thickness, was apparent in our CPT soundings and hand-auger samples. The existing fill appears to be highly variable, which could result in variable performance for structures on shallow foundations bearing on this material. Existing fill without documentation that it was placed in an engineered manner with appropriate levels of compaction for the proposed development should be considered non-engineered. In general, non-engineered fill should be excavated and replaced as engineered fill. The extent and quality of existing fill should be evaluated at the time of design-level study and mitigated during grading activities.

6.4 EXPANSIVE SOIL

Based upon our sampling and testing of near-surface soil, the surficial soil at the site is expected to be moderately expansive. Expansive soil shrinks and swells as a result of moisture changes. This can cause heaving and cracking of slabs-on-grade, pavements, and structures founded on shallow foundations.

Successful construction on expansive soil requires special attention during grading. It is imperative to keep exposed soils moist by occasional sprinkling. If the soil dries, it is extremely difficult to remoisturize the soil (because of their clayey nature) without excavation, moisture conditioning, and recompaction.

6.5 SHALLOW GROUNDWATER

Based on the encountered groundwater depth encountered in our exploration at a depth of between 6½ and 9½ feet below the ground surface, the static groundwater level beneath the site could affect the proposed development.

Shallow groundwater can:

1. Impede grading activities.
2. Require temporary construction dewatering.
3. Cause moisture damage to sensitive floor coverings.
4. Transmit moisture vapor through slabs causing excessive mold/mildew build-up, fogging of windows, and damage to computers and other sensitive equipment.

7.0 2013 CBC SEISMIC DESIGN PARAMETERS

Based on the subsurface conditions and the types of structures planned, we characterized the site as Site Class D. We provide the ASCE 7-10 seismic design parameters for Site Class D in the table below:

TABLE 7.0-1
ASCE 7-10 Seismic Design Parameters
Site Location Lat: 38.2368°N Long: 122.6356°W

Parameter	Design Value
Site Class	D
Mapped MCE _R Spectral Response Acceleration at Short Periods, S _S (g)	1.56
Mapped MCE _R Spectral Response Acceleration at 1-second Period, S ₁ (g)	0.61
Site Coefficient, F _A	1.0
Site Coefficient, F _V	1.5
MCE _R Spectral Response Acceleration at Short Periods, S _{MS} (g)	1.56
MCE _R Spectral Response Acceleration at 1-second Period, S _{M1} (g)	0.92
Design Spectral Response Acceleration at Short Period, S _{DS} (g)	1.04
Design Spectral Response Acceleration at 1-second Period, S _{D1} (g)	0.61
MCE _G Peak Ground Acceleration adjusted for Site Class effects, PGA _M (g)	0.60

8.0 PRELIMINARY FOUNDATION RECOMMENDATIONS

The proposed structures will need to be able to address the shrink-swell of the surface soil and potential differential settlement due to static loading and liquefaction. While these soil movements should be combined to evaluate the seismic load case, our experience indicates that larger amounts of architectural distress are commonly tolerated for load checks including seismic loading.

Based on our experience and the anticipated building types, it is our opinion that the proposed commercial, residential, and parking structures can be founded on post-tensioned (PT) or stiffened mat foundations bearing on geogrid-reinforced engineered fill.

Further discussion about proposed building loads and layouts, additional exploration, laboratory testing, and detailed assessment of estimated liquefaction- and load-induced settlements should occur prior to preparation of site-specific foundation designs for the development. The amount of estimated settlement will impact the selection of foundation type for the structures.

Additional PT mat foundation and reinforced mat foundation recommendations will be provided upon conclusion of a design-level study.

8.1 SECONDARY SLAB-ON-GRADE CONSTRUCTION

This section provides guidelines for secondary slabs such as exterior walkways, driveways, steps, approach ramps, and sidewalks.

Secondary slabs-on-grade should be constructed structurally independent of the foundation system. This allows slab movement to occur with a minimum of foundation distress. Secondary slabs-on-grade should be designed by the Structural Engineer specifically for their intended use and loading requirements. Cracking of conventional slabs should be expected as a result of concrete shrinkage. Slabs-on-grade should be reinforced and include frequent control joints to control the cracking. Such reinforcement should be designed by the Structural Engineer. In our experience, welded wire mesh may not be sufficient to control slab cracking.

Ideally, secondary slabs-on-grade should have a minimum thickness of 4 inches. A 4-inch-thick layer of clean crushed rock or gravel should be placed under slabs. Slabs should slope away from the buildings at a slope of at least 2 percent to prevent water from flowing toward the building. Turned down free edges extending at least beneath the crushed rock or gravel into compacted soil should be constructed to reduce water infiltration into subgrade soils. Waterproof barriers may also be considered.

Alternatively, and with some additional risk of cracking and/or heaving of secondary slabs, the layer of clean crushed rock or gravel beneath slabs and the turned down edges can be eliminated. If these recommendations are eliminated, it is critical that uniformity in soil moisture conditioning be achieved in subgrade soils and that subgrade soils are not allowed to dry out prior to slab construction.

9.0 PRELIMINARY EARTHWORK RECOMMENDATIONS

The following recommendations are for initial land planning and preliminary estimating purposes. Final recommendations regarding site grading and foundation construction will be provided after additional site-specific exploration has been undertaken.

9.1 LIQUEFACTION HAZARD MITIGATION MEASURES

Due to the variable subsurface conditions at the site and the associated varying degrees of liquefaction-induced settlement predicted around the site, we recommend that within the building envelope and the area extending 10 feet beyond the edge of the building that the existing fill be

removed and replaced with engineered fill reinforced with geotextile fabric (geogrid) layer(s). In order to help bridge any differential settlements caused by liquefaction, we recommend that the upper 5 feet of subsurface material be completely over-excavated and recompacted as engineered fill or imported granular fill. The layers of geogrids should consist of triaxial geogrids placed between layers of backfill. Further recommendations regarding liquefaction hazard mitigation measures will be provided upon conclusion of a design-level study.

9.2 EXISTING FILL

The history of the fill placement on the site is unknown. Consequently, it is assumed that the existing fill and utility trench backfill are considered non-engineered and should be subexcavated to expose underlying competent native soil that is approved in the field by a representative of our firm. Additionally, as discussed above in Section 9.1, on a preliminary level we recommend that a layer of triaxial geogrid should be installed over the exposed overexcavated subgrade and again in the middle of the engineered fill layer in order to help bridge differential settlements caused by liquefaction-induced or load-induced settlements.

9.3 SELECTION OF MATERIALS

The site soils are suitable for use as engineered fill provided they do not contain deleterious material, debris and high organic content (soil that contains more than 3 percent organics). We should be informed when import materials are planned for the site. Import materials should have a PI less than 12 and with no particle greater than 6 inches in diameter. Import materials should be submitted and approved by our representatives prior to delivery at the site.

9.4 FILL PLACEMENT

After removal of any loose soil, the exposed non-yielding surface of areas to receive fill should be scarified to a depth of 12 inches, moisture conditioned, and recompacted to provide adequate bonding with the initial lift of fill. The lift thickness should not exceed 12 inches or the depth of penetration of the compaction equipment used, whichever is less. For land planning and cost estimating purposes, the following compaction control requirements should be applied to all fill including backfill, except for landscape areas:

- For materials with an observed Plasticity Index (PI) less than 12 we recommend:

Test Procedures:	ASTM D-1557, latest edition.
Required Moisture Content:	Not less than 2 percentage points above optimum moisture content.
Minimum Relative Compaction:	Not less than 90 percent.

- For materials with an observed PI greater than 12 we recommend:

Test Procedures:	ASTM D-1557, latest edition.
Required Moisture Content:	Not less than 4 percentage points above optimum moisture content.
Relative Compaction:	Between 87 and 92 percent.

We recommend that all site preparation, including demolition and stripping be performed under the observation of the Geotechnical Engineer’s qualified field representative.

9.5 TEMPORARY DEWATERING FOR UTILITY CONSTRUCTION

As previously mentioned, groundwater was encountered between 6½ and 9½ feet below ground surface during our site exploration. Utility trench excavation may require temporary dewatering during construction to keep the excavation and working areas reasonably dry. We anticipate that dewatering for utility construction can be accomplished by pumping from sumps. Extended dewatering of utility trench excavations may cause settlement of newly installed pipelines and adjacent improvements. In addition, post-construction long-term dewatering may occur due to the movement of water along utility trenches. We recommend that utility trenches include low permeability cutoffs to reduce the risk of inadvertent groundwater flow along permeable backfill. In addition, seepage into utility joints may effectively cause dewatering and lead to settlement. We recommend that trench depth be limited as much as practical for the development and that utilities be watertight.

10.0 PRELIMINARY PAVEMENT DESIGN

Preliminary pavement design is provided based on assumed Traffic Indices and subgrade resistance values (R-value). The Traffic Index should be determined by the Civil Engineer or appropriate public agency. Based on an assumed R-value of 5, the method contained in Chapters 600 through 630 of the Highway Design Manual by Caltrans (including the asphalt factor of safety), and assumed Traffic Indices ranging from 5.0 to 6.0, we recommend the minimum pavement design sections shown in Table 10.0-1

TABLE 10.0-1
Preliminary Asphalt Concrete Pavement Sections for an R-Value of 5

Traffic Index (TI)	Pavement Design	
	HMA (inches)	AB (inches)
5.0	3.0	10.0
5.5	3.0	12.0
6.0	3.5	13.0

The Civil Engineer should determine the appropriate traffic indices based on the estimated traffic loads and frequencies. The subgrade and aggregate base should be compacted in accordance with Section 7.4. Aggregate Base should meet the requirements for $\frac{3}{4}$ inch maximum Class 2 AB per Section 26-1.02a of the latest Caltrans Standard Specifications.

11.0 DESIGN-LEVEL GEOTECHNICAL EXPLORATION

A design-level geotechnical exploration should be performed as part of the design process, which would include borings, and laboratory soil testing as needed, to provide data for preparation of specific recommendations regarding site grading, remedial grading measures, foundations, and drainage for the proposed development. The exploration will also allow for more detailed evaluations of the above-described geotechnical issues and afford the opportunity to provide techniques and procedures to be implemented during construction to mitigate potential geotechnical/geological hazards.

12.0 LIMITATIONS AND UNIFORMITY OF CONDITIONS

This report is issued with the understanding that it is the responsibility of the owner to transmit the information and recommendations of this report to developers, owners, buyers, architects, engineers, and designers for the project so that the necessary steps can be taken by the contractors and subcontractors to carry out such recommendations in the field. The conclusions and recommendations contained in this report are solely professional opinions.

The professional staff of ENGEO strives to perform its services in a proper and professional manner with reasonable care and competence but is not infallible. There are risks of earth movement and property damages inherent in land development. We are unable to eliminate all risks or provide insurance; therefore, we are unable to guarantee or warrant the results of our services.

This report is based upon field and other conditions discovered at the time of preparation of ENGEO's report. This document must not be subject to unauthorized reuse that is, reusing without written authorization of ENGEO. Such authorization is essential because it requires ENGEO to evaluate the document's applicability given new circumstances, not the least of which is passage of time. Actual field or other conditions will necessitate clarifications, adjustments, modifications or other changes to ENGEO's documents. Therefore, ENGEO must be engaged to prepare the necessary clarifications, adjustments, modifications or other changes before construction activities commence or further activity proceeds. If ENGEO's scope of services does not include on-study area construction observation, or if other persons or entities are retained to provide such services, ENGEO cannot be held responsible for any or all claims arising from or resulting from the performance of such services by other persons or entities, and from any or all claims arising from or resulting from clarifications, adjustments, modifications, discrepancies or other changes necessary to reflect changed field or other conditions.

SELECTED REFERENCES

- Bray, J.D. and Sancio, R.B., September 2006, Assessment of the Liquefaction Susceptibility of Fine-Grained Soils, Journal of Geotechnical and Geoenvironmental Engineering, California Building Code, 2010.
- Bezore, S., Randolph-Load, C.E., Witter, R.C., 2002, Geological Map of Petaluma, California, U.S. California Geological Survey.
- California Building Standards Commission, 2013 California Building Code, Volumes 1 and 2, Sacramento, California.
- ENGEO, Geotechnical Exploration, Haystack Property, Petaluma, California; March 8, 2006; Project No. 6809.2.001.01.
- Hart, E.W., and Bryant, W.A., 1997, Fault rupture hazard in California: Alquist-Priolo earthquake fault zoning act with index to earthquake fault zone maps: California Division of Mines and Geology Special Publication 42.
- Idriss, I.M. and Boulanger, R.W., 2008, Soil Liquefaction During Earthquakes, Earthquake Engineering Research Institute, Monograph MNO-12.
- Robertson, P.K., 2009, Interpretation of Cone Penetration Tests – A Unified Approach, Canadian Geotechnical Journal 2009, Vol 46, pp. 1337-1355
- Seed, R.B., Cetin K.O., Moss R.E.S., Kammerer A.M., Wu J., Pestana J.M., Riemer M.F., Sancio R.B., Bray J.D., Kayen R.E., Faris A., 2003, Recent Advances in Soil Liquefaction Engineering A unified and Consistent Framework, 26th Annual ASCE Los Angeles Geotechnical Spring Seminar.
- SEAOC, 1996, Recommended Lateral Force Requirements and Commentary.
- United States Geologic Survey (USGS); 2008, National Seismic Hazard Maps Fault Parameters.
- Working Group on California Earthquake Probabilities, 2013, The Uniform California Earthquake Rupture Forecast, Version 3 UCERF 3, USGS Open File Report 2013.
- Youd, T.L. and Garris, C.T., 1995, Liquefaction-Induced Ground-Surface Disruption, Journal of Geotechnical Engineering, American Society of Civil Engineers, Vol. 121, No. 11, November, pp. 805-809.
- Zhang, G., Robertson, P.K., and Brachman, R.W.I., 2002, Estimating Liquefaction-Induced Ground Settlements from CPT for Level Ground, Can. Geotech. J. 39, 1168-1180.

FIGURES

Figure 1 - Vicinity Map

Figure 2 - Site Plan


Figure 3 - Regional Geologic Map

Figure 4 – Liquefaction Susceptibility Map

Figure 5 – Regional Faulting and Seismicity



COPYRIGHT © 2016 BY ENGeo INCORPORATED. THIS DOCUMENT MAY NOT BE REPRODUCED IN WHOLE OR IN PART BY ANY MEANS WHATSOEVER, NOR MAY IT BE QUOTED OR EXCERPTED WITHOUT THE EXPRESS WRITTEN CONSENT OF ENGeo INCORPORATED.



BASE MAP SOURCE: GOOGLE EARTH MAPPING SERVICE




VICINITY MAP
315 D STREET
PETALUMA, CALIFORNIA

PROJECT NO.: 13253.000.000
SCALE: AS SHOWN
DRAWN BY: SRP CHECKED BY: LC

FIGURE NO.
1

COPYRIGHT © 2016 BY ENGeo INCORPORATED. THIS DOCUMENT MAY NOT BE REPRODUCED IN WHOLE OR IN PART BY ANY MEANS WHATSOEVER, NOR MAY IT BE QUOTED OR EXCERPTED WITHOUT THE EXPRESS WRITTEN CONSENT OF ENGeo INCORPORATED.



EXPLANATION

ALL LOCATIONS ARE APPROXIMATE

- Qhbm HOLOCENE ESTUARINE DEPOSITS (COMPRESSIBLE CLAY DEPOSIT)
- Qhf HOLOCENE FAN DEPOSITS
- Qhty HOLOCENE TERRACE DEPOSITS
- Qpf LATE PLEISTOCENE FAN DEPOSITS
- Twg WILSON GROVE FORMATION


BASE MAP SOURCE: BEZORE, 2002



REGIONAL GEOLOGIC MAP
315 D STREET
PETALUMA, CALIFORNIA

PROJECT NO.:	13253.000.000
SCALE:	AS SHOWN
DRAWN BY:	SRP
CHECKED BY:	LC

FIGURE NO.
3



EXPLANATION

Liquefaction Susceptibility

- Very High
- High
- Moderate
- Low
- Very Low



BASE MAP SOURCE: ABAG, 2000



LIQUEFACTION SUSCEPTIBILITY MAP
 315 D STREET
 PETALUMA, CALIFORNIA

PROJECT NO.: 13253.000.000

SCALE: AS SHOWN

DRAWN BY: SRP

CHECKED BY: LC

FIGURE NO.

4

**A
P
P
E
N
D
I
X

A**

APPENDIX A

**Middle Earth Geo Testing
Cone Penetration Test (CPT) Logs**






Engeo Inc

Project Petaluma Station Mix Use Development Operator JH-KK
 Job Number 13253.000.000 Cone Number DDG1333
 Hole Number 1CPT-1 Date and Time 8/25/2016 9:19:36 AM
 EST GW Depth During Test 9.40 ft

Filename SDF(030).cpt
 GPS _____
 Maximum Depth 48.06 ft

Net Area Ratio .8

CPT DATA



- 1 - sensitive fine grained
- 4 - silty clay to clay
- 7 - silty sand to sandy silt
- 10 - gravelly sand to sand
- 2 - organic material
- 5 - clayey silt to silty clay
- 8 - sand to silty sand
- 11 - very stiff fine grained (*)
- 3 - clay
- 6 - sandy silt to clayey silt
- 9 - sand
- 12 - sand to clayey sand (*)

Cone Size 10cm squared

S*Soil behavior type and SPT based on data from UBC-1983




Engeo Inc

Project Petaluma Station Mix Use Development Operator JH-KK
 Job Number 13253.000.000 Cone Number DDG1333
 Hole Number 1CPT-2 Date and Time 8/25/2016 1:27:57 PM
 EST GW Depth During Test 6.70 ft

Filename SDF(004).cpt
 GPS _____
 Maximum Depth 50.52 ft

Net Area Ratio .8

CPT DATA



- | | | | |
|------------------------------|---------------------------------|--------------------------------|------------------------------------|
| ■ 1 - sensitive fine grained | ■ 4 - silty clay to clay | ■ 7 - silty sand to sandy silt | ■ 10 - gravelly sand to sand |
| ■ 2 - organic material | ■ 5 - clayey silt to silty clay | ■ 8 - sand to silty sand | ■ 11 - very stiff fine grained (*) |
| ■ 3 - clay | ■ 6 - sandy silt to clayey silt | ■ 9 - sand | ■ 12 - sand to clayey sand (*) |

Cone Size 10cm squared

S*Soil behavior type and SPT based on data from UBC-1983




Engeo Inc

Project Petaluma Station Mix Use Development Operator JH-KK
 Job Number 13253.000.000 Cone Number DDG1333
 Hole Number 1CPT-3 Date and Time 8/25/2016 12:31:16 PM
 EST GW Depth During Test 7.00 ft

Filename SDF(034).cpt
 GPS _____
 Maximum Depth 42.16 ft

Net Area Ratio .8

CPT DATA



SOIL BEHAVIOR TYPE

- | | | | |
|------------------------------|---------------------------------|--------------------------------|------------------------------------|
| ■ 1 - sensitive fine grained | ■ 4 - silty clay to clay | ■ 7 - silty sand to sandy silt | ■ 10 - gravelly sand to sand |
| ■ 2 - organic material | ■ 5 - clayey silt to silty clay | ■ 8 - sand to silty sand | ■ 11 - very stiff fine grained (*) |
| ■ 3 - clay | ■ 6 - sandy silt to clayey silt | ■ 9 - sand | ■ 12 - sand to clayey sand (*) |

Cone Size 10cm squared

S*Soil behavior type and SPT based on data from UBC-1983




Engeo Inc

Project Petaluma Station Mix Use Development Operator JH-KK
 Job Number 13253.000.000 Cone Number DDG1333
 Hole Number 1CPT-4 Date and Time 8/25/2016 11:32:20 AM
 EST GW Depth During Test 6.90 ft

Filename SDF(033).cpt
 GPS _____
 Maximum Depth 43.31 ft

Net Area Ratio .8

CPT DATA



Cone Size 10cm squared

S*Soil behavior type and SPT based on data from UBC-1983




Engeo Inc

Project Petaluma Station Mix Use Development Operator JH-KK
 Job Number 13253.000.000 Cone Number DDG1333
 Hole Number 1CPT-5 Date and Time 8/25/2016 2:14:26 PM
 EST GW Depth During Test 7.00 ft

Filename SDF(005).cpt
 GPS _____
 Maximum Depth 50.20 ft

Net Area Ratio .8

CPT DATA



- | | | | |
|------------------------------|---------------------------------|--------------------------------|------------------------------------|
| ■ 1 - sensitive fine grained | ■ 4 - silty clay to clay | ■ 7 - silty sand to sandy silt | ■ 10 - gravelly sand to sand |
| ■ 2 - organic material | ■ 5 - clayey silt to silty clay | ■ 8 - sand to silty sand | ■ 11 - very stiff fine grained (*) |
| ■ 3 - clay | ■ 6 - sandy silt to clayey silt | ■ 9 - sand | ■ 12 - sand to clayey sand (*) |

Cone Size 10cm squared

S*Soil behavior type and SPT based on data from UBC-1983

APPENDIX B

CLiq Preliminary Liquefaction Analysis



LIQUEFACTION ANALYSIS REPORT




Project title : 315 D Street

Location : Petaluma, California


CPT file : 1-CPT1

Input parameters and analysis data

Analysis method:	Robertson (2009)	G.W.T. (in-situ):	5.00 ft	Use fill:	No	Clay like behavior	
Fines correction method:	Robertson (2009)	G.W.T. (earthq.):	5.00 ft	Fill height:	N/A	applied:	All soils
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	No
Earthquake magnitude M_w :	7.94	Ic cut-off value:	2.60	Trans. detect. applied:	No	Limit depth:	N/A
Peak ground acceleration:	0.60	Unit weight calculation:	Based on SBT	K_σ applied:	No	MSF method:	Method based



CPT basic interpretation plots (normalized)




Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K _σ applied:	No
Earthquake magnitude M _w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis overall plots



Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K_{σ} applied:	No
Earthquake magnitude M_w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

F.S. color scheme

- Almost certain it will liquefy
- Very likely to liquefy
- Liquefaction and no liq. are equally likely
- Unlike to liquefy
- Almost certain it will not liquefy

LPI color scheme

- Very high risk
- High risk
- Low risk

LIQUEFACTION ANALYSIS REPORT




Project title : 315 D Street

Location : Petaluma, California


CPT file : 1-CPT2

Input parameters and analysis data

Analysis method:	Robertson (2009)	G.W.T. (in-situ):	5.00 ft	Use fill:	No	Clay like behavior	
Fines correction method:	Robertson (2009)	G.W.T. (earthq.):	5.00 ft	Fill height:	N/A	applied:	All soils
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	No
Earthquake magnitude M_w :	7.94	Ic cut-off value:	2.60	Trans. detect. applied:	No	Limit depth:	N/A
Peak ground acceleration:	0.60	Unit weight calculation:	Based on SBT	K_σ applied:	No	MSF method:	Method based



CPT basic interpretation plots (normalized)




Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K _σ applied:	No
Earthquake magnitude M _w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis overall plots



Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K_{σ} applied:	No
Earthquake magnitude M_w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

F.S. color scheme

- Almost certain it will liquefy
- Very likely to liquefy
- Liquefaction and no liq. are equally likely
- Unlike to liquefy
- Almost certain it will not liquefy

LPI color scheme

- Very high risk
- High risk
- Low risk

LIQUEFACTION ANALYSIS REPORT




Project title : 315 D Street

Location : Petaluma, California


CPT file : 1-CPT3

Input parameters and analysis data

Analysis method:	Robertson (2009)	G.W.T. (in-situ):	5.00 ft	Use fill:	No	Clay like behavior	
Fines correction method:	Robertson (2009)	G.W.T. (earthq.):	5.00 ft	Fill height:	N/A	applied:	All soils
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	No
Earthquake magnitude M_w :	7.94	Ic cut-off value:	2.60	Trans. detect. applied:	No	Limit depth:	N/A
Peak ground acceleration:	0.60	Unit weight calculation:	Based on SBT	K_σ applied:	No	MSF method:	Method based



CPT basic interpretation plots (normalized)




Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K _σ applied:	No
Earthquake magnitude M _w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis overall plots



Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K_{σ} applied:	No
Earthquake magnitude M_w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

F.S. color scheme

- Almost certain it will liquefy
- Very likely to liquefy
- Liquefaction and no liq. are equally likely
- Unlike to liquefy
- Almost certain it will not liquefy

LPI color scheme

- Very high risk
- High risk
- Low risk

LIQUEFACTION ANALYSIS REPORT




Project title : 315 D Street

Location : Petaluma, California


CPT file : 1-CPT4

Input parameters and analysis data

Analysis method:	Robertson (2009)	G.W.T. (in-situ):	5.00 ft	Use fill:	No	Clay like behavior	
Fines correction method:	Robertson (2009)	G.W.T. (earthq.):	5.00 ft	Fill height:	N/A	applied:	All soils
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	No
Earthquake magnitude M_w :	7.94	Ic cut-off value:	2.60	Trans. detect. applied:	No	Limit depth:	N/A
Peak ground acceleration:	0.60	Unit weight calculation:	Based on SBT	K_o applied:	No	MSF method:	Method based



CPT basic interpretation plots (normalized)




Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K _σ applied:	No
Earthquake magnitude M _w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis overall plots



Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K_{σ} applied:	No
Earthquake magnitude M_w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

F.S. color scheme

- Almost certain it will liquefy
- Very likely to liquefy
- Liquefaction and no liq. are equally likely
- Unlike to liquefy
- Almost certain it will not liquefy

LPI color scheme

- Very high risk
- High risk
- Low risk

LIQUEFACTION ANALYSIS REPORT




Project title : 315 D Street

Location : Petaluma, California


CPT file : 1-CPT5

Input parameters and analysis data

Analysis method:	Robertson (2009)	G.W.T. (in-situ):	5.00 ft	Use fill:	No	Clay like behavior	
Fines correction method:	Robertson (2009)	G.W.T. (earthq.):	5.00 ft	Fill height:	N/A	applied:	All soils
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	No
Earthquake magnitude M_w :	7.94	Ic cut-off value:	2.60	Trans. detect. applied:	No	Limit depth:	N/A
Peak ground acceleration:	0.60	Unit weight calculation:	Based on SBT	K_σ applied:	No	MSF method:	Method based



CPT basic interpretation plots (normalized)




Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K _σ applied:	No
Earthquake magnitude M _w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis overall plots



Input parameters and analysis data

Analysis method:	Robertson (2009)	Depth to water table (erthq.):	5.00 ft	Fill weight:	N/A
Fines correction method:	Robertson (2009)	Average results interval:	3	Transition detect. applied:	No
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K_{σ} applied:	No
Earthquake magnitude M_w :	7.94	Unit weight calculation:	Based on SBT	Clay like behavior applied:	All soils
Peak ground acceleration:	0.60	Use fill:	No	Limit depth applied:	No
Depth to water table (insitu):	5.00 ft	Fill height:	N/A	Limit depth:	N/A

F.S. color scheme

- Almost certain it will liquefy
- Very likely to liquefy
- Liquefaction and no liq. are equally likely
- Unlike to liquefy
- Almost certain it will not liquefy

LPI color scheme

- Very high risk
- High risk
- Low risk

**A
P
P
E
N
D
I
X


C**

APPENDIX C

Laboratory Test Results



Particle Size Distribution Report



% +75mm	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
						49.7	

SIEVE SIZE	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
#200	49.7		

Soil Description

See exploration logs

Atterberg Limits
 PL= 13 LL= 32 PI= 19

Coefficients
 D₉₀= D₈₅= D₆₀=
 D₅₀= D₃₀= D₁₅=
 D₁₀= C_u= C_c=

Classification
 USCS= AASHTO=

Remarks
 GS: ASTM D1140
 PI: ASTM D4318, Wet method

* (no specification provided)

Sample Number: 1-CPT1 @ 4.5

Depth: 4.5-5.0 feet


Date: 08/31/16



Client: Loma Partners, LLC
Project: 315 D Street Petaluma
Project No: 13253.000.000

Tested By: G. Criste Checked By: D. Seibold

LIQUID AND PLASTIC LIMITS TEST REPORT



	MATERIAL DESCRIPTION	LL	PL	PI	%<#40	%<#200	USCS
●	See exploration logs	32	13	19		49.7	

Project No. 13253.000.000 **Client:** Loma Partners, LLC
Project: 315 D Street Petaluma
● Depth: 4.5-5.0 feet **Sample Number:** 1-CPT1 @ 4.5

Remarks:
 ● PI: ASTM D4318, Wet method
 GS: ASTM D1140



Tested By: M. Quasem **Checked By:** G. Criste




APPENDIX B

PREVIOUS SUBSURFACE EXPLORATION AND LAB TESTING

BORINGS BY MILLER PACIFIC, 2016

		BORING 1							
DEPTH meters feet	SAMPLE SYMBOL (4)	EQUIPMENT: Truck-Mounted B54 Drill Rig with 6-inch hollow stem auger		BLOWS / FOOT (1)	DRY UNIT WEIGHT pcf (2)	MOISTURE CONTENT (%)	SHEAR STRENGTH psf (3)	OTHER TEST DATA	OTHER TEST DATA
		DATE: 11/14/2016							
		ELEVATION: 10 - feet (+/-)*							
		*REFERENCE: ALTA Suvey by Cinquini and Passarino, Inc. dated February, 2016							
0		4 in of Asphalt over 6 in of Aggregate Base							
1		Clayey SAND with Gravel (SC) dark blue-gray to brown, moist, medium dense, fine- to coarse-grained sand, low plasticity clay [Fill]		18	114	11.6	500	10 (PI)	
5		Clayey SAND (SC) dark gray, wet, loose, fine-grained sand [Estuarine Deposits]		7	102	21.6		33.2% (P200)	
2				9		22.3			
3		Poorly Graded SAND with Silt (SP-SM) gray-brown, saturated, medium dense, fine-grained sand [Estuarine Deposits]		12		23.8		11.4% (P200)	
4									
5		CLAY with Sand (CH) brown, wet, stiff, medium to high plasticity [Estuarine Deposits]		18		42.4			
6									

NOTES: (1) UNCORRECTED FIELD BLOW COUNTS
(2) METRIC EQUIVALENT DRY UNIT WEIGHT $\text{kN/m}^3 = 0.1571 \times \text{DRY UNIT WEIGHT (pcf)}$
(3) METRIC EQUIVALENT STRENGTH (kPa) = $0.0479 \times \text{STRENGTH (psf)}$
(4) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY



A CALIFORNIA CORPORATION, © 2016, ALL RIGHTS RESERVED
FILE: 2379.001 BL.dwg

504 Redwood Blvd.
Suite 220
Novato, CA 94947
T 415 / 382-3444
F 415 / 382-3450
www.millerpac.com

BORING LOG		Drawn <u> </u> Checked <u>RCA</u>	A-3 FIGURE
Adobe Road Winery Petaluma, California			
Project No. 2379.001	Date: 11/18/2016		

		BORING 1								
DEPTH meters feet	SAMPLE	SYMBOL (3)	EQUIPMENT: Truck-Mounted B54 Drill Rig with 6-inch hollow stem auger		BLOWS / FOOT (1)	DRY UNIT WEIGHT pcf (2)	MOISTURE CONTENT (%)	SHEAR STRENGTH psf (3)	OTHER TEST DATA	OTHER TEST DATA
			DATE: 11/14/2016							
			ELEVATION: 10 - feet (+/-)*							
			*REFERENCE: ALTA Suvey by Cinquini and Passarino, Inc. dated February, 2016							
20			CLAY with Sand (CH) brown, wet, stiff, medium to high plasticity [Estuarine Deposits]							
7										
25										
8			CLAYSTONE gray-brown, wet, weak to friable, highly to completely weathered [Bedrock]		20		43.4			
9										
30										
10					32		34.2			
35			Boring terminated at 34.5 feet Groundwater encountered at 6 feet below ground surface during drilling.							
11										
12										
40										






NOTES: (1) UNCORRECTED FIELD BLOW COUNTS
(2) METRIC EQUIVALENT DRY UNIT WEIGHT $\text{kN/m}^3 = 0.1571 \times \text{DRY UNIT WEIGHT (pcf)}$
(3) METRIC EQUIVALENT STRENGTH $(\text{kPa}) = 0.0479 \times \text{STRENGTH (psf)}$
(4) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

 <p>A CALIFORNIA CORPORATION, © 2016, ALL RIGHTS RESERVED FILE: 2379.001 BL.dwg</p>	504 Redwood Blvd. Suite 220 Novato, CA 94947 T 415 / 382-3444 F 415 / 382-3450 www.millerpac.com	BORING LOG		Drawn <u>RCA</u> Checked _____	
	Adobe Road Winery Petaluma, California		Project No. 2379.001 Date: 11/18/2016		

CPTS BY MILLER PACIFIC, 2011

CPT: CPT-01 - Total depth: 70.01 (ft)

Project: Petaluma Trestle Rehabilitation



- SBT legend**
- 1. Sensitive fine grained
 - 2. Organic material
 - 3. Clay
 - 4. Clay & silty clay
 - 5. Clay & silty clay
 - 6. Sandy silt & clayey silt
 - 7. Silty sand & sandy silt
 - 8. Sand & silty sand
 - 9. Sand
 - 10. Sand
 - 11. Very dense/stiff soil
 - 12. Very dense/stiff soil

CPeT v.1.5.3.0 - CPTU data presentation & interpretation software - Report created on: 9/19/2011, 4:19:10 PM
 Project file: H:\Jobs\1206-1299\1206_13\CPT\1206_13_CPT.cpt

Miller Pacific
ENGINEERING GROUP






504 Redwood Blvd.
Suite 220
Novato, CA 94947
T 415 / 382-3444
F 415 / 382-3450
www.millerpac.com

CPT DATA LOGS

Petaluma Trestle Rehabilitation
Petaluma, California

Drawn: JTO
Checked:

A-4
FIGURE



SBT legend

- 1. Sensitive fine grained
- 2. Organic material
- 3. Clay
- 4. Clay & silty clay
- 5. Clay & silty clay
- 6. Sandy silt & clayey silt
- 7. Silty sand & sandy silt
- 8. Sand & silty sand
- 9. Sand
- 10. Sand
- 11. Very dense/stiff soil
- 12. Very dense/stiff soil

Miller Pacific
ENGINEERING GROUP

504 Redwood Blvd.
Suite 220
Novato, CA 94947
T 415 / 382-3444
F 415 / 382-3450
www.millerpac.com

CPT DATA LOGS

Petaluma Trestle Rehabilitation
Petaluma, California

Drawn JTO
Checked

A-6
FIGURE

BORINGS BY MILLER PACIFIC, 2004

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters DEPTH feet	SAMPLE	SYMBOL (3)	BORING 1	
								EQUIPMENT: AT-600 Drill Rig	DATE: 4/24/03 ELEVATION: +12 feet *REFERENCE: McNear Peninsula Phase I Implementation, NAVD88, 12/02/02
		30	19.5	97	0 - 0			SILTY CLAY (CL) w/ SAND (FILL) medium olive-brown, moist, medium stiff, low plasticity, contains white shell fragments	
		25	14.5	107	-1 5			SANDY CLAY (CL) w/ GRAVEL (FILL) dark brown, moist, medium stiff, low plasticity	
	560 (UC)	12	40.9	79	-2 10			CLAYEY SILT (MH-CH) w/ GRAVEL (FILL) dark gray to black, moist, soft to medium stiff, high plasticity (bay mud)	
	85 (UC)	9	25.7	104	-3 4			SILTY CLAY (CL) w/ SAND mottled light gray and blue, moist, medium stiff, medium plasticity	
	1095 (UC)	27	24.8	99	-5 6 20			Bottom of hole at 19.5 feet Groundwater at 15 feet	

NOTES: (1) METRIC EQUIVALENT STRENGTH (kPa) = 0.0479 x STRENGTH (psf)
(2) METRIC EQUIVALENT DRY UNIT WEIGHT kN/m³ = 0.1571 x DRY UNIT WEIGHT (pcf)
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

FILE: 1039.01BL1.dwg
COPYRIGHT 2002, MILLER PACIFIC ENGINEERING GROUP

Miller Pacific
ENGINEERING GROUP

BORING LOG
Petaluma McNear
Petaluma, California

3

Project No. 1039.01

Date 7/09/03

Approved By: *SJS*

Figure

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH meters feet	SAMPLE	SYMBOL (3)	BORING 2	
								EQUIPMENT: Drill Rig AT-600	DATE: 4/24/03
					0 - 0			SILTY CLAY w/ SAND (CL) (FILL) dark brown, moist, medium plasticity, medium stiff, contains roots	
	1845 (UC)	19	28.9	80	-1				
		51	29.4	87	5			same material w/ gravel, lighter brown, stiff	
	410 (UC)	26	17.9	107	-2			CLAYEY SAND (SC) dark olive brown, very moist, dense	
					10			same material w/ interbedded bay mud, dark gray-blue	
	325 (UC)	13	24.3	96	-3			CLAYEY SILT (MH-CH) dark gray-blue, moist, high plasticity, soft, organics (roots) (bay mud)	
					15			same material w/ interbedded sand	
	405 (UC)	12	56.7	64	-5				
								same material w/o interbedded sand, yellow limonite (iron oxide) staining	
	485 (UC)	19	70.2	57	-6				
					20			Bottom of hole at 20 feet Groundwater at 18 feet	

NOTES: (1) METRIC EQUIVALENT STRENGTH (kPa) = 0.0479 x STRENGTH (psf)
(2) METRIC EQUIVALENT DRY UNIT WEIGHT kN/m³ = 0.1571 x DRY UNIT WEIGHT (pcf)
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

FILE: 1039.01BL1.dwg
COPYRIGHT 2002, MILLER PACIFIC ENGINEERING GROUP

Miller Pacific
ENGINEERING GROUP

BORING LOG
Petaluma McNear
Petaluma, California

4

Project No. 1039.01

Date 7/09/03

Approved By: *YTS*

Figure

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH meters feet	SAMPLE	SYMBOL (3)	<p align="center">BORING 3</p> <p>EQUIPMENT: AT-600 Drill Rig</p> <p>DATE: 4/24/03</p> <p>ELEVATION: +12 feet</p> <p>*REFERENCE: McNear Peninsula Phase I Implementation, NAVD88, 12/02/02</p>
		33	0.0	000	0 - 0			CLAYEY SILT (ML) mottled white-olive brown, slightly moist, dense, contains white shell fragments
		30	17.2	107	-1			CLAYEY SAND (SC) mottled dark brown-orange, coarse sand, contains white shell fragments and foam rubber debris
		22	23.1	97	-2			CLAYEY SAND (SC) olive brown, moist, medium dense
					-3			SILTY CLAY (CL) dark olive-brown, medium to high plasticity, medium stiff, contains small gravel and foam rubber debris
					-4			Bottom of hole at 6.5 feet No groundwater encountered
					-5			
					-6			

NOTES: (1) METRIC EQUIVALENT STRENGTH (kPa) = 0.0479 x STRENGTH (psf)
(2) METRIC EQUIVALENT DRY UNIT WEIGHT kN/m³ = 0.1571 x DRY UNIT WEIGHT (pcf)
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

FILE: 1039.01BL1.dwg
COPYRIGHT 2002, MILLER PACIFIC ENGINEERING GROUP

Miller Pacific
ENGINEERING GROUP

BORING LOG
Petaluma McNear
Petaluma, California

5

Project No. 1039.01

Date 7/09/03

Approved By: 

Figure

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH meters feet	SAMPLE	SYMBOL (3)	<p align="center">BORING 4</p> <p align="center">EQUIPMENT: AT-600 Drill Rig</p> <p align="center">DATE: 4/24/03</p> <p align="center">ELEVATION: +15 feet</p> <p align="center">*REFERENCE: McNear Peninsula Phase I Implementation, NAVD88, 12/02/02</p>
		30	24.7	78	0 0			CLAYEY SANDY SILT (SM) olive-brown, slightly moist, contains small rounded gravel
		51	18.1	81	-1 5			same material, less gravel, some organics (roots)
	460 (UC)	51	18.1	81	-2			SILTY CLAY (MH-CH) dark gray-blue, moist, high plasticity, stiff, contains organics (roots)
					-3 10			Bottom of hole at 8.5 feet No groundwater encountered
					-4 15			
					-5			
					-6 20			

NOTES: (1) METRIC EQUIVALENT STRENGTH (kPa) = 0.0479 x STRENGTH (psf)
(2) METRIC EQUIVALENT DRY UNIT WEIGHT kN/m³ = 0.1571 x DRY UNIT WEIGHT (pcf)
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

FILE: 1039.01BL1.dwg
COPYRIGHT 2002, MILLER PACIFIC ENGINEERING GROUP

Miller Pacific
ENGINEERING GROUP

BORING LOG
Petaluma McNear
Petaluma, California

6

Project No. 1039.01

Date 7/09/03

Approved By: *YJS*

Figure

BORINGS BY MILLER PACIFIC, 1999

					BORING 3	
OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH meters feet	SAMPLE SYMBOL (3)
					0	
					0	
		34	6.5	103		3 inches asphalt concrete, 6 inches aggregate base
						SANDY GRAVEL (GM) moist, medium dense to dense, brown (Fill)
		16	5.8	109	1	
					5	POORLY-GRADED SAND (SP) moist, medium dense, brown (Trench Sand)
					2	
		17	22.9	103	3	CLAYEY SAND (SC) moist, medium dense, dark gray (Fill)
					10	
						Bottom at 10.5 feet, no water encountered
					4	
					15	
					5	
					6	
					20	

EQUIPMENT: 6-inch Solid Auger
 DATE: February 5, 1999
 ELEVATION: +12.6 Feet*
 *REFERENCE: Winzler & Kelly, Topographic Map, 1999

NOTES: (1) METRIC EQUIVALENT STRENGTH (kPa) = 0.0479 x STRENGTH (psf)
 (2) METRIC EQUIVALENT DRY UNIT WEIGHT kN/m³ = 0.1571 x DRY UNIT WEIGHT (pcf)
 (3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

FILE: 24319B3A.DW2
 COPYRIGHT 1998, MILLER PACIFIC ENGINEERING GROUP

Miller Pacific
 ENGINEERING GROUP

BORING LOG
 NWP Railroad Mainline Bridge
 Petaluma, California

A-5

Project 243 10 Date 2/22/99 Approved

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH		SAMPLE	SYMBOL (3)	BORING 4	
					meters	feet			EQUIPMENT: 6-inch Solid Auger	DATE: February 5, 1999
					0	0			ELEVATION: +13.3 Feet*	
									*REFERENCE: Winzler & Kelly, Topographic Map, 1999	
									2 inches asphalt concrete, 4 inches aggregate base	
		50/2"	7.9	106					GRAVELLY SAND (SW) moist, very, dark brown with gravels to 1-1/2 inch (Fill)	
		57	19.5	104	1				CLAYEY SAND (SC) moist, very dense, mottled rust and brown (Alluvium)	
		35	19.1	103	2				grades to fine sand with trace of clayey fines, moist to wet, medium dense to dense	
		57	18.0	106	3	10			Bottom at 10.5 feet, no water encountered	
					4					
					15					
					5					
					6	20				

NOTES: (1) METRIC EQUIVALENT STRENGTH (kPa) = 0.0479 x STRENGTH (psf)
(2) METRIC EQUIVALENT DRY UNIT WEIGHT kN/m³ = 0.1571 x DRY UNIT WEIGHT (pcf)
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

FILE: 24319B4A.DW2
COPYRIGHT 1998, MILLER PACIFIC ENGINEERING GROUP

Miller Pacific
ENGINEERING GROUP

BORING LOG
NWP Railroad Mainline Bridge
Petaluma, California

A-6

Project No. 243.19

Date 2/26/99

Approved By: *AS*

Figure

BORINGS AND CPTS BY MILLER PACIFIC, 1996

SHEAR STRENGTH psf	BLOWS PER FOOT	MOIST. CONT. %	DRY DENSITY pcf	DEPTH feet	BORING 3 (CONTINUED)
DS=2650 $\phi=49.0$ deg.	47	14.0	119	23-	SANDY GRAVEL (GP) drilling easy gray, wet, dense, gravels to 1/8 inch larger gravels in cuttings (1/4"+)
				25-	
	42	23.2	108	30-	SILTY SAND (SM) greenish-gray, wet, medium dense, fine sand
				35-	
	88	14.4	127	40-	drilling hard, wet, gravels in cuttings light brown, very dense, fine and coarse sand, minor silt
				45-	drilling very hard (350 psi)
					cemented sand and gravel on auger
					(continued)

FILE: 243-038.B3

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-4

Project No. 243.07

Date 06/06/96

Approved By: *SAS*

Figure

SHEAR STRENGTH psf	BLOWS PER FOOT	MOIST. CONT. %	DRY DENSITY pcf	DEPTH feet	BORING 3 (CONTINUED)
SA	64	19.7	112	46-	SILTY SAND (SM) same, cemented Bottom of Boring at 50.5 feet Groundwater Encountered at 11.0 feet While Drilling
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				-	
				55-	
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
				60-	
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
				65-	
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					
-					

FILE: 243-03C.B3

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
 Petaluma Flood Control Project
 Petaluma, California

A-5

Project No. 243.07 Date 06/06/96 Approved By: *SAS* Figure

SHEAR STRENGTH psf	BLOWS PER FOOT	MOIST. CONT. %	DRY DENSITY pcf	DEPTH feet	BORING 4	
					EQUIPMENT:	6-in. Rotary Wash
				0-		DATE: July 7, 1995
						ELEVATION: Approx. +12.3 feet
UC=1500	15	20.2	99	0-	4-in. Baserock	
				5-	SILTY CLAY (CL) drilling soft gray and olive gray, moist, medium stiff, minor fine sand grades to brown with more fine sand	
	24			5-	SANDY CLAY (CL) brown cuttings	
				10-	brown, moist, stiff, fine sand drilling soft	
UU=700 $\sigma_3=1300$	15	23.5	103	10-	SANDY SILT (ML) brown, moist to wet, stiff, fine sand, minor clay, few gravels drilling soft	
				15-	Groundwater Encountered at 16.0 feet While Drilling	
	60	16.4	113	15-	SANDY GRAVEL (GP) olive gray, wet, loose, fine and coarse sand, 60% gravels to 1/8 inch, grades more gravels (continued)	
				20-		

FILE: 243-03A.B4

M I L L E R
P A C I F I C
E N G I N E E R I N G

G R O U P

Project No. 243.07

Date 06/06/96

Approved By: SAS

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-6

Figure

					BORING 4 (CONTINUED)
SHEAR STRENGTH psf	BLOWS PER FOOT	MOIST. CONT. %	DRY DENSITY pcf	DEPTH feet	
				23-	SANDY GRAVEL (GP) slight loss of water (15-20 gallons) gravels in cuttings
				-	
				25-	
				-	
				-	
				30-	SILTY SAND (SM) light brown, wet, dense, fine sand, gravels to 1/4 inch grades more gravels drilling hard minor gravels in cuttings
	50/6"	20.3	108	-	
				-	
				-	
				35-	
				-	coarse sand, less gravels drilling hard (300 psi)
				-	
				-	
SA	61	20.2	110	40-	
				-	
				45-	
				-	

FILE: 243-038.B4

(continued)

M I L L E R
P A C I F I C
E N G I N E E R I N G

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-7

G R O U P

Project No. 243.07

Date 06/06/96

Approved By: *SAS*

Figure

SHEAR STRENGTH psf	BLOWS PER FOOT	MOIST. CONT. %	DRY DENSITY pcf	DEPTH feet	BORING 4 (CONTINUED)
				69-	SAND (SW)
				70-	
				-	GRAVELLY SAND (SP) drilling hard (300 psi) gravels in cuttings
				-	
				-	
				-	
				75-	
				-	
				-	large gravels
				-	
				80-	SILTY SAND AND SANDY SILT (SM-ML) dark gray, wet, dense, fine and coarse sand
	41	36.9	89	-	
				-	Bottom of Boring at 81.5 feet Groundwater Encountered at 16.0 feet While Drilling
				-	
				-	
				-	
				85-	
				-	
				-	
				-	
				90-	
				-	
				-	

FILE 243-03D.B4

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California


A-9

Project No. 243.07

Date 06/06/96

Approved By: *SAS*

Figure



FILE: 243B5-A.DW2
COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-10

Project No. 243.07

Date 05/28/96

Approved By: *SAS*

Figure

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters	DEPTH	feet	SAMPLE	SYMBOL (3)	BORING 5 (CONTINUED)	
			20			20					SAND (SP) no recovery	
			11	24.4		7					greenish-gray, wet, loose	
						25					losing water: ~50 gallons	
						8					SANDY GRAVEL (GP) greenish-gray, moist to wet, very dense, cemented, fine and coarse sand, rounded gravels to 1/2 inch	
			50/4"	14.9	118	9		30				
						10						
						35						
						11					SANDY GRAVEL (GP) brownish yellow, wet, very dense, fine and coarse sand, rounded gravels to 1/2 inch, large gravels to 1.5 inches	
						12						
						40						(continued)

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243B5-B.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-11

Project No. **243.07**

Date **05/28/96**

Approved By: **SAS**

Figure

						BORING 5 (CONTINUED)	
OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters feet	DEPTH	SAMPLE SYMBOL (3)
		50/5"	10.4		40		
					13		
					45		
					14		
					15		
		50/2"	12.1	108	50		
					16		
					55		
					17		
					18		
					60		

SANDY GRAVEL (GP)
brownish yellow, wet, very dense, fine and coarse sand, rounded gravels to 1/2 inch, large gravels to 1.5 inches

large gravels, drilling hard

drilling eases

less sands, gravels to 1/4 inch

large gravels

(continued)

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243B5-C.DW2

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters	DEPTH	feet	SAMPLE	SYMBOL (3)	BORING 5 (CONTINUED)	
			50/3"	12.4	125	60						SANDY GRAVEL (GP) light brown, wet, very dense, cemented, fine and coarse sand, gravels to 1/8 inch
						19						large gravels
						65						drilling eases
						20						large gravels
			94/9"	28.0		21						SILTSTONE gray, highly weathered, moderately strong, moderately hard
						70						drilling very hard
						22						
			62	29.6 31.0	90 90	75						
						23						
						24						Bottom of Boring at 77.5 feet
						80						Groundwater Observed at 19.0 feet During Drilling

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243B5-D.DW2

MILLER
PACIFIC
ENGINEERING
GROUP

BORING LOG
Petaluma Flood Control Project
Petaluma, California


A-13

Project No. 243.07

Date 05/28/96

Approved By: *SAS*

Figure



FILE: 24387-A.DW2
COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-17

G R O U P

Project No. **243.07**

Date **05/28/96**

Approved By: **SAS**

Figure

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters	DEPTH	feet	SAMPLE	SYMBOL (3)	BORING 7 (CONTINUED)	
SA	19	23.4	105	20	7	25	8	9	30	10	35	SILTY SAND (SM) light brown, wet, loose, fine sand
												8
	50/4"	9.3	132									less gravels
												more gravels
												(continued)

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243B7-B.DWG2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-18

Project No. 243.07

Date 05/28/96

Approved By: *SAS*

Figure

BORING 7 (CONTINUED)						
OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters feet	SAMPLE SYMBOL (3)
SA	2690 (DS)	50/3"	12.4	125	40	
					13	
					45	
		88/11"	12.1	108	14	SAND (SP) WITH GRAVELS light brown, wet, dense, fine and coarse sand, minor gravels to 1/8 inch
					15	
					50	
					16	losing water, ~40 gallons
					55	
					17	SANDY GRAVEL (GP) light brown, wet, very dense
					18	
					60	

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
 (2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
 (3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
 FILE: 24387-C.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
 Petaluma Flood Control Project
 Petaluma, California

A-19

G R O U P

Project No. **243.07**

Date **05/28/96**

Approved By: **SAS**

Figure

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters feet DEPTH	SAMPLE	SYMBOL (3)	BORING 7 (CONTINUED)
					60			<p>SANDY GRAVEL (GP) drilling rate: 5 minutes/foot</p> <p>SILTSTONE dark gray, highly weathered, hard, moderately strong</p> <p>Bottom of Boring at 66.5 feet</p> <p>Groundwater Observed at 14.0 feet 3.5 Hours After Drilling</p>
		42	35.1	82	19			
					65 20			
					70			
					75			
					23			
					24			
					80			

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243B7-D.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-20

G R O U P

Project No. **243.07**

Date **05/28/96**

Approved By: **SAS**

Figure

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH meters feet	SAMPLE	SYMBOL (3)	BORING 7 (CONTINUED)
					60			<p>SANDY GRAVEL (GP) drilling rate: 5 minutes/foot</p> <p>SILTSTONE dark gray, highly weathered, hard, moderately strong</p> <p>Bottom of Boring at 66.5 feet</p> <p>Groundwater Observed at 14.0 feet During Drilling</p>
		42	35.1	82	19			
					65 20			
					70			
					75			
					23			
					24			
					80			

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 24387-D.DW2

**MILLER
PACIFIC
ENGINEERING
GROUP**

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-20

GROUP

Project No. 243.07

Date 05/28/96

Approved By: *SAS*

Figure

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	DEPTH 0 meters 0 feet	SAMPLE	SYMBOL (3)	BORING 10	
									EQUIPMENT: 3-inch Solid Augers DATE: May 22, 1996 ELEVATION: +13.3 Feet*	
									*REFERENCE: Winzler & Kelly Topographic Map	
		560 (UC)	11	22.3	99	0			SANDY CLAY (CL) brown, moist, soft, minor gravels to 1/2 inch	
		860 (UC)	14	21.4	97	1			brown to gray, medium stiff, fine sand	
		(UC) 280				2			SILTY CLAY (CH) gray, moist, soft to medium stiff, roots	
		410 (UU)	11	34.7	84					
		$\sigma_3=800$		24.5	92					
		1000 (UC)	23	27.3	93	3			medium stiff, petroleum odor	
						4				
		1500 (UC)	44	20.5	106	5			Groundwater Observed at 15.0 Feet During Drilling	
						6			SILTY CLAY WITH SAND (CL) mottled light gray to light brown, moist, very stiff, fine sand	
						20			(continued)	

FILE: 243B10-A.DW2
COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

MILLER
PACIFIC
ENGINEERING
GROUP

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-26

GROUP

Project No. 243.07

Date 05/28/96

Approved By: *SAS*

Figure

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters feet	DEPTH	SAMPLE	SYMBOL (3)	BORING 10 (CONTINUED)	
		2000 (UC)	22	11.5	119	20				SILTY CLAY WITH SAND (CL) greenish gray, moist, stiff, gravels to 1/2 inch	
						7				hole caved	
						25				SILTY SAND WITH GRAVELS (SM)	
						8				wet, gravels	
			50/4"			9				no sample recovered	
						30					
						10					
						35					
						11				Bottom of Boring at 36.0 feet	
						12				Groundwater Observed at 15.0 feet Immediately After Drilling	
						40					

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243B10-B.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-27

G R O U P

Project No. **243.07**

Date **05/28/96**

Approved By: **SAS**


Figure

V B I

Operator : VIRGIL A. BAKER
 Location : CPT-3

CPT Date : 08-27-95 10:41
 Cone Used : HO 322 -U2

Sounding : 88Z065 Pg 1 / 1
 Job No. : 95-041



M I L L E R
 P A C I F I C
 E N G I N E E R I N G
 G R O U P

CPT-3 FIELD DATA
 Petaluma Flood Control Project
 Petaluma, California

A-46

Project No. 243.07

Date 06/07/96

Approved By: *SAS*


Figure

V B I

Operator : VIRGIL A. BAKER
 Location : CPT-4

CPT Date : 08-27-88 12:18
 Cone Used : HD 322 -U2

Sounding : 86Z086 Pg 1 / 1
 Job No. : 88-041



Max Depth : 40.82 ft

Depth Increment : .05 m

M I L L E R
P A C I F I C
E N G I N E E R I N G

CPT-4 FIELD DATA
 Petaluma Flood Control Project
 Petaluma, California

A-47

G R O U P


Project No. 243.07

Date 06/07/96


Approved By: *SAS*

Figure

Rf Zone vs Depth



SPT N1 Blow Counts vs. Depth



MILLER
PACIFIC
ENGINEERING

CPT INTERPRETED DATA
Petaluma Flood Control Project
Petaluma, California

A-48

GROUP


Project No. 243.07

Date 06/07/96


Approved By: SAC

Figure

Friction Angle vs. Depth



Undrained Shear Strength vs. Depth



M I L L E R
P A C I F I C
E N G I N E E R I N G

CPT INTERPRETED DATA
 Petaluma Flood Control Project
 Petaluma, California

A-49


G R O U P

Project No. **243.07**

Date **06/07/96**

Approved By: *STs*

Figure



SYMBOL	SAMPLE SOURCE	CLASSIFICATION	TOTAL STRESS (ksf)		EFFECTIVE STRESS (ksf)	
			C	ϕ	C'	ϕ'
-----	BORING 4 14.5 feet	SANDY SILT (ML) brown, fine sand	0.70	- °	-	- °
- . - . -	BORING 5 5.5 feet	CLAYEY SAND (SC) olive gray, fine sand	0.69	- °	-	- °
.....	BORING 6 5.5 feet	SANDY SILT (ML) dark brown, fine sand	0.99	- °	-	- °

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 2437TR11.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G

TRIAXIAL COMPRESSION TEST
Petaluma Flood Control Project
Petaluma, California

A-50


G R O U P

Project No. 243.07

Date 06/06/96

Approved By: *STJ*

Figure



SYMBOL	SAMPLE SOURCE	CLASSIFICATION	TOTAL STRESS (ksf)		EFFECTIVE STRESS (ksf)	
			C	ϕ	C'	ϕ'
-----	BORING 10 8.0 feet	SILTY CLAY (CL) brown, minor gravels	0.41	- °	-	- °
- · - · -	BORING 11 5.0 feet	SILTY SAND (SM) brown, fine sand	0.75	- °	-	- °

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 2437TRI2.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G

TRIAxIAL COMPRESSION TEST
Petaluma Flood Control Project
Petaluma, California

A-51


G R O U P

Project No. 243.07

Date 06/06/96

Approved By: *SAS*

Figure



SYMBOL	SAMPLE SOURCE	CLASSIFICATION	NORMAL STRESS (ksf)	RESIDUAL STRENGTH (ksf)	EFFECTIVE STRESS (ksf)	
					C'	ϕ'
— ○ —	BORING 3 24.5 feet	SANDY GRAVEL (GP) gray, gravels to 1/8 inch	2.3	2.7	0	49.0°
— ◻ —	BORING 7 40.5 feet	SAND (SW-SM) light brown, coarse sand	3.0	2.7	0	42.0°
— ◆ —	BORING 8 5.5 feet	SILTY SAND (SM) dark brown, fine sand	0.6	0.5	0	40.0°

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243-7ds1.dwg2

M I L L E R
P A C I F I C
E N G I N E E R I N G

DIRECT SHEAR TEST
Petaluma Flood Control Project
Petaluma, California

A-52


G R O U P

Project No. 243.07

Date 06/07/96

Approved By: *SAS*

Figure



SYMBOL	SAMPLE SOURCE	CLASSIFICATION
---△---	BORING 3 49.5 feet	SILTY SAND (SM)
---○---	BORING 4 41.5 feet	SILTY SAND (SM)
---□---	BORING 4 61 feet	WELL-GRADED SAND (SW)

FILE: 243-7SA1.DW2

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP

MILLER
PACIFIC
ENGINEERING

SIEVE ANALYSIS
Petaluma River Flood Control
Petaluma, California

A-55

GROUP

Project No. 243.07

Date 06/07/96

Approved By: *SAS*

Figure

BORINGS AND BY ARMY CORP, 1994

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters	DEPTH	feet	SAMPLE	SYMBOL (3)	COE BORING PR-11	
		1700 (DS)	7			0	0	0			EQUIPMENT: 8-inch Rotary Wash DATE: April 10, 1990 ELEVATION: +13.5 Feet*	
											*REFERENCE: Winzler and Kelly Topographic Map	
											CLAYEY SAND WITH GRAVEL (SC) very dark grayish brown, dry, medium and coarse sand, 15% clay, 15% angular gravel to 3/4 inch dia.	
											POORLY GRADED SAND (SP) dark grayish brown, moist, medium sand	
											POORLY GRADED SAND (SP) black, medium sand, 10% clay	
											SILTY/CLAYEY SAND (SM/SC) very dark gray, moist to wet, medium sand, 20% clay	
			6								(continued)	

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243CE11A.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

CORPS OF ENGINEERS BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-34

Project No. **243.07** Date **06/10/96** Approved By: **SAS** Figure

COE BORING PR-11 (CONTINUED)						
OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters feet	SAMPLE SYMBOL (3)
					20	
					7	
		40			25	
					8	
					9	
	2400 (DS)	33			30	
					10	
					35	
		51			11	
					12	
					40	

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243CE11B.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

CORPS OF ENGINEERS BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-35

G R O U P

Project No. 243.07

Date 06/10/96

Approved By:

SAS

Figure

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters	DEPTH	feet	SAMPLE	SYMBOL (3)	COE BORING PR-11 (CONTINUED)
		2200 (DS)	65/6"			40					POORLY GRADED SAND (SP) 10% coarse sand
						13					
						45					
						14					interbeds of well graded sand, 15% coarse sand, 10% subrounded gravel to 3/8-inch dia.
						15					
						50					
						16					
						55					3-inch interbed of well graded sand, 50% coarse sand, 30% medium sand, 10% gravel
						17					
						18					interbed of well graded sand, 25% medium sand, 25% coarse sand, 25% sub-rounded gravel to 1/8-inch dia.
						60					

(continued)

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243CE11C.DWG2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

CORPS OF ENGINEERS BORING LOG
Petaluma Flood Control Project
Petaluma, California


A-36

Project No. **243.07**

Date **05/28/96**

Approved By: **SAS**

Figure

OTHER TEST DATA	UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters feet DEPTH	SAMPLE SYMBOL (3)	COE BORING PR-11 (CONTINUED)
		67/11"			60		POORLY GRADED SAND (SP) interbed of well graded sand, 25% medium sand, 25% coarse sand, 25% sub-rounded gravel to 1/8-inch dia.
		72/11"			19		WELL GRADED SAND (SW) grayish brown and light olive brown, wet, 40% medium sand, 40% coarse sand, 15% rounded gravels to 0.5-inch diameter, 5% clay
		72/11"			65		
		72/11"			20		
		72/11"			21		poorly graded sand, grayish brown, wet, medium and fine sand
		72/11"			70		
		72/11"			22		
		72/11"			21		4-inch interbed of well graded sand with gravel, 60% coarse sand, 30% medium sand, 20% gravel
		85/11"			75		
		85/11"			23		
		85/11"			24		poorly graded sand, light olive brown, wet, medium sand, medium compaction
					80		SILTSTONE (continued)

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243CE11D.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

CORPS OF ENIGNEERS BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-37

Project No. **243.07** Date **06/10/96** Approved By: **SAS** Figure

OTHER TEST DATA		UNDRAINED SHEAR STRENGTH psf (1)	BLOWS PER FOOT	MOISTURE CONTENT (%)	DRY UNIT WEIGHT pcf (2)	meters	DEPTH	feet	SAMPLE	SYMBOL (3)	COE BORING PR-11 (CONTINUED)	
			83/11"			80					SILTSTONE light olive brown, dry, strong compaction	
						25					POORLY GRADED SAND (SP) light olive brown, wet, 80% medium sand, 20% fine sand, weak compaction	
			63			85					POORLY GRADED SAND (SP) light blue gray, wet, medium sand, 10% fine sand, 10% clay, trace coarse sand	
						26					dark greenish gray, dry, 30% clay, low plasticity, medium compaction	
						27						
						90						
						28						
						29						
			50/6"			95					LEAN CLAY (CL) dark greenish gray, very moist, clay, 20% silt, firm	
						100					Bottom of Boring at 100 feet	

NOTES: (1) METRIC EQUIVALENT STRENGTH IS 0.0479 kPa
(2) METRIC EQUIVALENT DRY UNIT WEIGHT IS 0.1571 kN/m³
(3) GRAPHIC SYMBOLS ARE ILLUSTRATIVE ONLY

COPYRIGHT 1996, MILLER PACIFIC ENGINEERING GROUP
FILE: 243CE11E.DW2

M I L L E R
P A C I F I C
E N G I N E E R I N G
G R O U P

CORPS OF ENIGNEERS BORING LOG
Petaluma Flood Control Project
Petaluma, California

A-38

Project No. **243.07**

Date **06/10/96**

Approved By: **SAS**

Figure

BOREING PR-14

DEPTH FT	CLAY MLLN	LAB	Ca	Sa	FL	LL	PI	DO	UC	N	DESCRIPTION
0											LEAN CLAY with GRAVEL and SAND Dark brown (7.5 YR 4/3) dry, clay, 25% fine sand and fine gravel
5											POORLY-GRADED SAND Light pinkish brown (10 YR 6/4) dry, fine grained
0											LEAN CLAY Very dark gray (2.5 Y 3/0) medium plasticity, soft, 20% air Decrease in air content, wet
5										7 SPT	POORLY GRADED SAND Dark gray (2.5 Y N/4) wet, fine grained
0										7 SPT	WELL-GRADED SAND Dark gray (2.5 Y N/4) wet, 80% fine to coarse sand, 10% fine subrounded gravel
5											POORLY GRADED GRAVEL wet, fine grained, subrounded to rounded sand
0											POORLY GRADED SAND POORLY light olive brown (2.5 Y 3/4) wet, 75-80% fine subrounded CLAYEY SAND with GRAVEL gravel, 10-25% fine to coarse sand, (20% air at 27.5) Pale olive (3 Y 6/3) wet, 80% fine to coarse sand, 20% clay, 20% fine gravel

BORING PR-15

9 APRIL 1990

DEPTH MLV	ELEV										DESCRIPTION		
	LAB	Ca	So	FL	LL	PI	DO	WC	N				
0												LEAN CLAY (MLL) Gray (5 YR 2.5/1), medium to coarse silt, medium plasticity, fine glass and concrete	
5												LEAN CLAY (MLL) Very dark gray (5YR 2.5 Y 1/2), medium, fine silt, medium sand, medium plasticity	
10												FAT CLAY with Sand Very dark gray (2.5 Y 4.5/1), medium plasticity, slightly silty sand	
12	CH				79	47							
15													
16	CL				71	19							
20												WELL GRADED SAND Very dark gray (2.5 Y 4.5/1), medium and coarse sand, medium plasticity	
22												SILT (SILTSTONE) Very dark gray (2.5 Y 4.5/1), silty, well compacted	
25												WELL GRADED SAND Very dark gray (5 Y 1/1), medium and coarse sand	
28											89 (12.5)		
30												73 (11)	These conditions prevail from collection banding, more poorly graded