



Community Development Department
11 English Street
Petaluma, CA 94952
<http://cityofpetaluma.org>

Building Division
Phone: (707) 778-4301
To schedule inspections: (707) 778-4479
Email: building@cityofpetaluma.org

Online Permit Portal Link: <https://petalumaca-energovweb.tylerhost.net/apps/SelfService#/home>

FOUNDATION WORK INFORMATION

The following items must be provided and/or shown on the plans submitted through the online portal. This handout can be used for new foundation work, repair to existing foundation, and foundation earthquake retrofit. This is a comprehensive (but not complete) list of items to be shown on plans. All other code compliance items will be reviewed at time of plan check and during construction by the field inspectors.

1. Provide scale on all plan sheets – see **Electronic Submittal Standards** handout
2. Provide project address on all plan sheets
3. Provide wet signature of person responsible for plans on all plan sheets
4. Provide floor/foundation plan showing:
 - a. Shape of floor/foundation
 - b. Location of all work
 - c. Provide references to details, i.e. detail bubbles
 - d. Location and size of foundation vents
 - e. Location and size of underfloor access
 - f. Provide positive drainage for underfloor area. Foundation walls shall have a 3-inch (minimum) diameter through wall pipe to conduct underfloor water to the outside of the building. Grade level in underfloor areas shall not be lower than exterior grade unless adequate drainage to a positive outfall is provided. Where any water will collect in the underfloor area, an approved drainage system shall be provided.
5. Provide a perimeter foundation detail showing:
 - a. Shape of foundation and stem wall
 - b. Depth of foundation below grade
 - c. Depth of footing
 - d. Width of foundation
 - e. Width of stem wall
 - f. Height of stem wall above grade
 - g. Location and size of rebar
 - h. Size and spacing of anchor bolts. Show embedment depth
 - i. Clearance between earth and wood
 - j. Detail pony/cripple wall
 - k. Grade and species of all lumber
6. Provide an interior foundation/pier detail showing:

- a. Concrete footing required to support load. Typically 16"x16"x8" deep grid and supporting only one floor
 - b. Precast pier block (typical) or post base
 - c. Foundation grade redwood or pressure treated Douglas fir post. Specify size of post and connections to girder and foundation
 - d. Dimension height of girder and floor joist above earth. Provide a minimum clearance of 12" to the girder and 18" to the floor joist
7. Show/detail all additional work, i.e. stairs, porch, decks, girders, joist, plumbing, mechanical and electrical work
 8. Show all new exterior finish material, if any, or add note to plans "All exterior wall finish material to match the existing."
 9. If the new foundation will raise the height of the house, show new height of the house. A note can be added to the plans stating, "Height of house to remain the same," or "Height of house to be raised _____ inches."
 10. If the work you propose to do is "Earthquake Retrofit," the Building Division recommends that you access the Association of Bay Area Governments (ABAG) website, located at www.abag.ca.gov for information and a standard plan set for residential seismic retrofitting.
 11. All construction shall conform to the 2019 California Building Code, 2019 California Mechanical Code, 2019 California Plumbing Code and the 2019 California Electrical Code