



STREET TYPE	W1	W2	W3
LOCAL STREET	60'	12'	18'
LOCAL STREET	56'	10'	18'
LOCAL COLLECTOR STREET	60'	10'	20'
LOCAL COLLECTOR STREET	56'	8'	20'

- ① LOCAL AND COLLECTOR STREETS ARE TYPICALLY CONSTRUCTED USING 6" AND 12" FULL DEPTH ASHALT CONCRETE RESPECTIVELY. IF CONCRETE PAVEMENT IS PRESENT, 6" THICK CLASS 560-A-3250 PCC SHALL BE CONSTRUCTED.
- ② THICKNESS OF STRUCTURAL SECTION SHALL BE BASED ON TRAFFIC INDEX AND SOIL "R" VALUE DETERMINATIONS. PAVEMENT DESIGN SHALL BE SUBMITTED TO THE CITY FOR APPROVAL.
- ③ WHERE TRANSVERSE ROADWAY SLOPE IS USED, THE CROWN HEIGHT SHALL BE NOT LESS THAN 0.40' ABOVE THE GUTTER FLOW LINE ON THE HIGH SIDE.
- ④ SEE STD. PLAN NO. 1104 FOR SIDEWALK DETAIL.
- ⑤ SEE STD. PLAN NO. 1101 FOR CURB AND GUTTER DETAIL.
- ⑥ MAXIMUM STREET GRADE BREAK SHALL BE 0.5%, OTHERWISE VERTICAL CURVE SHALL BE USED.



APPROVED: *[Signature]* DATE: 3/22/16
CITY ENGINEER

CITY OF SANTA ANA
PUBLIC WORKS AGENCY

DATE	REVISION

TYPICAL SECTION
LOCAL STREETS

STD. PLAN
NUMBER
1102