


CURB FACE	X
UNDER 6"	3'
6" TO < 8"	3'
8" TO < 10"	4'
10" TO < 12"	5'
12"	6'

DRIVEWAY (DRWY) USE	T	A	W
COMMERCIAL	8"	50' MAX.	40' MAX.
RESIDENTIAL	6"	34' MAX.	24' MAX.

*A>W UNLESS NOTED OTHERWISE ON PLANS

**	CONDITION	ADJUSTMENT
1)	SLOPE ≤ 10% MAX	WIDTH SHALL BE 4'
2)	SLOPE > 10% MAX	REDUCE WIDTH TO 3'
3)	SLOPE > 10% MAX WITH 3' WIDTH	INCREASE 2% SLOPE TO 5% MAX
4)	RIGHT OF ENTRY REQUIRED	RIGHT OF ENTRY REQUIRED AS DIRECTED BY ENGINEER

- NOTES**
- SEE SECTION 33-34 OF SANTA ANA MUNICIPAL CODE FOR ORDINANCE FOR DRIVEWAYS.
 - USE CASE 1 WHERE "Y" IS GREATER THAN OR EQUAL 12'. USE CASE 2 WHERE "Y" IS LESS THAN 12'.
 - CONCRETE SHALL BE CLASS 520-C-2500.



APPROVED: *[Signature]* DATE: 3/22/16
CITY ENGINEER

CITY OF SANTA ANA
PUBLIC WORKS AGENCY

DATE	REVISION

DRIVEWAY APPROACH

STD. PLAN NUMBER 1112