



▨ LIMITS OF ASPHALT CONCRETE PAVEMENT RESTORATION

■ TRENCH OR POTHOLE

GENERAL NOTES:

A. ASPHALT CONCRETE RESTORATION FOR STREETS UNDER MORATORIUM AS DESCRIBED IN SAMC 33-54 IS AS SHOWN.

APPROVED: _____ DATE: 08/23/23

[Signature]
CITY ENGINEER

CITY OF SANTA ANA
PUBLIC WORKS AGENCY



DATE		REVISION
08/23	J.G.	REVISED GRIND DEPTH

RESTORATION FOR
MORATORIUM STREETS

STD. PLAN
NUMBER
1151
SHEET 1 OF 2

GENERAL NOTES CONTINUED:

- B. RESTORATION SHALL CONSIST OF GRINDING AND OVERLAYING TO A DEPTH OF 3" OF ASPHALT CONCRETE IN ADDITION TO RESTORATION REQUIRED BY CITY STANDARD 1150.
- C. GAPS LESS THAN 100' BETWEEN GRIND AND OVERLAY EDGES SHALL BE INCLUDED IN THE RESTORATION.
- D. POTHOLES USING A 10" DIAMETER OR LESS ROUND VACUUM CORE MAY NOT REQUIRE A GRIND AND OVERLAY, AT THE DISCRETION OF THE CITY ENGINEER'S FIELD REPRESENTATIVE.
- E. IF THE EDGE OF TRENCH WITHIN 2' OF A LANE LINE, THE GRIND AND OVERLAY SHALL EXTEND TO COVER THE ENTIRE NEIGHBORHOOD LANE.
- F. RESTORATION FOR ANGLED TRENCHES ARE TO BE SQUARED OFF AS SHOWN ON PAGE 1.
- G. IN LIEU OF GRIND AND OVERLAY, ASPHALT BEYOND THE LIMITS OF THE RESTORATION REQUIRED BY CITY STANDARD 1150 MAY BE REPLACED AT FULL DEPTH.
- H. IN PORTLAND CEMENT CONCRETE PAVED STREETS, THE RESTORATION LIMITS ARE DETERMINED USING CITY STANDARD 1150.

APPROVED: _____ DATE: 08/23/23

[Signature]

CITY ENGINEER

**CITY OF SANTA ANA
PUBLIC WORKS AGENCY**



**RESTORATION FOR
MORATORIUM STREETS**

**STD. PLAN
NUMBER
1151
SHEET 2 OF 2**

DATE		REVISION
08/23	J.G.	REVISED GRIND DEPTH