



ALL UNITS ARE IN INCHES.

NOTES:

1. Color of legends, letters, borders, etc. shall be white on a screened brown background. Unless noted otherwise, same message shall be on both sides of the sign.
2. The retroreflective material shall meet or exceed ASTM D 4956 Type IX sheeting requirements.
3. All signs shall have graffiti coating or film such as 3M 1160 Overlay or City approved equivalent.
4. Sign blade shall be flat aluminum and 0.10 inches thick. Predrilled holes are not required.
5. Length of sign shall be according to content with no excessive empty spaces.
6. Minor vertical adjustment may be made to spacing between street name and border to accommodate letters g, j, p, q and y.
7. All signs shall have CITY OF SANTA ANA XX/20XX with the month and year the sign was manufactured in lower border of the signs.
8. All signs highest on the post shall not have holes on the top of the sign, unless directed otherwise.
9. Exception to the above requires prior approval from the City.

Acceptable Suffix Abbreviation:

Avenue	AVE	Highway	HWY
Boulevard	BLVD	Lane	LN
Center	CNTR	Loop	LP
Circle	CIR	Parkway	PKWY
Court	CT	Place	PL
Common	COM	Plaza	PLZ
Crossing	XING	Road	RD
Drive	DR	Street	ST
Expressway	EXPWY	Terrace	TER
Freeway	FRWY	Trail	TR
Glen	GLN	Way	WY

Acceptable Directional Abbreviation:

North	N
South	S
East	E
West	W
Northwest	NW
Northeast	NE
Southwest	SW
Southwest	SE

APPROVED:

DATE: 10/7/22

CITY ENGINEER

**CITY OF SANTA ANA**

**PUBLIC WORKS AGENCY**



DATE

REVISION

**CEREMONIAL  
STREET SIGN TOPPER**

**STD. PLAN  
NUMBER  
1503A**