


EXTERIOR MANHOLE CHIMNEY SEAL AS MANUFACTURED BY CRETEX OR AN APPROVED EQUAL IF SPECIFIED.

NOTES: BED FRAME IN MORTAR, INSTALL PRECAST TWO-INCH RINGS, AND PLASTER INSIDE AND OUT WITH MORTAR.

INSTALLED COST AT EXISTING LOCATIONS SHALL BE INCLUDED IN PRICE BID FOR "ADJUST FLOATING MANHOLE CASTING", OR "FURNISH & ADJUST FLOATING MANHOLE CASTING".


INSTALLATION COST AT NEW MANHOLE LOCATIONS SHALL BE INCLUDED IN THE PRICE BID FOR "MANHOLES".



CROSS SECTION OF CONNECTION TO CONICAL MANHOLE - TYPICAL

FRAMES WHEN COMPRESSED ARE 11 1/2" IN HEIGHT. SET UPPER FRAME 1 1/2" ABOVE LOWER FRAME.

WHEN INSTALLING A BOX OUT INTO EXISTING PAVEMENT, DRILL 20" LONG NO.5 REBAR 6" DEEP - 15" O.C. SEE STD. DETAIL 1206-4



CROSS SECTION

CITY OF WATFORD CITY, NORTH DAKOTA PUBLIC WORKS DEPARTMENT	
FLOATING MANHOLE CASTING DETAIL (SHEET 1 OF 2)	
APPROVED FOR PUBLICATION	DWG. NO.
City Engineer _____	1206-3
Date _____	