



- NOTE NO. 1 DRILLED IN DOWELS & NO. 4 REBAR OR 3/4" EXPANSION WITH 3/4"x24" SMOOTH DOWELS & 16" PAPER TUBES, OR 1/2" REBAR DRILLED WITH 5/8" BIT. DOWELS SHALL BE GREASED THE FULL LENGTH. ALL PAPER TUBES SHALL BE PLUGGED OR CRIMPED ON OPEN END AS DETERMINED BY THE ENGINEER. ALL JOINTS SHALL BE SEALED.
- NOTE NO. 2 CONTRACTION JOINT SCORED TO 1/3 DEPTH OF THE CONCRETE.
- NOTE NO. 3 CURB & GUTTER SHALL BE 6" & REINFORCED 10' ON EITHER SIDE OF THE INLET. ALL BARS SHALL BE 1/2" DIA. DEFORMED REINFORCING BARS. SPLICES WILL NOT BE PERMITTED.
- NOTE NO. 4 DOWELS SHALL BE SUPPORTED BY AN APPROVED SUPPORT MADE OF NO. 7 AWG WIRE.
- NOTE NO. 5 A CONTINUOUS KEYED CONSTRUCTION JOINT SHALL BE USED.

| | |
|---|---------------|
| CITY OF WATFORD CITY, NORTH DAKOTA PUBLIC WORKS DEPARTMENT | |
| MOUNTABLE CURB & GUTTER W/ INLET | |
| APPROVED FOR PUBLICATION | DWG. NO. |
| _____ City Engineer | _____ Date |
| 600-14 | |