





AVAILABLE SPONGES




ACCESSORIES



PACKAGE



TECHNICAL CHARACTERISTICS



- Sponge-machine for cleaning grout (cement based or epoxy resin) from floors: terracotta, porcelain, double-fired and single-fired tiles, marble, porphyry, natural stone, quarry tile, treaded tile, etc. during the grouting phase.
- Does not pull grout from the joints.
- Performance: 100 sq m/h for medium difficulty surfaces (800 - 1500 s.f. per hour in general).
- Sponge rollers can last from 150 to 2000 sq m (1600 - 21000 s.f.).
- Water is fed to the roller via a foam-reducing rubber belt. So, no pump is needed resulting in no clog up.
- Moisture level of the sponge roller is adjustable via the easy-to-use pressure adjustment lever.

- Separate lever adjusts the front wheels height.
- Easy-to-replace sponge roller thanks to the magnetic "quick clutch" system.
- The handle folds down for transport and storage. Also thanks to its ergonomic design, handle is fully adjustable for height and angle according to the user(s) needs.
- Die cast aluminium body reduces weight while increasing overall strength and durability.
- Easy-to-remove water-tank (15 liters/4 gal) made of impact resistant plastic to prevent breakage.
- Supplied with: sponge roller for cement based grout, anti-foaming liquid, user and maintenance.
- Sponge roller for epoxy-based grouts available as accessory.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Roller	Roller	Roller	Roller
399 ADV	8024648004529	1	230 V 50/60 Hz	Single-phase	0,16 HP / 0,12 kW	2800/3360			21 / 25
399 ADV GB	8024648009685	1	110 V 50 Hz	Single-phase	0,16 HP / 0,12 kW	2800	"Havana" sponge		21
399 ADV USA	8024648009692	1	110 V 60 Hz	Single-phase	0,16 HP / 0,12 kW	3360			25

DIMENSIONS AND WEIGHT

Part No.	Dimensions	Weight	Dimensions	Weight
BERTA ADV	65x55xh 50 cm / 25 3/8" x 21 5/8" x h 20"	29 Kg / 64 lbs	73x60xh 55 cm / 29" x 23 5/8" x h 21 5/8"	32 Kg / 70 lbs



ELECTROSPONGES