

Descriptions

- Mobilization (Maximum 5% of Contract and payment per DOTD Std. Specs table 727-1)
- Stripping of Site (4") (Spoiled Onsite)
- Common Excavation (Offsite)
- Common Embankment (Offsite)
- 7" Portland Cement Concrete Paving
- 4" Crushed Aggregate Base Course
- Biaxial Grid (BX 1100 or equivalent)
- 6" Barrier Curb
- Sidewalk (4" thick)
- Handicap Ramp
- Storm Drain Pipe (All Sizes)
- Safety End Treatment
- Catch Basins (All Types)
- Hydro-Seeding Property
- Silt Fencing
- 30# Rip-Rap
- Hay Bales at Inlets
- Signage
- Parking Striping
- Maintenance Bond (2 Year, 10% to the Owner)
- Mobilization (Maximum 5% of Contract and payment per DOTD Std. Specs table 727-1)
- 8" PVC Water Main (C-900, Class 150) (Bends Included)
- 8" PVC Water Main (DR11) (Bends Included) (Directional Bore)
- Fire hydrant assembly; double pumper type
- Water Services (Terminate 5 ft. inside lot w/PVC marker painted blue)
- Maintenance Bond (2 Year, 10% to the Owner)
- 8" SS (SDR 26) main (All Depths)
- Precast concrete manhole (All Depths); bituminous coating inside & out
- 6" Service Laterals
- Cap and Plug for Future Expansion