



SWP916TS

Compact 9-input multiswitches with dip switch to select active or passive TV gain.

| SWP916TS | |
|---------------------------------------|-----------------------------------|
| Code | 287352 |
| Inputs | 8 SAT, 1 TV |
| Taps | 16 |
| SAT | |
| Bandwidth | MHz 950-2300 |
| Positive slope gain | dB -3/1 |
| Max output level (-35dBc 2 tone) dBμV | 100 |
| SAT-SAT Isolation | dB >30 |
| TV | |
| Bandwidth | MHz Passive: 5-862 Active: 47-862 |
| Gain (Active) | dB -1 |
| Gain (Passive) | dB -21 |
| Max output level (-35dBc 2 tone) dBμV | Active TV gain: 92 |
| Return path | |
| Bandwidth | MHz Passive TV: 5-65 |
| Consumption | |
| Tap consumption | mA 50 |

| | | |
|---------------------|-------|--|
| Current consumption | mA, V | Active TV: 160, 13 Passive TV entirely powered by the receiver |
|---------------------|-------|--|

| | | |
|-----------------------------|----|----------------------------------|
| Max LNB current consumption | mA | Passive TV: 1500 Active TV: 1340 |
|-----------------------------|----|----------------------------------|

Features

| | | |
|------------|----|------------|
| Dimensions | mm | 170x190x40 |
|------------|----|------------|

| | | |
|-------------------------|----|----------|
| Dimensions power supply | mm | 90x70x45 |
|-------------------------|----|----------|

| | | |
|-----------------------|----|---------|
| Operating temperature | °C | -10÷+55 |
|-----------------------|----|---------|