

SDS No.: HKO-015L

Revision date: 25/11/2022 Ver

Version no.: 03

# SECTION 1: Identification of the substance or mixture and of the company 1.1 Product Identifier Product name : Bactigas 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses : General purpose sanitizer. It is the responsibility of the end user to ensure that the product as supplied is suitable for its intended use.

## 1.3 Details of the supplier of the safety data sheet

Supplier name	:	Linde HKO Limited
Address	:	12 Chun Yat Street, Tseung Kwan O Industrial Estate, Tseung Kwan O,
		Kowloon, Hong Kong
Phone no.	:	(852) 2372-2288
Fax no.	:	(852) 2372-2508

## 1.3 Emergency telephone number

Emergency no.	: (852) 2661 0920 (24 hours)
---------------	------------------------------



:

SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 2: Hazards identification

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Gases under pressure (Liquefied gas) : H280: Contains gas under pressure; may explode if heated.

## 2.2 Label Elements

Pictograms



Signal word	: Warning
Hazard statements	: H280: Contains gas under pressure; may explode if heated.
Precautionary statements	
General	: None
Prevention	: None
Response	: None
Storage	: P403: Store in a well-ventilated place.
Disposal	: None

## 2.3 Other hazards

None



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 3: Composition / information on ingredients

#### 3.1 Substances

Not applicable

## 3.2 Mixtures

Ingredient(s)	Chemical formula	CAS No.	EC no.	Purity
Carbon Dioxide	CO <sub>2</sub>	124-38-9	204-696-9	97%
Ethanol	$C_2H_5OH$	64-17-5	200-578-6	2.7%
Melaleuca	$C_{28}H_{60}O_4P_2S_4Zn$	68647-73-4	614-679-1	0.3%
alternifolia oil				
(Tea tree oil)				

## SECTION 4: First Aid Measures

#### 4.1 Description of first aid measures

Inhalation	: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.
	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial
	respiration if breathing stopped. Low concentrations of CO2 cause increased respiration and headache.
Eye contact	: Rinse the eye with water immediately. Remove contact lenses, if present
	and easy to do. Continue rinsing. Flush thoroughly with water for at least
	15 minutes. Get immediate medical assistance. If medical assistance is not
	immediately available, flush an additional 15 minutes.
Skin Contact	: Contact with evaporating liquid may cause frostbite or freezing of skin
Ingestion	: Ingestion is not considered a potential route of exposure.

## 4.2 Most important symptoms and effects, both acute and delayed

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

## 4.3 Immediate medical attention and special treatment needed

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

SECTION 5: Firefighting Measure	S
<b>5.1 Extinguishing media</b> Suitable extinguishing media :	Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.
<b>5.2 Special hazards arising from the s</b> None	ubstance or mixture
5.3 Advice for firefighters	
Special fire fighting procedures :	In case of fire, stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.
Special protective equipment for : firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and Self-Contained Breathing Apparatus (SCBA).

## SECTION 6: Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

## 6.2 Environmental Precautions

Prevent further leakage or spillage if safe to do so.

## 6.3 Methods and material for containment and cleaning up

Provide adequate ventilation.

## 6.4 Reference to other sections

See also sections 8 and 13.



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 7: Handling and Storage

#### 7.1 Precautions for safe handling

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place. Depressurisation of liquid CO<sub>2</sub> below approximately 5 bar can create solid CO<sub>2</sub> which may block protective devices, pipework and create dry-ice within containers. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide.

## 7.2 Conditions for safe storage, including any incompatibilities

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

## 7.3 Specific end uses

None



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 8: Exposure Controls/Personal Protection

<b>8.1 Control parameters</b> Occupational Exposure Limits Biological limits	:	Carbon Dioxide [5,000 ppm (8 hour TWA), 30,000 ppm (STEL)] Ethanol [1,000 ppm (8 hour TWA)] Source: Code of Practice on Control of Air Impurities (Chemical Substances) in the Workplace. (Published by the Labour Department, Hong Kong) No biological limits have been established for this product.
8.2 Exposure controls Appropriate engineering controls	:	Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.
Individual protection measures, such	n as	personal protective equipment.
Eye protection	:	Wear safety glasses.
Hand Protection	:	Wear leather gloves or insulated gloves.
Body protection	:	Wear safety boots.

Respiratory Protection:Where an inhalation risk exists, wear Self Contained Breathing Apparatus<br/>(SCBA) or an Air-line respirator.

SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 9: Physical and Chemical Properties

Linde

## 9.1 Information on basic physical and chemical properties

Appearance		
Physical state	:	Gas
Form	:	Liquefied gas
Colour	:	Colorless
Odour	:	Warm spicy odour
Odour Threshold	:	No data available.
рН	:	No data available.
Melting Point	:	No data available.
Boiling Point	:	No data available.
Sublimation Point	:	No data available.
Critical Temp. (°C)	:	31°C
Flash Point	:	No data available.
Evaporation Rate	:	No data available.
Flammability (solid, gas)	:	This product is not flammable
Flammability limit - upper (%)	:	No data available.
Flammability limit – lower (%)	:	No data available.
Vapour pressure	:	No data available.
Vapour density (air=1)	:	1.53 (Air = 1)
Relative density	:	No data available.
Solubility (in Water)	:	0.759 cm³/cm³
Partition coefficient (n-	:	No data available.
octanol/water)		
Autoignition Temperature	:	No data available.
Decomposition Temperature	:	No data available.
Viscosity		
Kinematic viscosity	:	No data available.
Dynamic viscosity	:	No data available.
Explosive properties	:	No data available.
Oxidising Properties	:	No data available.

#### 9.2 Other information

- Additional information
- : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.



SDS No.: HKO-015L

Revision date: 25/11/2022 Ve

Version no.: 03

## SECTION 10: Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazard other than the effects described in sub-section below.

## 10.2 Chemical Stability

Stable under normal conditions.

## 10.3 Possibility of Hazardous Reactions

None

#### 10.4 Conditions to Avoid

None

## 10.5 Incompatible Materials

No reaction with any common materials in dry or wet conditions.

## 10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 11: Toxicological Information

## 11.1 Information on toxicological effects

Acute toxicity	
Oral	<ul> <li>Based on available data, the classification criteria are not met.</li> <li>Ethanol [LD 50 (Mouse): 3450mg/kg]</li> <li>Melaleuca alternifolia oil (Tea tree oil) [LD 50 (Rat): 1900mg/kg]</li> </ul>
Inhalation	: Based on available data, the classification criteria are not met. Ethanol [LC 50 (Rat): 20000ppm/10 hours]
Dermal	: Based on available data, the classification criteria are not met.
Skin Corrosion/Irritation	: Based on available data, the classification criteria are not met.
Serious Eye Damage/Eye Irritation	: Based on available data, the classification criteria are not met.
Respiratory or Skin Sensitisation	: Based on available data, the classification criteria are not met.
Germ Cell Mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific Target Organ Toxicity	
Single Exposure	: Based on available data, the classification criteria are not met.
Repeated Exposure	: Based on available data, the classification criteria are not met.
Aspiration Hazard	: Not applicable to gases and gas mixtures.

## SECTION 12: Ecological Information

## 12.1 Toxicity

No ecological damage caused by this product.

## 12.2 Persistence and Degradability

Not expected to be persistent in the aquatic environment.

## 12.3 Bioaccumulative Potential

Bioaccumulation is not expected.

## 12.4 Mobility in Soil

Not applicable.



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## 12.5 Other Adverse Effects

No ecological damage caused by this product.

## SECTION 13: Disposal Considerations

#### 13.1 Waste treatment methods

Disposal method

: Do not discharge into any place where its accumulation could be dangerous. Cylinders should be returned to the supplier for disposal of contents.

## SECTION 14: Transport Information

## ADR/RID

14.1 UN Number	: UN 3163
14.2 UN proper shipping name	: LIQUEFIED GAS, N.O.S.
14.3 Transport Hazard Class(es)	
Class	: 2
Label(s)	: 2.2: Non-flammable, non-toxic gases
Classification Code	: 2A
Hazard No.	: 20
14.4 Packaging group	: None
14.5 Environmental hazards	: Not Applicable
14.6 Special precautions for user	: None

IMDG		
14.1 UN Number	:	UN 3163
14.2 UN proper shipping name	:	LIQUEFIED GAS, N.O.S.
14.3 Transport Hazard Class(es)		
Class	:	2.2
Label(s)	:	2.2: Non-flammable, non-toxic gases
14.4 Packaging group	:	None
14.5 Environmental hazards	:	Not Applicable
14.6 Special precautions for user	:	None



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

ΙΑΤΑ		
14.1 UN Number	:	UN 3163
14.2 UN proper shipping name	:	LIQUEFIED GAS, N.O.S.
14.3 Transport Hazard Class(es)		
Class	:	2.2
Label(s)	:	2.2: Non-flammable, non-toxic gases
14.4 Packaging group	:	None
14.5 Environmental hazards	:	Not Applicable
14.6 Special precautions for user	:	None
Other information		
Passenger and cargo aircraft	:	Allowed

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not Applicable

: Allowed

## 14.8 Additional information

Cargo aircraft only

Transport precautions: Avoid transport on vehicles where the load space is not separated from the<br/>driver's compartment. Ensure vehicle driver is aware of the potential<br/>hazards of the load and knows what to do in the event of an accident or an<br/>emergency. Before transporting product containers ensure that they are<br/>firmly secured. Ensure that the container valve is closed and not leaking.<br/>Container valve guards or caps should be in place. Ensure adequate air<br/>ventilation.

## SECTION 15: Regulatory information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Local legislation

: Dangerous Goods Ordinance (Chapter 295)



SDS No.: HKO-015L

Revision date: 25/11/2022

Version no.: 03

## SECTION 16: Other Information

Other information	material compatib adequate air ver observed. Whilst p	product in any new process or experiment, a thorough ility and safety study should be carried out. Ensure ntilation. Ensure all national/local regulations are proper care has been taken in the preparation of this lity for injury or damage resulting from its use can be
Revision date	25/11/2022	
Disclaimer		tion is believed to be correct. This information should be dependent determination of the methods to safeguard avironment.

End of document