

Report No.: MPICHCJL470377U3

MSDS Report

Sample Name
& Model

Li-ion battery 100901-1

Applicant

WS Technicals A/S

Address

Gjellerupvej 89A, 8230 Åbyhøj, Danmark



No.: MPICHCJL470377U3
Code: kmu7uk3x

Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.8 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification

Sample Name: Li-ion battery

Sample Model: 100901-1

Recommended Uses: N/A

Restrictions on Use: N/A

Supplier Name: WS Technicals A/S

Address: Gjellerupvej 89A, 8230 Åbyhøj, Danmark

Phone Number: (0045) 8861 8388

FAX: (0045) 2390 9281

E-mail: wstech@wstech.dk

Emergency Phone Number: (0045) 8861 8388

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxicity, oral (4)

Skin corrosion/irritation (2)

Serious eye damage/eye irritation (2A)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements

Hazard pictogram(s):



Signal word:

Warning

Hazard statement(s):

H302 Harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

Precautionary statement(s):

Prevention:

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty water.

P321 Specific treatment (See additional emergency instructions).

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Cobalt lithium manganese nickel oxide	182442-95-1	695-690-9	30-34
Polyvinylidene fluoride resin	24937-79-9	607-458-6	0.8-1.0

Cellulose, carboxymethyl ether	9000-11-7	618-326-2	0.2-0.3
Styrene-butadiene rubber 1500	9003-55-8	618-370-2	0.4-0.5
Carbon black	1333-86-4	215-609-9	17-19
Polypropylene	9003-07-0	618-352-4	2-3
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	1.2-1.5
Carbonic acid, dimethyl ester	616-38-6	210-478-4	2.5-3.0
Carbonic acid, ethyl methyl ester	623-53-0	613-014-2	4.0-6.0
1,3-Dioxolan-2-one	96-49-1	202-510-0	2.0-2.5
Copper	7440-50-8	231-159-6	7.0-9.0
Aluminium	7429-90-5	231-072-3	3.0-4.0
Iron	7439-89-6	231-096-4	16-19.2
Nickel	7440-02-0	231-111-4	0.9

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, CO₂, water spray or regular foam. Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150°C (302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handling must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
182442-95-1	N/A	N/A	N/A
24937-79-9	N/A	N/A	N/A
9000-11-7	N/A	N/A	N/A
9003-55-8	N/A	N/A	N/A
1333-86-4	TLV-TWA 3mg/m ³	REL-TWA 3.5mg/m ³	PEL-TWA 3.5mg/m ³
9003-07-0	N/A	N/A	N/A
21324-40-3	N/A	N/A	N/A
616-38-6	N/A	N/A	N/A
623-53-0	N/A	N/A	N/A
96-49-1	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m ³ TLV-TWA 1mg/m ³	REL-TWA 1mg/m ³ REL-TWA 0.1mg/m ³	PEL-TWA 0.1mg/m ³ PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 1mg/m ³	REL-TWA 2mg/m ³ REL-TWA 5mg/m ³ REL-TWA 10mg/m ³	PEL-TWA 5mg/m ³ PEL-TWA 15mg/m ³
7439-89-6	N/A	N/A	N/A
7440-02-0	TLV-TWA 1.5mg/m ³	REL-TWA 0.015mg/m ³	PEL-TWA 1mg/m ³

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Colour:	Black.
Physical State:	Prismatic.
Odour:	Not available.
Odour threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.
Explosion Limits (vol% in air):	Not available.
Vapour pressure, kPa at 20°C:	Not available.
Vapor density:	Not available.
Density/Relative density (water = 1):	Not available.
Solubility(ies):	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.

Viscosity: Not available.

Other information:

Voltage 14.4V

Electric capacity 14.4Ah

Electric Energy 207Wh

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
182442-95-1	No data available.
24937-79-9	No data available.
9000-11-7	No data available.
9003-55-8	No data available.
1333-86-4	No data available.
9003-07-0	No data available.
21324-40-3	No data available.
616-38-6	No data available.
623-53-0	No data available.
96-49-1	LD50 Rat (oral): 10g/kg
7440-50-8	No data available.
7429-90-5	No data available.
7439-89-6	No data available.
7440-02-0	LD50 Rat (oral): >9000mg/kg

Skin corrosion/irritation: No data available.
Serious eye damage/irritation: No data available.
Respiratory or Skin sensitization: No data available.
Germ Cell mutagenicity: No data available.
Carcinogenicity: No data available.
Reproductive toxicity: No data available.
Specific target organ toxicity-Single exposure: No data available.
Specific target organ toxicity-Repeated exposure: No data available.
Aspiration hazard: No data available.
Information on the likely routes of exposure: No data available.
Eye: No data available.
Skin: No data available.
Ingestion: No data available.
Inhalation: No data available.

Section 12 - Ecological Information

Ecological Toxicity: No data available.
Persistence and degradability: No data available.
Bioaccumulative Potential: No data available.
Mobility in Soil: No data available.
Other adverse effects: No data available.

Section 13 - Disposal Considerations


Disposal methods:
Recommendation:
Consult state, local or national regulations to ensure proper disposal.
Uncleaned packaging
Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN or ID Number

IATA

UN3480

IMDG	UN3480
Proper Shipping Name/Description	
IATA	Lithium ion batteries
IMDG	LITHIUM ION BATTERIES
Class or Div. (Sub Hazard)	
IATA	9
IMDG	9
Packing Group	
IATA	N/A
IMDG	N/A
Hazard Label	
IATA	
IMDG	
Environmental hazards	
Marine pollutant:	No
Special precautions for user	No information available.

Transport information: The Li-ion battery 100901-1 has passed the test UN38.3, according to the report ID: MPIQGOZL417057U5.

Watt-hour exceeds the standard. The goods are packaged according to the packaging Instruction 965 section IA of IATA DGR 62nd Edition for transportation, Cargo aircraft only.

Watt-hour exceeds the standard. The goods are packaged according to the special provision 230, 348, 384 of IMDG (39-18).

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Note: State of Charge (SoC) not exceeding 30% of their rated capacity. (By air, Lithium ion batteries)

Transport Fashion: By air, by sea.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDL	EINECS/ ELINCS/ NLP
182442-95-1	Listed	Listed	Listed DSL	Listed
24937-79-9	Listed	Listed	Listed DSL	Listed
9000-11-7	Listed	Listed	Listed DSL	Listed
9003-55-8	Listed	Listed	Listed DSL	Listed
1333-86-4	Listed	Listed	Listed DSL	Listed
9003-07-0	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed
616-38-6	Listed	Listed	Listed DSL	Listed
623-53-0	Listed	Listed	Listed DSL	Listed
96-49-1	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
7439-89-6	Listed	Listed	Listed DSL	Listed
7440-02-0	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Date: 2021-12-13

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);
EC: (European Commission);
ACGIH: (American Conference of Governmental Industrial Hygienists);
NIOSH: (US National Institute for Occupational Safety and Health);
OSHA: (US Occupational Safety and Health);
TLV: (Threshold Limit Value)
TWA: (Time Weighted Average);
STEL: (Short Term Exposure Limit);
PEL: (Permissible Exposure Level);
REL: (Recommended Exposure Limit);
PC-STEL: (Permissible concentration-short time exposure limit);
PC-TWA: (Permissible concentration-time weighted average);
LC50: (Lethal concentration, 50 percent kill);
LD50: (Lethal dose, 50 percent kill);
IARC: (International Agency for Research on Cancer);
EC50: (Median effective concentration);
BCF: (Bioconcentration Factor);
BOD: (Biochemical oxygen demand);
NOEC: (No observed effect concentration);
NTP: (US National Toxicology Program);
RTECS: (Registry of Toxic Effects of Chemical Substances);
IATA: (International Air Transport Association);
IMDG: (International Maritime Dangerous Goods);
TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);
TOC: (Total Organic Carbon);
TSCA: (Toxic Substances Control Act of USA);
DSL: (the Domestic Substances List of Canada);
NDSL: (the Non-domestic Substances List of Canada)

End of report